

Eaton D51519

Catalog Number: D51519

Drive Isolation Transformer, Ventilated, Dry Type Distribution, DT-3, Three-phase, PV: 230 delta, Taps: 1 at +5% FCAN, 1 at -5% FCBN, SV: 230Y/133V, 150°C, 51 kVA, Al windings, Frame: 914D, uses WS39



Photo is representative

General specifications

Product Name	Catalog Number
Eaton Drive isolation ventilated transformer	D51519
	UPC
	786680330155
Product Length/Depth	Product Height
22 in	39 in
Product Width	Product Weight
29 in	480 lb
Warranty	Certifications
Eaton Selling Policy 25-000, one (1) year UL Listed from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.	

Physical Attributes

Coil material

Aluminum

Design

DT-3

Frame

914D

Tap size

1 at +5% FCAN, 1 at -5% FCBN

Type

Dry Type Distribution, Drive Isolation Transformer

Performance Ratings

Frequency rating

60 Hz

Horsepower

40 hp

Kva Rating

51 kVA

Phase

Three-phase

Primary voltage

230 V

Secondary Voltage

230Y/133 V

Temperature rise

150 °C rise

Resources

Specifications and datasheets

[Eaton Specification Sheet - D51519](#)

Warranty guides

[Selling Policy 25-000 - Distribution and Control Products and Services](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia