SAFETY DATA SHEET

1. Identification

Product identifier **OCAL Spray Patch- White**

Other means of identification

SDS number SDS - 00026

Product code SPRAY-W

Recommended use Vinyl Resin Coating.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Company name ABB Installation Products Inc.

Address 860 Ridge Lake Blvd.
Memphis, TN 38120
US

Telephone 901-252-5000 ext.8324

E-mail Not available.

Emergency phone number CHEMTREC - 24 HOURS: +1 703-741-5970

2. Hazard(s) identification

Physical hazards	Flammable aerosols	Category 1
	Gases under pressure	Liquefied gas
Health hazards	Acute toxicity, inhalation	Category 4
	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2A
	Carcinogenicity	Category 1A
	Reproductive toxicity	Category 2
	Specific target organ toxicity, single exposure	Category 3 respiratory tract irritation
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure	Category 2 (central nervous system, respiratory system)
	Aspiration hazard	Category 1

OSHA defined hazards Simple asphyxiant

Label elements



Signal word Danger

Hazard statement Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. May cause cancer. Suspected of damaging the unborn child. May cause respiratory irritation. May cause drowsiness or dizziness. May cause damage to organs (central nervous system, respiratory system) through prolonged or repeated exposure. May be fatal if swallowed and enters airways. May displace oxygen and cause rapid suffocation.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Keep container tightly closed. Pressurized container: Do not pierce or burn, even after use. Do not breathe mist or vapor. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Wear respiratory protection.

Response	If exposed or concerned: Get medical advice/attention. If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Storage	Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
4-Methylpentan-2-one	108-10-1	30-40
Toluene	108-88-3	30-40
Vinyl chloride	75-01-4	5-10
Titanium Dioxide	13463-67-7	1-5
Vinyl acetate	108-05-4	1-5

Composition comments All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation Remove from further exposure. For those providing assistance, avoid exposure to yourself or others. Use adequate respiratory protection. If respiratory tract irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance. If breathing has stopped, assist ventilation with a mechanical device or use mouth-to-mouth resuscitation. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Get medical attention immediately.

Skin contact Take off immediately all contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and delayed Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Narcosis. Headache. Fatigue. Nausea, vomiting. Behavioral changes. Decrease in motor functions. Very high exposure can cause suffocation from lack of oxygen. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Asphyxiation may bring about unconsciousness without warning and so rapidly that victim may be unable to protect themself. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General information IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media Water fog. Foam. Dry chemical powder. Carbon dioxide (CO_2).

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk.
General fire hazards	Extremely flammable aerosol. Contents under pressure. Pressurized container may explode when exposed to heat or flame.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	In the event of a leak evacuate all personnel until ventilation can restore oxygen concentrations to safe levels. Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water. Large Spills: Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Scoop up used absorbent into drums or other appropriate container. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Do not enter storage areas or confined spaces unless adequately ventilated. Use only outdoors or in a well-ventilated area. Oxygen concentration should not fall below 19.5 % at sea level (pO2 = 135 mmHg). Mechanical ventilation or local exhaust ventilation may be required. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Keep away from heat, sparks and open flame. This material can accumulate static charge which may cause spark and become an ignition source. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Components	Type	Value
Vinyl chloride (CAS 75-01-4)	STEL	5 ppm
	TWA	1 ppm

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
4-Methylpentan-2-one (CAS 108-10-1)	PEL	410 mg/m3	
		100 ppm	
Titanium Dioxide (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.

US. OSHA Table Z-2 (29 CFR 1910.1000)

Components	Type	Value
Toluene (CAS 108-88-3)	Ceiling	300 ppm
	TWA	200 ppm

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value	Form
Titanium Dioxide (CAS 13463-67-7)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.

US. ACGIH Threshold Limit Values

Components	Type	Value
4-Methylpentan-2-one (CAS 108-10-1)	STEL	75 ppm
	TWA	20 ppm
Titanium Dioxide (CAS 13463-67-7)	TWA	10 mg/m3
Toluene (CAS 108-88-3)	TWA	20 ppm
Vinyl acetate (CAS 108-05-4)	STEL	15 ppm
	TWA	10 ppm
Vinyl chloride (CAS 75-01-4)	TWA	1 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
4-Methylpentan-2-one (CAS 108-10-1)	STEL	300 mg/m3
		75 ppm
	TWA	205 mg/m3
		50 ppm
Toluene (CAS 108-88-3)	STEL	560 mg/m3
		150 ppm
	TWA	375 mg/m3
		100 ppm
Vinyl acetate (CAS 108-05-4)	Ceiling	15 mg/m3
		4 ppm

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
4-Methylpentan-2-one (CAS 108-10-1)	1 mg/l	Methyl isobutyl ketone	Urine	*
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*

* - For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

Toluene (CAS 108-88-3) Can be absorbed through the skin.

Vinyl chloride (CAS 75-01-4) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Toluene (CAS 108-88-3) Skin designation applies.

Appropriate engineering controls Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

Skin protection

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Chemical respirator with organic vapor cartridge.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid.

Form Aerosol. Compressed gas.

Color White.

Odor Solvent.

Odor threshold 84.24

pH Not available.

Melting point/freezing point Not available.

Initial boiling point and boiling range 57.2 °F (14 °C)

Flash point -0.4 °F (-18.0 °C)

Evaporation rate 2.1 (BUAC=1)

Flammability (solid, gas) Extremely flammable aerosol.

Upper/lower flammability or explosive limits

Flammability limit - lower (%) 1

Flammability limit - upper (%)	6.3
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	2055 mm Hg
Vapor density	2.3
Relative density	0.968
Solubility(ies)	
Solubility (water)	Negligible.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	< 50 SUS
Other information	
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
VOC	4.69 lb/gal

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Contact with incompatible materials.
Incompatible materials	Acids. Strong oxidizing agents. Aluminum. Peroxides.
Hazardous decomposition products	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Suffocation (asphyxiant) hazard - if allowed to accumulate to concentrations that reduce oxygen below safe breathing levels. Harmful if inhaled. May cause drowsiness and dizziness. Headache. Nausea, vomiting.
Skin contact	Causes skin irritation.
Eye contact	Causes serious eye irritation.
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.
Symptoms related to the physical, chemical and toxicological characteristics	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Narcosis. Headache. Fatigue. Nausea, vomiting. Behavioral changes. Decrease in motor functions. Very high exposure can cause suffocation from lack of oxygen. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Asphyxiation may bring about unconsciousness without warning and so rapidly that victim may be unable to protect themself. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways. Harmful if inhaled.

Components	Species	Test Results
4-Methylpentan-2-one (CAS 108-10-1)		
Acute		
Inhalation		
LC50	Rat	2000 - 4000 ppm, 4 Hours

Components	Species	Test Results
Toluene (CAS 108-88-3)		
Acute		
Dermal		
LD50	Rabbit	12200 mg/kg
Inhalation		
Vapor		
LC50	Rat	28.1 mg/l, 4 Hours
Vinyl acetate (CAS 108-05-4)		
Acute		
Oral		
LD50	Rat	2920 mg/kg
Vinyl chloride (CAS 75-01-4)		
Acute		
Inhalation		
Gas		
LC50	Rat	195000 mg/m³, 4 Hours
Oral		
LD50	Rat	> 4000 mg/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye irritation Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity May cause cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

4-Methylpentan-2-one (CAS 108-10-1)	2B Possibly carcinogenic to humans.
Titanium Dioxide (CAS 13463-67-7)	2B Possibly carcinogenic to humans.
Toluene (CAS 108-88-3)	3 Not classifiable as to carcinogenicity to humans.
Vinyl acetate (CAS 108-05-4)	2B Possibly carcinogenic to humans.
Vinyl chloride (CAS 75-01-4)	1 Carcinogenic to humans.

NTP Report on Carcinogens

Vinyl chloride (CAS 75-01-4)	Known To Be Human Carcinogen.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Vinyl chloride (CAS 75-01-4)	Cancer

Reproductive toxicity Suspected of damaging the unborn child.

Specific target organ toxicity - single exposure May cause respiratory irritation. May cause drowsiness and dizziness.

Specific target organ toxicity - repeated exposure May cause damage to organs (central nervous system, respiratory system) through prolonged or repeated exposure.

Aspiration hazard May be fatal if swallowed and enters airways.

Chronic effects May cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components		Species	Test Results
Toluene (CAS 108-88-3)			
Aquatic			
Acute			
Crustacea	EC50	Daphnia magna	11.5 mg/l, 48 hours
Fish	LC50	Oncorhynchus kisutch	5.5 mg/l, 96 hours
Chronic			
Crustacea	NOEC	Ceriodaphnia dubia	0.74 mg/l, 7 days
Fish	NOEC	Oncorhynchus kisutch	1.4 mg/l, 40 days

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

4-Methylpentan-2-one (CAS 108-10-1)	1.31
Toluene (CAS 108-88-3)	2.73
Vinyl acetate (CAS 108-05-4)	0.73

Mobility in soil No data available.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation potential.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Incinerate the material under controlled conditions in an approved incinerator. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code D001: Waste Flammable material with a flash point <140 F
The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14. Transport information

DOT

UN number UN1950
UN proper shipping name Aerosols (No)
Transport hazard class(es)
Class 2
Subsidiary risk -
Label(s) 2.1
Packing group Not available.
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.
Packaging exceptions 306
Packaging non bulk None
Packaging bulk None

IATA

UN number UN1950
UN proper shipping name Aerosols
Transport hazard class(es)
Class 2
Subsidiary risk -
Label(s) 2.1
Packing group Not available.
Environmental hazards No
ERG Code 10L
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN number	UN1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	
Class	2
Subsidiary risk	-
Label(s)	2.1
Packing group	Not available.
Environmental hazards	
Marine pollutant	No
EmS	Not available.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not established.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

4-Methylpentan-2-one (CAS 108-10-1)	Listed.
Toluene (CAS 108-88-3)	Listed.
Vinyl acetate (CAS 108-05-4)	Listed.
Vinyl chloride (CAS 75-01-4)	Listed.

SARA 304 Emergency release notification

Acetic acid ethenyl ester (CAS 108-05-4)	5000 LBS

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Vinyl chloride (CAS 75-01-4)	Cancer Central nervous system Liver Blood Flammability

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Chemical name	CAS number	Reportable quantity (pounds)	Threshold planning quantity (pounds)	Threshold planning quantity, lower value (pounds)	Threshold planning quantity, upper value (pounds)
Vinyl acetate	108-05-4	5000	1000		

SARA 311/312 Hazardous chemical Yes

Classified hazard categories
Flammable (gases, aerosols, liquids, or solids)
Gas under pressure
Acute toxicity (any route of exposure)
Skin corrosion or irritation
Serious eye damage or eye irritation
Carcinogenicity
Reproductive toxicity
Specific target organ toxicity (single or repeated exposure)
Aspiration hazard
Simple asphyxiant

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
4-Methylpentan-2-one	108-10-1	30-40
Toluene	108-88-3	30-40
Vinyl acetate	108-05-4	1-5
Vinyl chloride	75-01-4	5-10

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

4-Methylpentan-2-one (CAS 108-10-1)
Toluene (CAS 108-88-3)
Vinyl acetate (CAS 108-05-4)
Vinyl chloride (CAS 75-01-4)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Vinyl acetate (CAS 108-05-4)
Vinyl chloride (CAS 75-01-4)

Safe Drinking Water Act (SDWA) Contains component(s) regulated under the Safe Drinking Water Act.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

4-Methylpentan-2-one (CAS 108-10-1)	6715
Toluene (CAS 108-88-3)	6594

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

4-Methylpentan-2-one (CAS 108-10-1)	35 %WV
Toluene (CAS 108-88-3)	35 %WV

DEA Exempt Chemical Mixtures Code Number

4-Methylpentan-2-one (CAS 108-10-1)	6715
Toluene (CAS 108-88-3)	594

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

4-Methylpentan-2-one (CAS 108-10-1)	Low priority

US state regulations

US. Massachusetts RTK - Substance List

4-Methylpentan-2-one (CAS 108-10-1)
Titanium Dioxide (CAS 13463-67-7)
Toluene (CAS 108-88-3)
Vinyl acetate (CAS 108-05-4)
Vinyl chloride (CAS 75-01-4)

US. New Jersey Worker and Community Right-to-Know Act

4-Methylpentan-2-one (CAS 108-10-1)
Titanium Dioxide (CAS 13463-67-7)
Toluene (CAS 108-88-3)
Vinyl acetate (CAS 108-05-4)
Vinyl chloride (CAS 75-01-4)

US. Pennsylvania Worker and Community Right-to-Know Law

4-Methylpentan-2-one (CAS 108-10-1)
Titanium Dioxide (CAS 13463-67-7)
Toluene (CAS 108-88-3)
Vinyl acetate (CAS 108-05-4)
Vinyl chloride (CAS 75-01-4)

US. Rhode Island RTK

4-Methylpentan-2-one (CAS 108-10-1)
Titanium Dioxide (CAS 13463-67-7)
Toluene (CAS 108-88-3)
Vinyl acetate (CAS 108-05-4)
Vinyl chloride (CAS 75-01-4)

California Proposition 65



WARNING: This product can expose you to chemicals including 4-Methylpentan-2-one, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

4-Methylpentan-2-one (CAS 108-10-1)	Listed: November 4, 2011
Titanium Dioxide (CAS 13463-67-7)	Listed: September 2, 2011
Vinyl chloride (CAS 75-01-4)	Listed: February 27, 1987

California Proposition 65 - CRT: Listed date/Developmental toxin

4-Methylpentan-2-one (CAS 108-10-1)	Listed: March 28, 2014
Toluene (CAS 108-88-3)	Listed: January 1, 1991

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

4-Methylpentan-2-one (CAS 108-10-1)
Titanium Dioxide (CAS 13463-67-7)
Toluene (CAS 108-88-3)
Vinyl acetate (CAS 108-05-4)
Vinyl chloride (CAS 75-01-4)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 08-December-2015

Revision date 05-November-2018

Version D

HMIS® ratings Health: 3*
Flammability: 4
Physical hazard: 3

NFPA ratings



Disclaimer ABB Installation Products Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.