

Catalog Number: FTN 175-6 R
Product ID: 7TAA262020R0144
UPC Number: 78378672685
Status: Active

Flood Seal, Aluminum Transformer Spade Connector, Dual Rated Aluminum and Copper, Six Tower, 3 pieces

- Flood-Seal Connectors Permit the Use of Aluminum or Copper Standard Side-Formed 2-Hole Lugs.
- Flood-Seal EPDM Rubber Insulating Sleeves are Available to Fully Insulate Outlets.
- All Outlets are Provided with 1/2 inch Plated Steel Hex-Head Bolts and Captive Belleville Washers.
- Cable Range from 4/0 to 1000 kcmil Aluminum or Copper/
- maximum Contact Ensures Cooler Operating, More Reliable Connections.
- All Flood-Seal Connectors Meet or Exceed ANSI C119.4 Specifications.

North American Specifications (UNSPSC)

UNSPSC	39121448 Wire or cable compression connector
IGCC	4668 Wire or cable compression connector
Brand Name	Homac
Type	Transformer Spade Connector.
Special Features	PVC Coating, No PVC on Pads. Includes 12 HS Screws. Right Handed.
Size	Length 12.250 inches x 10.250 inches.
Material	Aluminum
Finish	Bare
Insulation	None
Bolt Size	1/2 inch

Packaging

Outer Quantity	3
Outer Dimensions (inches)	17.875x13.875x8.625
Weight Uom	10.18 lbs. Each

For further technical assistance, please contact us...

Thomas & Betts - USA
860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

T&B Technical Support
MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com