NO-LEAD PRESSURE GAUGES
STANDARD GAUGE – STEEL CASE

SPECIFICATIONS:

- Constructed with a durable steel case, these gauges are available with a 1/4” NPT no-lead brass lower male connection or a 1/8” NPT or 1/4” NPT no-lead brass back mount connection.
- No-lead pressure gauges are specifically designed for water, air, steam, and other pressure applications that will not deteriorate brass alloys.
- These gauges provide an accuracy of +/- 3%, +/- 2%, +/- 3%.
- With a temperature range up to 140° F, they ensure reliable performance under various conditions.
- Each pressure gauge is individually boxed.





DIMENSIONS						
Part No.	**Dial Size Inches**	**Pressure Range**	**PSI Increments**	**Connection**	**Master Ctn. Qty.**	**Wt. Each Lbs.**
PGNL100	2”	0-100 psi	2#	1/4” NPT NL Brass - Lower Male	100	0.22
*PGBNL100	2”	0-100 psi	2#	1/8” NPT NL Brass - Back Mount	100	0.24
*PGBNL10025	2”	0-100 psi	2#	1/4” NPT NL Brass - Back Mount	100	0.24
*PGBNL160	2”	0-160 psi	4#	1/8” NPT NL Brass - Back Mount	100	0.18
*PGBNL15160	1-1/2”	0-160 psi	4#	1/8” NPT NL Brass - Back Mount	100	0.20
*PGBNL16025	2”	0-160 psi	4#	1/4” NPT NL Brass - Back Mount	100	0.15
PGNL15	2”	0-15 psi	1/5#	1/4” NPT NL Brass - Lower Male	100	0.22
PGNL30	2”	0-30 psi	1/2#	1/4” NPT NL Brass - Lower Male	100	0.22
PGNL60	2”	0-60 psi	1/2#	1/4” NPT NL Brass - Lower Male	100	0.22
PGNL160	2”	0-160 psi	4#	1/4” NPT NL Brass - Lower Male	100	0.22
PGNL200	2”	0-200 psi	4#	1/4” NPT NL Brass - Lower Male	100	0.22
PGNL300	2”	0-300 psi	5#	1/4” NPT NL Brass - Lower Male	100	0.22

* Back Mount Model

MATERIALS LIST	
Part Name	**Material**
Case	Steel
1/4” NPT or 1/8” NPT Lower Male Connection or Back Mount	No-Lead Brass

MERRILL MANUFACTURING

315 Flindt Drive P.O. Box 392
Storm Lake, Iowa 50588-0392 U.S.A.
merrillmfg.com

(800) 831-6962
(712) 732-2760
Fax No. 1-800-ANYFLOW