



Revision Date: 03/25/2008

Issue date: 10/23/2008

CHEMICAL PRODUCT AND COMPANY IDENTIFICATION 1.

Product name: SpeedBonder(TM) 326 Adhesive Product type: Adhesive Company address: Henkel Corporation One Henkel Way Rocky Hill, Connecticut 06067

| Item No. : | 32685 / IDH No. 135404 | |
|-------------------------------------|------------------------|--|
| Region: | United States | |
| Contact Information | : | |
| Telephone: (860) 571-5100 | | |
| Emergency telephone: (860) 571-5100 | | |
| Internet: www.henkel | na.com | |

2. COMPOSITION/INFORMATION ON INGREDIENTS

| Hazardous components Polyurethane methacrylate resin PROPRIETARY | <u>%</u> 30-60 | ACGIH TLV None | OSHA PEL None | OTHER None |
|--|-------------------|-------------------------------|----------------------|--|
| Hydroxyalkyl methacrylate 868-77-9 | 10-30 | None | None | 3 ppm (ceiling) |
| High boiling methacrylate 7534-94-3 | 10-30 | None | None | None |
| Acrylic acid 79-10-7 | 1-5 | 2 ppm TWA (skin) | 10 ppm TWA; 30 mg/m³ | 1 ppm TWA (skin); 3 ppm STEL (skin) |
| 1-Acetyl-2-phenylhydrazine 114-83-0 | 0.1-1 | None | None | None |
| Ethylene glycol 107-21-1 | 0.1-1 | 100 mg/m ³ Ceiling | None | None |

3. HAZARDS IDENTIFICATION

| | | | EMERGENCY OVERVIEW HMIS: | |
|------------------------------------|---------------------------|------------------|---|-------------------------------|
| Physical state: Color: Odor: | Liquid Amber Sharp, | | HEALTH: FLAMMABILITY: PHYSICAL HAZARD: Personal Protection: | 2* 1 1 See Section 8 |
| WARNING | 6: | MAY CAUSE RESPIR | SKIN IRRITATION. GIC SKIN REACTION. RATORY TRACT IRRITATION. F SWALLOWED OR INHALED. | |

Relevant routes of exposure:

Skin, Inhalation, Eyes

Potential Health Effects

| Inhala | tion: | May cause irritation to nose and throat. |
|---------------------------|------------------------|--|
| Skin o | ontact: | Irritating to skin. May cause allergic skin reaction. |
| Eye co | ontact: | Vapors may irritate eyes. Contact with eyes will cause irritation. |
| Ingest | ion: | May be harmful if swallowed. May cause gastrointestinal tract irritation if swallowed. |
| Existing con exposure: | ditions aggravated by | Skin disorders. Eye disorders. Acrylic acid: Respiratory disorders. Lung disease. |
| Item No. : | 32685 / IDH No. 135404 | Product name: SpeedBonder(TM) 326 Adh |

nesive Spee r(TM)

See Section 11 for additional toxicological information.

4. FIRST AID MEASURES

| Inhalation: | Remove to fresh air. If symptoms develop and persist, get medical attention. |
|---------------|--|
| Skin contact: | Wash with soap and water. Remove contaminated clothing and shoes. Wash clothing before reuse. Get medical attention if symptoms occur. |
| Eye contact: | Flush with copious amounts of water, preferably, lukewarm water for at least 15 minutes, holding eyelids open all the time. Get medical attention. |
| Ingestion: | Do not induce vomiting. Keep individual calm. Obtain medical attention. |

| 5. FIRE-FIGHTING MEASURES | | |
|--|--|--|
| Flash point: | Greater than 93°C (200°F) Tagliabue closed cup | |
| Autoignition temperature: | Not available | |
| Flammable/Explosive limits-lower %: | 2.0 % (Acrylic Acid) | |
| Flammable/Explosive limits-upper %: | 8.0 % (Acrylic Acid) | |
| Extinguishing media: | Foam, dry chemical or carbon dioxide. | |
| Special fire fighting procedures: | Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. | |
| Unusual fire or explosion hazards: | None | |
| Hazardous combustion products: | Oxides of carbon. Irritating organic vapors. | |
| | 6. ACCIDENTAL RELEASE MEASURES | |
| Environmental precautions: | Prevent product from entering drains or open waters. | |
| Clean-up methods: | Ensure adequate ventilation. Soak up with inert absorbent. Store in a partly filled, closed container until disposal. | |
| | 7. HANDLING AND STORAGE | |
| Handling: | Avoid contact with eyes, skin and clothing. Avoid breathing vapor and mist. Wash thoroughly after handling. | |
| Storage: | For safe storage, store at or below 38°C (100°F). Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use. | |
| Incompatible products: | Refer to Section 10. | |
| For informati | ion on product shelf life contact Henkel Customer Service at (800) 243-4874. | |
| 8. EXPOSURE CONTROLS / PERSONAL PROTECTION | | |
| Engineering controls: | Use local exhaust ventilation to maintain airborne concentrations below established exposure limits. | |
| Respiratory protection: | Use NIOSH approved respirator if there is potential to exceed exposure limit(s). | |
| Skin protection: | Use impermeable gloves and protective clothing as necessary to prevent skin contact. Neoprene gloves. | |
| Eye/face protection: | Safety goggles or safety glasses with side shields. | |
| | See Section 2 for expecting limits | |

See Section 2 for exposure limits.

Item No. : 32685 / IDH No. 135404

Product name: SpeedBonder(TM) 326 Adhesive

9. PHYSICAL AND CHEMICAL PROPERTIES

| Physical state: | Liquid |
|--|--|
| Color: | Amber |
| Odor: | Sharp, Irritating |
| Vapor pressure: | Less than 10 mm Hg at 27°C (80°F) |
| pH: | Not applicable |
| Boiling point/range: | Greater than 149°C (300°F) |
| Melting point/range: | Not available |
| Specific gravity: | 1.1 at 26.6°C (80°F) |
| Specific gravity: Vapor density: Evaporation rate: Solubility in water: Partition coefficient (n-octanol/water): VOC content: | Not available Slight Not available 3.106%; 35.5 grams/liter (EPA Method 24) |

10. STABILITY AND REACTIVITY

| Stability: | Stable at normal conditions | |
|-----------------------------------|---|--|
| Hazardous polymerization: | Will not occur. | |
| Hazardous decomposition products: | Oxides of carbon. Irritating organic vapors. | |
| Incompatability: | Strong oxidizers. Reducing agents. Acids. Bases. Copper. Alkalis. Aldehydes. Amines. Free radical initiators. Peroxides. | |
| Conditions to avoid: | Exposure to sunlight. Heat, flames and sparks. See "Handling and Storage" (Section 7) and "Incompatability" (Section 10). | |
| 11. TOXICOLOGICAL INFORMATION | | |

Product toxicity data:

Acute LD50 (oral): 5000 (rat). (estimated). Acute dermal LD50 greater than 2000 mg/kg (rabbit) (estimated).

Carcinogen Status

| Hazardous components | NTP Carcinogen | IARC Carcinogen | OSHA Carcinogen |
|--|----------------|-----------------|-----------------|
| Polyurethane methacrylate resin PROPRIETARY | No | No | No |
| Hydroxyalkyl methacrylate 868-77-9 | No | No | No |
| High boiling methacrylate 7534-94-3 | No | No | No |
| Acrylic acid 79-10-7 | No | No | No |
| 1-Acetyl-2-phenylhydrazine 114-83-0 | No | No | No |
| Ethylene glycol 107-21-1 | No | No | No |

Literature Referenced Target Organ & Other Health Effects

| Hazardous components | Health Effects/Target Organs |
|--|---|
| Polyurethane methacrylate resin PROPRIETARY | Allergen, Irritant |
| Hydroxyalkyl methacrylate 868-77-9 | Allergen, Irritant |
| High boiling methacrylate 7534-94-3 | Allergen, Irritant |
| Acrylic acid 79-10-7 | Allergen, Corrosive, Irritant, Kidney, Liver |
| 1-Acetyl-2-phenylhydrazine 114-83-0 | Allergen, Blood, Kidney, Mutagen, Some evidence of carcinogenicity |
| Ethylene glycol 107-21-1 | Blood, Bone Marrow, Central nervous system, Developmental, Eyes, Irritant, Kidney, Liver, Metabolic |

12. ECOLOGICAL INFORMATION

| Ecological information: | Not available |
|--|--|
| | 13. DISPOSAL CONSIDERATIONS |
| | Information provided is for unused product only. |
| Recommended method of disposal: | Dispose of according to Federal, State and local governmental regulations. |
| EPA hazardous waste number: | Not a RCRA hazardous waste. |
| | 14. TRANSPORT INFORMATION |
| U.S. Department of Transportation Grou | und (49 CFR): |
| Proper shipping name: | Unrestricted |
| Hazard class or division: | None |
| Identification number: | None |
| Packing group: | None |
| International Air Transportation (ICAO/ | |
| Proper shipping name: | Unrestricted |
| Hazard class or division: | None |
| Identification number: | None |
| Packing group: | None |
| WaterTransportation (IMO/IMDG): | |
| Proper shipping name: Hazard class or division: | Unrestricted |
| Identification number: | None None |
| Packing group: | None |
| Marine pollutant: | None |
| | 15. REGULATORY INFORMATION |
| | |
| United States Regulatory Information | |
| TSCA 8 (b) Inventory Status: TSCA 12 (b) Export Notification: | All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory. None. |
| CERCLA/SARA Section 302 EHS: CERCLA/SARA Section 311/312: | None above reporting de minimus. Immediate Health Hazard, Delayed Health Hazard |
| CERCLA/SARA 313: | This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Acrylic acid (CAS# 79-10-7). |
| California Proposition 65: | This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm. |
| Canada Regulatory Information | |
| CEPA DSL/NDSL Status: | One or more components are not listed on, and are not exempt from listing on either the Domestic Substances List or the Non-Domestic Substances List. Those components must be tracked by all Canadian Importers of Record as required by the Canadian Environmental Protection Agency. They may be imported into Canada in limited quantities. Please contact Product Safety and Regulatory |
| WHMIS hazard class: | Affairs for details. D.2.A, D.2.B |

This material safety data sheet contains changes from the previous version in sections: Updated Revision Date Only

Prepared by:

Regulatory Affairs

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.