



Revision Number: 002.1

Issue date: 04/22/2009

## 1. PRODUCT AND COMPANY IDENTIFICATION

**Product name:** 736 Primer Locquic® Primer NF  
**Product type:** Accelerator

**IDH number:** 135537  
**Item number:** 73656  
**Region:** United States

**Company address:**  
 Henkel Corporation  
 1001 Trout Brook Crossing  
 Rocky Hill, Connecticut 06067

**Contact information:**  
 Telephone: 860.571.5100  
 Emergency telephone: 860.571.5100  
 Internet: www.henkelna.com

## 2. HAZARDS IDENTIFICATION

### EMERGENCY OVERVIEW

<b>Physical state:</b>	Liquid	<b>HEALTH:</b>	*2
<b>Color:</b>	Amber	<b>FLAMMABILITY:</b>	2
<b>Odor:</b>	Sharp	<b>PHYSICAL HAZARD:</b>	1
		<b>Personal Protection:</b>	See MSDS Section 8

**WARNING:** COMBUSTIBLE LIQUID AND VAPOR.  
 HARMFUL IF SWALLOWED OR INHALED.  
 MAY CAUSE ALLERGIC SKIN REACTION.  
 CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION.

**Relevant routes of exposure:** Skin, Inhalation, Eyes, Ingestion

### Potential Health Effects

**Inhalation:** May cause respiratory tract irritation. Excessive inhalation of this material causes headache, dizziness, nausea and incoordination.  
**Skin contact:** Causes skin irritation. Solvent action can dry and defat the skin, causing the skin to crack, leading to dermatitis.  
**Eye contact:** Contact with eyes will cause irritation.  
**Ingestion:** Moderately toxic by ingestion.

**Existing conditions aggravated by exposure:** Eye, skin, and respiratory disorders.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

See Section 11 for additional toxicological information.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%
Trichloroethylene	79-01-6	60 - 100
2-Propanol	67-63-0	5 - 10
Carbon dioxide	124-38-9	1 - 5
Butanal, reaction products with butylamine	68411-19-8	1 - 5

## 4. FIRST AID MEASURES

**Inhalation:** Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

<b>Skin contact:</b>	Wash with soap and water. Remove contaminated clothing and footwear. Wash clothing before reuse. If symptoms develop and persist, get medical attention.
<b>Eye contact:</b>	Flush with copious amounts of water, preferably, lukewarm water for at least 15 minutes, holding eyelids open all the time. Get medical attention.
<b>Ingestion:</b>	If conscious, drink plenty of water. Do not induce vomiting. Keep individual calm. Get medical attention.

## 5. FIRE FIGHTING MEASURES

<b>Flash point:</b>	76 °C (168.8 °F) ; (Base only)
<b>Autoignition temperature:</b>	Not available
<b>Flammable/Explosive limits - lower:</b>	Not available
<b>Flammable/Explosive limits - upper:</b>	Not available
<b>Extinguishing media:</b>	Foam, dry chemical or carbon dioxide.
<b>Special firefighting procedures:</b>	Not available
<b>Unusual fire or explosion hazards:</b>	Vapors may accumulate in low or confined areas, travel considerable distance to source of ignition, and flash back.
<b>Hazardous combustion products:</b>	Oxides of carbon. Hydrogen chloride. Phosgene. Irritating organic vapours. Toxic chlorides.

## 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

<b>Environmental precautions:</b>	Do not allow product to enter sewer or waterways.
<b>Clean-up methods:</b>	Remove all sources of ignition. Ensure adequate ventilation. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Store in a partly filled, closed container until disposal.

## 7. HANDLING AND STORAGE

<b>Handling:</b>	Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. During use and until all vapors are gone: Keep area ventilated - do not smoke; extinguish all flames, pilot lights, and heaters; turn off stoves, electrical tools and appliances, and any other sources of ignition.
<b>Storage:</b>	For safe storage, store at or below 49 °C (120.2 °F) Store away from heat, sparks, flames, or other sources of ignition.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Trichloroethylene	10 ppm TWA 25 ppm STEL	100 ppm TWA 200 ppm Ceiling 300 ppm MAX. CONC 5 minutes in any 2 hours	None	None
2-Propanol	200 ppm TWA 400 ppm STEL	400 ppm (980 mg/m3) TWA	None	None
Carbon dioxide	5,000 ppm TWA 30,000 ppm STEL	5,000 ppm (9,000 mg/m3) TWA	None	None
Butanal, reaction products with butylamine	None	None	None	None

**Engineering controls:**

Use local ventilation if general ventilation is insufficient to maintain vapor concentration below established exposure limits.

**Respiratory protection:**

Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

**Eye/face protection:**

Safety goggles or safety glasses with side shields.

**Skin protection:**

Chemical resistant, impermeable gloves. Solvent resistant gloves such as Viton, poly (vinyl alcohol), or equivalent is recommended. Silver Shield gloves.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical state:</b>	Liquid
<b>Color:</b>	Amber
<b>Odor:</b>	Sharp
<b>Odor threshold:</b>	Not available
<b>pH:</b>	Not applicable
<b>Vapor pressure:</b>	100 mm hg (21 °C (69.8 °F)) Approximately
<b>Boiling point/range:</b>	77 - 82 °C (170.6 - 179.6 °F)
<b>Melting point/ range:</b>	Not available
<b>Specific gravity:</b>	1.3 at 26.6 °C (79.88 °F)
<b>Vapor density:</b>	4.5 Approximately
<b>Flash point:</b>	76 °C (168.8 °F) ; (Base only)
<b>Flammable/Explosive limits - lower:</b>	Not available
<b>Flammable/Explosive limits - upper:</b>	Not available
<b>Autoignition temperature:</b>	Not available
<b>Evaporation rate:</b>	Not available
<b>Solubility in water:</b>	Slight
<b>Partition coefficient (n-octanol/water):</b>	Not available
<b>VOC content:</b>	95.6 %; 1,243 g/l EPA Method 24

## 10. STABILITY AND REACTIVITY

<b>Stability:</b>	Stable
<b>Hazardous reactions:</b>	Will not occur.
<b>Hazardous decomposition products:</b>	Oxides of carbon. Phosgene. Hydrogen chloride. Irritating organic vapours. Toxic chlorides.
<b>Incompatible materials:</b>	Strong oxidizing agents. Bases. Metals. Reducing agents. Strong alkalis. Caustics.
<b>Conditions to avoid:</b>	See "Handling and Storage" (Section 7) and "Incompatibility" (Section 10).

## 11. TOXICOLOGICAL INFORMATION

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Trichloroethylene	Anticipated carcinogen.	Group 2A	No
2-Propanol	No	No	No
Carbon dioxide	No	No	No
Butanal, reaction products with butylamine	No	No	No

Hazardous components	Health Effects/Target Organs
Trichloroethylene	Behavioral, Cardiac, Central nervous system, Irritant, Kidney, Liver, Some evidence of carcinogenicity
2-Propanol	Allergen, Blood, Brain, Central nervous system, Irritant, Kidney, Liver, Spleen
Carbon dioxide	Central nervous system
Butanal, reaction products with butylamine	No Records

## 12. ECOLOGICAL INFORMATION

Ecological information: Not available

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: D040: Trichloroethylene

## 14. TRANSPORT INFORMATION

### U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Aerosols  
 Hazard class or division: 2.2 (6.1)  
 Identification number: UN 1950  
 Packing group: None  
 Exceptions: Consumer Commodity, (Not more than 1 L), ORM-D

### International Air Transportation (ICAO/IATA)

Proper shipping name: Aerosols, non-flammable, containing substances in Division 6.1, Packing Group III  
 Hazard class or division: 2.2 (6.1)  
 Identification number: UN 1950  
 Packing group: None

### Water Transportation (IMO/IMDG)

Proper shipping name: AEROSOLS  
 Hazard class or division: 2.2 (6.1)  
 Identification number: UN 1950  
 Packing group: None  
 Exceptions: Limited quantity (Not more than 120 ml)

## 15. REGULATORY INFORMATION

### United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.  
 TSCA 12(b) Export Notification: None above reporting de minimus  
 CERCLA/SARA Section 302 EHS: None above reporting de minimus  
 CERCLA/SARA Section 311/312: Immediate Health, Delayed Health

<b>CERCLA/SARA 313:</b>	This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Trichloroethylene (CAS# 79-01-6).
<b>CERCLA Reportable quantity:</b>	Trichloroethylene (CAS# 79-01-6) 100 lbs. (45.4 kg)
<b>California Proposition 65:</b>	This product contains a chemical known in the State of California to cause cancer.

#### **Canada Regulatory Information**

<b>CEPA DSL/NDL Status:</b>	All components are listed on or are exempt from listing on the Canadian Domestic Substances List.
<b>WHMIS hazard class:</b>	A, B.3, D.1.B, D.2.A, D.2.B

### **16. OTHER INFORMATION**

**This material safety data sheet contains changes from the previous version in sections:** New Material Safety Data Sheet format.

**Prepared by:** Kyra Kozak Woods, Manager, Regulatory Affairs

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.