Material Safety Data Sheet

Revision Number: 003.1

Issue date: 10/30/2009

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: **Loctite(R) 332 Structural Adhesive Magnet Bonder**
Product type: Adhesive

IDH number: 232743
Item number: 33275
Region: United States

Company address:
Henkel Corporation
One Henkel Way
Rocky Hill, Connecticut 06067

Contact information:
Telephone: 860.571.5100
Emergency telephone: 860.571.5100
Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

HMIS:

Physical state: Liquid
Color: Pale yellow
Odor: Sharp

HEALTH: *2
FLAMMABILITY: 2
PHYSICAL HAZARD: 1
Personal Protection: See MSDS Section 8

WARNING: COMBUSTIBLE LIQUID AND VAPOR.
CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION.
MAY CAUSE ALLERGIC SKIN REACTION.
MAY BE HARMFUL IF SWALLOWED.

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

Potential Health Effects

Inhalation: May cause irritation to nose and throat. Coughing. Shortness of breath.
Skin contact: Causes skin irritation. May cause allergic skin reaction.
Eye contact: Vapors may irritate eyes. Contact with eyes will cause irritation. Burning sensation. Redness. Tearing.
Ingestion: May cause gastrointestinal tract irritation if swallowed.

Existing conditions aggravated by exposure: Eye, skin, and respiratory disorders.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%
Cyclohexyl methacrylate	101-43-9	30 - 60
Styrene Polymer with 1,3-Butadiene	9003-55-8	30 - 60
Methacrylic acid	79-41-4	5 - 10
Silica, amorphous, fumed, crystal-free	112945-52-5	1 - 5
Acrylic acid	79-10-7	1 - 5
1,3-Butylene glycol dimethacrylate	1189-08-8	1 - 5
Tert-butyl perbenzoate	614-45-9	1 - 5

4. FIRST AID MEASURES

Inhalation: Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention.

Skin contact: Immediately wash skin thoroughly with soap and water. Remove contaminated clothing and footwear. If symptoms develop and persist, get medical attention. Wash clothing before reuse.

Eye contact: Flush with copious amounts of water, preferably, lukewarm water for at least 15 minutes, holding eyelids open all the time. Get medical attention.

Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious person. Keep individual calm. Get medical attention.

5. FIRE FIGHTING MEASURES

Flash point: 77 °C (170.6 °F) Setaflash Closed Cup

Autoignition temperature: Not available

Flammable/Explosive limits - lower: 2 % (Acrylic Acid)

Flammable/Explosive limits - upper: 8 % (Acrylic Acid)

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. In case of fire, keep containers cool with water spray.

Unusual fire or explosion hazards: Uncontrolled polymerization may occur at high temperatures resulting in explosions or rupture of storage containers.

Hazardous combustion products: Oxides of carbon. Oxides of sulfur. Oxides of nitrogen. Irritating organic vapours.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Do not allow product to enter sewer or waterways.

Clean-up methods: Remove all sources of ignition. Ensure adequate ventilation. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Store in a partly filled, closed container until disposal.

7. HANDLING AND STORAGE

Handling: Use only with adequate ventilation. Keep away from heat, spark and flame. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Do not taste or swallow. Make sure containers are properly grounded before use or transfer of material.

Storage: For safe storage, store at or below 38 °C (100.4 °F)
Keep in a cool, well ventilated area away from heat, sparks and open flame.
Keep container tightly closed until ready for use.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Cyclohexyl methacrylate	None	None	None	None
Styrene Polymer with 1,3-Butadiene	None	None	None	None
Methacrylic acid	20 ppm TWA	None	None	None
Silica, amorphous, fumed, crystal-free	10 mg/m3 TWA Inhalable dust. 3 mg/m3 TWA Respirable fraction.	20 MPPCF TWA 0.8 mg/m3 TWA	None	None
Acrylic acid	2 ppm TWA (SKIN)	None	None	1 ppm TWA 3 ppm STEL (SKIN)
1,3-Butylene glycol dimethacrylate	None	None	None	None
Tert-butyl perbenzoate	None	None	None	None

Engineering controls: Use explosion-proof mechanical ventilation and local exhaust to control contaminants to within their occupational exposure limits during the use of this product.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

Eye/face protection: Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists.

Skin protection: Use impermeable gloves and protective clothing as necessary to prevent skin contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid
Color: Pale yellow
Odor: Sharp
Odor threshold: Not available
pH: Not applicable
Vapor pressure: < 30 mm hg (25 °C (77°F))
Boiling point/range: > 149 °C (> 300.2 °F)
Melting point/ range: Not available
Specific gravity: 0.97
Vapor density: > 2
Flash point: 77 °C (170.6 °F) Setaflash Closed Cup
Flammable/Explosive limits - lower: 2 % (Acrylic Acid)
Flammable/Explosive limits - upper: 8 % (Acrylic Acid)
Autoignition temperature: Not available
Evaporation rate: Not available
Solubility in water: Slight
Partition coefficient (n-octanol/water): Not available
VOC content: 0.92 %; 8.91 g/l

10. STABILITY AND REACTIVITY

Stability: Stable

Hazardous reactions: None under normal processing.

Hazardous decomposition products: Oxides of carbon. Irritating organic vapours.

Incompatible materials: Strong oxidizing agents. Strong reducing agents. Free radical initiators. Oxygen scavengers. Acids and bases. Heavy metals.

Conditions to avoid: Heat, flames, sparks and other sources of ignition. Freezing conditions. Store away from incompatible materials. Direct sunlight. UV light.

11. TOXICOLOGICAL INFORMATION

Acute oral product toxicity: LD50 (rat) > 5,000 mg/kg (Estimated)

Acute dermal product toxicity: LD50 (rabbit) > 2,000 mg/kg (Estimated)

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Cyclohexyl methacrylate	No	No	No
Styrene Polymer with 1,3-Butadiene	No	No	No
Methacrylic acid	No	No	No
Silica, amorphous, fumed, crystal-free	No	No	No
Acrylic acid	No	No	No
1,3-Butylene glycol dimethacrylate	No	No	No
Tert-butyl perbenzoate	No	No	No

Hazardous components	Health Effects/Target Organs
Cyclohexyl methacrylate	Irritant, Allergen
Styrene Polymer with 1,3-Butadiene	No Target Organs
Methacrylic acid	Corrosive, Irritant, Allergen
Silica, amorphous, fumed, crystal-free	Nuisance dust
Acrylic acid	Allergen, Corrosive, Irritant, Kidney, Liver
1,3-Butylene glycol dimethacrylate	Irritant, Allergen
Tert-butyl perbenzoate	Central nervous system, Irritant, Mutagen

12. ECOLOGICAL INFORMATION

Ecological information: Not available

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Dispose of according to Federal, State and local governmental regulations.

Hazardous waste number: Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

The shipping classifications in this sections are for non-bulk packaging only (unless otherwise specified). Shipping classification may be different for bulk packaging.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

International Air Transportation (ICAO/IATA)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

Water Transportation (IMO/IMDG)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status:	All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.
TSCA 12(b) Export Notification:	None above reporting de minimus
CERCLA/SARA Section 302 EHS:	None above reporting de minimus
CERCLA/SARA Section 311/312:	Fire, Immediate Health, Delayed Health
CERCLA/SARA 313:	This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Acrylic acid (CAS# 79-10-7).
California Proposition 65:	This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Canada Regulatory Information

CEPA DSL/NDSL Status:	Contains one or more components listed on the Non-Domestic Substances List. All other components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities. Please contact Regulatory Affairs for additional details.
WHMIS hazard class:	B.3, D.2.B

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: New Material Safety Data Sheet format. 1,2,3,5,6,7,8,10

Prepared by: Tricia Voghell, Regulatory Affairs Specialist

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.