



Revision Date: 01/14/2008

Issue date: 01/14/2008

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product name: C-200 Solid Film Lubricant
Product type: Lubricant
Company address:
Henkel Corporation
One Henkel Way
Rocky Hill, Connecticut 06067

Item No. : 39894 / IDH No. 233499
Region: United States
Contact Information:
Telephone: (860) 571-5100
Emergency telephone: (860) 571-5100
Internet: www.henkelna.com

2. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Hazardous components</u>	<u>%</u>	<u>ACGIH TLV</u>	<u>OSHA PEL</u>	<u>OTHER</u>
Distillates (petroleum), hydrotreated heavy naphthenic 64742-52-5	30-60	5 mg/m ³ TWA (mist) 10mg/m ³ STEL (mist)	5 mg/m ³ TWA (mist)	None
Molybdenum disulfide 1317-33-5	10-30	10 mg/m ³ TWA	10 mg/m ³ TWA	None
Lead monoxide 1317-36-8	10-30	0.05 mg/m ³ TWA	30 µg/m ³ Action Level as Pb. Poison - see 29 CFR 1910.1025 50 µg/m ³ TWA as Pb 50 µg/m ³ PEL as Pb	None
Graphite 7782-42-5	10-30	2 mg/m ³ TWA all forms except graphite fibers	15 mg/m ³ (total), 5 mg/m ³ (respirable)	None
Siloxanes and silicones, di-me, me vinyl, hydroxy-terminated 68037-81-0	1-5	None	None	None
Xylene 1330-20-7	1-5	100 ppm TWA 150 ppm STEL	100 ppm TWA 435 mg/m ³ TWA	None
Ethyl benzene 100-41-4	1-5	100 ppm TWA 125 ppm STEL	100 ppm TWA 435 mg/m ³ TWA	None

3. HAZARDS IDENTIFICATION**EMERGENCY OVERVIEW**

Physical state: Solid
Color: Black
Odor: Slight, Oily

HMIS:

HEALTH: 1
FLAMMABILITY: 1
PHYSICAL HAZARD: 0
Personal Protection: See Section 8

CAUTION: MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects**Inhalation:**

Mild respiratory tract irritation. Lead is a cumulative poison and continuous exposure to small amounts over time can raise the body's content to toxic levels.

Skin contact:

May cause irritation due to defatting of the skin.

Eye contact:

May cause irritation.

Item No. : 39894 / IDH No. 233499

Product name: C-200 Solid Film Lubricant

Ingestion: Lead is a cumulative poison and continuous exposure to small amounts over time can raise the body's content to toxic levels.

Existing conditions aggravated by exposure: Eye, skin, and respiratory disorders.

See Section 11 for additional toxicological information.

4. FIRST AID MEASURES

Inhalation: Remove to fresh air. If discomfort persists seek medical attention.

Skin contact: Remove contaminated clothing and shoes. Wash with soap and water. Get medical attention if symptoms develop and persist. Wash clothing before reuse.

Eye contact: Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.

Ingestion: Do not induce vomiting. Aspiration may cause pulmonary edema and pneumonitis. Obtain medical attention.

5. FIRE-FIGHTING MEASURES

Flash point: Product is a solid. Not classified as a flammable solid per DOT Classification Guidelines Part 173 Appendix H 7/10/2002.

Autoignition temperature: Not determined

Flammable/Explosive limits-lower %: Not available

Flammable/Explosive limits-upper %: Not available

Extinguishing media: Carbon dioxide (CO₂). Dry chemical. Foam. Water spray.

Special fire fighting procedures: Use water spray to keep fire exposed containers cool and disperse vapors.

Unusual fire or explosion hazards: None

Hazardous combustion products: Oxides of carbon.

6. ACCIDENTAL RELEASE MEASURES

Environmental precautions: Remove sources of ignition. Contain spill. Prevent further leakage or spillage. Do not let product enter drains. Ventilate area.

Clean-up methods: Scrape up spilled material and place in sealed container for disposal.

7. HANDLING AND STORAGE

Handling: Avoid contact with eyes, skin and clothing. Avoid breathing vapor and mist. Wash thoroughly after handling.

Storage: Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.

Incompatible products: Not available

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering controls: Ensure adequate ventilation. Local exhaust ventilation is recommended when general ventilation is not sufficient to control airborne contamination below occupational exposure limits.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure limit(s). Observe OSHA regulations for respiratory use (29 CFR 1910.134).

Item No. : 39894 / IDH No. 233499

2 of 5

Product name: C-200 Solid Film Lubricant

Skin protection: Chemical resistant, impermeable gloves.

Eye/face protection: Safety glasses with side-shields. Goggles.

See Section 2 for exposure limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Solid
Color: Black
Odor: Slight, Oily
Vapor pressure: Not available
pH: Not applicable
Boiling point/range: Not available
Melting point/range: Not available
Specific gravity: 1.4406
Vapor density: Heavier than air
Evaporation rate: Slower than butyl acetate
Solubility in water: Slightly soluble
Partition coefficient (n-octanol/water): Not available
VOC content: Essentially Zero (Exempt Compounds)

10. STABILITY AND REACTIVITY

Stability: Stable at normal conditions

Hazardous polymerization: Will not occur.

Hazardous decomposition products: Oxides of carbon. Hydrocarbons.

Incompatibility: Oxidizing agents. Strong acids and strong bases.

Conditions to avoid: Prolonged exposure to heat.

11. TOXICOLOGICAL INFORMATION

Carcinogen Status

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen
Distillates (petroleum), hydrotreated heavy naphthenic 64742-52-5	No	No	No
Molybdenum disulfide 1317-33-5	No	No	No
Lead monoxide 1317-36-8	Suspect Carcinogen	Group 2A Group 2B Group 2B	Yes
Graphite 7782-42-5	No	No	No
Siloxanes and silicones, di-me, me vinyl, hydroxy-terminated 68037-81-0	No	No	No
Xylene 1330-20-7	No	No	No
Ethyl benzene 100-41-4	No	Group 2B	Yes

Literature Referenced Target Organ & Other Health Effects

Hazardous components	Health Effects/Target Organs
Distillates (petroleum), hydrotreated heavy naphthenic 64742-52-5	Irritant
Molybdenum disulfide 1317-33-5	No Target Organs
Lead monoxide 1317-36-8	Irritant, Nervous System, Gastrointestinal, Blood, Kidney, Teeth, Reproductive, Developmental, Liver, Muscle, Cardiac, Vascular, Behavioral, Eyes, Thyroid
Graphite 7782-42-5	Lung
Siloxanes and silicones, di-me, me vinyl, hydroxy-terminated 68037-81-0	No Records
Xylene 1330-20-7	Cardiac, Central nervous system, Irritant, Kidney, Liver
Ethyl benzene 100-41-4	Central nervous system, Irritant

12. ECOLOGICAL INFORMATION

Ecological information: Not available

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Dispose of according to Federal, State and local governmental regulations.

EPA hazardous waste number: D008 Lead

14. TRANSPORT INFORMATION

U.S. Department of Transportation Ground (49 CFR):

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

International Air Transportation (ICAO/IATA):

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

WaterTransportation (IMO/IMDG):

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None
Marine pollutant: None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status:	All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.
TSCA 12 (b) Export Notification:	None.
CERCLA/SARA Section 302 EHS:	None.
CERCLA/SARA Section 311/312:	Immediate Health Hazard, Delayed Health Hazard
CERCLA/SARA 313:	This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Lead (CAS# 7439-92-1). Ethyl benzene (CAS# 100-41-4). Xylene (CAS# 1330-20-7). Toluene (CAS# 108-88-3).
California Proposition 65:	This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

Canada Regulatory Information

CEPA DSL/NDL Status:	All components are listed on or are exempt from listing on the Domestic Substances List.
WHMIS hazard class:	D.2.A, D.2.B

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: 15

Prepared by: Regulatory Affairs

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.