



Revision Number: 003.1 Issue date: 04/02/2010

1. PRODUCT AND COMPANY IDENTIFICATION

IDH number:

234172

Product name: 246 Threadlocker High Temp/Med

Strength Oil Tolerant

Product type: Anaerobic Sealant Item number: 29514
Region: United States

Company address:Contact information:Henkel CorporationTelephone: 860.571.5100

One Henkel Way Emergency telephone: 860.571.5100 Rocky Hill, Connecticut 06067 Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

HMIS:

Physical state:LiquidHEALTH:*2Color:Opaque, BlueFLAMMABILITY:1Odor:MildPHYSICAL HAZARD:1

Personal Protection: See MSDS Section 8

WARNING: CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION.

MAY CAUSE ALLERGIC SKIN REACTION.

MAY BE HARMFUL IF SWALLOWED OR INHALED.

Relevant routes of exposure: Skin, Lungs, Eyes

Potential Health Effects

Inhalation: May cause respiratory tract irritation.

Skin contact: May cause skin irritation with discomfort or rash. Causes skin irritation. May cause allergic skin

reaction.

Eye contact: Contact with eyes will cause irritation.

Ingestion: May be harmful if swallowed.

Existing conditions aggravated by

exposure:

IDH number: 234172

Eye, skin, and respiratory disorders.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR

1910.1200).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%
Silsesquioxanes, 3-[(2-methyl-1-oxo-2-propenyl)oxy]propyl Ph, polymers with silicic acid (H4SiO4) tetra-Et ester	193486-90-7	30 - 60
Hexanedioic acid, polymer with 1,4-butanediol and 1,2- propanediol, dodecanoate	68186-73-2	10 - 30
Hydroxyalkyl methacrylate	27813-02-1	5 - 10
Maleimide resin	3006-93-7	5 - 10
2-Propenoic acid, 2-methyl-, (1-methylethylidene)	24448-20-2	1 - 5
Silica, amorphous, treated	68909-20-6	1 - 5
Cumene hydroperoxide	80-15-9	1 - 5
Saccharin	81-07-2	1 - 5
1-Acetyl-2-phenylhydrazine	114-83-0	0.1 - 1

Product name: 246 Threadlocker High Temp/Med Strength Oil Tolerant Page 1 of 5

4. FIRST AID MEASURES

Inhalation: Move to fresh air. If symptoms develop and persist, get medical attention.

Skin contact: If symptoms develop and persist, get medical attention. Wash clothing before

reuse. Remove contaminated clothing and footwear. Wash with soap and

water.

Eye contact: Get medical attention. Flush with copious amounts of water, preferably,

lukewarm water for at least 15 minutes, holding eyelids open all the time.

Ingestion: Keep individual calm. Do not induce vomiting. Get medical attention.

5. FIRE FIGHTING MEASURES

Flash point: > 93.3 °C (> 199.94 °F) Tagliabue closed cup

Autoignition temperature:

Flammable/Explosive limits - lower:

Not available

Flammable/Explosive limits - upper:

Not available

Extinguishing media: Foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear.

Unusual fire or explosion hazards: None

IDH number: 234172

Hazardous combustion products: Formaldehyde. Irritating organic vapours. Oxides of nitrogen. Oxides of

carbon.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Do not allow product to enter sewer or waterways.

Clean-up methods: Store in a partly filled, closed container until disposal. Soak up with inert

absorbent material (e.g. sand, silica gel, acid binder, universal binder,

sawdust).

7. HANDLING AND STORAGE

Handling: Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist.

Wash thoroughly after handling.

Storage: For safe storage, store at or below 38 °C (100.4 °F)

Keep in a cool, well ventilated area away from heat, sparks and open flame.

Keep container tightly closed until ready for use.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Silsesquioxanes, 3-[(2-methyl-1-oxo-2- propenyl)oxy]propyl Ph, polymers with silicic acid (H4SiO4) tetra-Et ester	None	None	None	None
Hexanedioic acid, polymer with 1,4-butanediol and 1,2-propanediol, dodecanoate	None	None	None	None
Hydroxyalkyl methacrylate	None	None	None	1 ppm TWA 3 ppm STEL
Maleimide resin	None	None	None	None
2-Propenoic acid, 2-methyl-, (1-methylethylidene)	None	None	None	None
Silica, amorphous, treated	10 mg/m3 TWA Inhalable dust.	6 mg/m3 TWA	None	None
Cumene hydroperoxide	None	None	1 ppm (6 mg/m3) TWA (SKIN)	None
Saccharin	None	None	None	None
1-Acetyl-2-phenylhydrazine	None	None	None	None

Engineering controls: No specific ventilation requirements noted, but forced ventilation may still be

required if concentrations exceed occupational exposure limits.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure

limit(s).

Eye/face protection: Safety goggles or safety glasses with side shields.

Skin protection: Natural rubber gloves. Use impermeable gloves and protective clothing as

necessary to prevent skin contact. Neoprene gloves. Butyl rubber gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid

Color: Opaque, Blue Odor: Mild Net systiable

Odor threshold: Not available pH: Not applicable

Vapor pressure:< 5 mm hg (80 °F (26.7 °C))Boiling point/range:> 300 °F (> 148.9 °C)

Melting point/ range:Not availableSpecific gravity:1.147Vapor density:Not available

Flash point: > 93.3 °C (> 199.94 °F) Tagliabue closed cup

Flammable/Explosive limits - lower:

Flammable/Explosive limits - upper:

Autoignition temperature:

Evaporation rate:

Solubility in water:

Partition coefficient (n-octanol/water):

VOC content:

Not available

Not available

Not available

2.11 %; 22 g/l

10. STABILITY AND REACTIVITY

Stability: Stable

IDH number: 234172

Hazardous reactions: Will not occur.

Hazardous decomposition products: Irritating organic vapours. Oxides of carbon. Oxides of nitrogen.

Formaldehyde.

Incompatible materials: Free radical initiators. Reducing agents. Strong alkalis. Amines. Peroxides.

Azo-compounds. Strong acids and oxidizing agents.

Conditions to avoid: See "Handling and Storage" (Section 7) and "Incompatibility" (Section 10).

Product name: 246 Threadlocker High Temp/Med Strength Oil Tolerant

Page 3 of 5

11. TOXICOLOGICAL INFORMATION

Acute oral product toxicity: LD50 (rat) > 10,000 mg/kg

Acute dermal product toxicity: LD50 (rabbit) > 5,000 mg/kg

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Silsesquioxanes, 3-[(2-methyl-1-oxo-2- propenyl)oxy]propyl Ph, polymers with silicic acid (H4SiO4) tetra-Et ester	No	No	No
Hexanedioic acid, polymer with 1,4- butanediol and 1,2-propanediol, dodecanoate	No	No	No
Hydroxyalkyl methacrylate	No	No	No
Maleimide resin	No	No	No
2-Propenoic acid, 2-methyl-, (1-methylethylidene)	No	No	No
Silica, amorphous, treated	No	No	No
Cumene hydroperoxide	No	No	No
Saccharin	No	No	No
1-Acetyl-2-phenylhydrazine	No	No	No

Hazardous components	Health Effects/Target Organs	
Silsesquioxanes, 3-[(2-methyl-1-oxo-2- propenyl)oxy]propyl Ph, polymers with silicic acid (H4SiO4) tetra-Et ester	Allergen, Irritant	
Hexanedioic acid, polymer with 1,4-butanediol and 1,2-propanediol, dodecanoate	No Records	
Hydroxyalkyl methacrylate	Irritant, Allergen	
Maleimide resin	No Target Organs	
2-Propenoic acid, 2-methyl-, (1-methylethylidene)	Irritant, Allergen	
Silica, amorphous, treated	No Target Organs	
Cumene hydroperoxide	Allergen, Central nervous system, Corrosive, Irritant, Mutagen	
Saccharin	No Target Organs	
1-Acetyl-2-phenylhydrazine	Allergen, Blood, Kidney, Mutagen, Some evidence of carcinogenicity	

12. ECOLOGICAL INFORMATION

Ecological information: Not available

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number:Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

The shipping classifications in this sections are for non-bulk packaging only (unless otherwise specified). Shipping classification may be different for bulk packaging.

U.S. Department of Transportation Ground (49 CFR)

IDH number: 234172

Proper shipping name:Not regulatedHazard class or division:NoneIdentification number:NonePacking group:None

Product name: 246 Threadlocker High Temp/Med Strength Oil Tolerant Page 4 of $5\,$

International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated

Hazard class or division:
Identification number:
Packing group:
None

Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated

Hazard class or division: None Identification number: None Packing group: None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12(b) Export Notification: None above reporting de minimus

CERCLA/SARA Section 302 EHS: None above reporting de minimus CERCLA/SARA Section 311/312: Delayed Health, Immediate Health

CERCLA/SARA 313: This product contains the following toxic chemicals subject to the reporting requirements of

section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40

CFR 372). Cumene hydroperoxide (CAS# 80-15-9).

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This

product contains a chemical known to the State of California to cause birth defects or other

reproductive harm.

Canada Regulatory Information

IDH number: 234172

CEPA DSL/NDSL Status: One or more components are not listed on, and are not exempt from listing on either the

Domestic Substances List or the Non-Domestic Substances List.

WHMIS hazard class: D.2.B

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: New Material Safety Data Sheet format

Prepared by: Kyra Kozak Woods, Manager, Regulatory Affairs

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.