



Revision Date: 06/17/2008

Issue date: 06/17/2008

### 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

<b>Product name:</b>	Loctite(R) 598 Black RTV High Performance Silicone Gasket Maker	<b>Item No. :</b>	34018 / IDH No. 274809
<b>Product type:</b>	Silicone	<b>Region:</b>	United States
<b>Company address:</b>	Henkel Corporation One Henkel Way Rocky Hill, Connecticut 06067	<b>Contact Information:</b>	Telephone: (860) 571-5100 Emergency telephone: (860) 571-5100 Internet: www.henkelna.com

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Hazardous components</u>	<u>%</u>	<u>ACGIH TLV</u>	<u>OSHA PEL</u>	<u>OTHER</u>
Silicone Resin Proprietary	30-60	None	None	None
Reinforcing Filler Proprietary	30-60	10 mg/m <sup>3</sup> TWA (particulate matter containing no asbestos and <1% crystalline silica)	15 mg/m <sup>3</sup> TWA total 5 mg/m <sup>3</sup> TWA	None
Silicone Resin Proprietary	10-30	None	None	None
Filler Proprietary	5-10	None	None	None
Oximino silaneProprietary	1-5	None	None	None
Carbon black 1333-86-4	0.1-1	3.5 mg/m <sup>3</sup> TWA	3.5 mg/m <sup>3</sup> TWA	None

Exposure to moisture during cure will release 0.1 - 0.9% methyl alcohol. Methyl ethyl ketoxime(MEKO) is formed during cure. This product will release up to 5% MEKO.

### 3. HAZARDS IDENTIFICATION

#### EMERGENCY OVERVIEW

**Physical state:** Paste  
**Color:** Black  
**Odor:** Mild

#### HMIS:

**HEALTH:** 2\*  
**FLAMMABILITY:** 1  
**PHYSICAL HAZARD:** 0  
**Personal Protection:** See Section 8

**WARNING:** PROLONGED OR REPEATED CONTACT WITH UNCURED SEALANT MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.  
REPEATED OR PROLONGED CONTACT MAY CAUSE ALLERGIC SKIN REACTION.

**Relevant routes of exposure:** Skin, Inhalation, Eyes

#### Potential Health Effects

**Item No. :** 34018 / IDH No. 274809

**Product name:** Loctite(R) 598 Black RTV High Performance Silicone Gasket  
Maker

<b>Inhalation:</b>	Vapors and mists will irritate the respiratory tract and nasal passages. When heated to temperatures exceeding 300° F (150° C) in the presence of air, silicones may form formaldehyde vapors. Formaldehyde is a potential cancer hazard and a known skin and respiratory sensitizer. Vapors irritate the eyes, nose and throat. Safe handling conditions may be maintained by keeping formaldehyde vapor concentrations below the OSHA permissible limit. The silane is a skin and eye irritant and prolonged contact may cause eye and skin burns. The low concentration makes such overexposure unlikely and minimizes its affect on health and safety.
<b>Skin contact:</b>	Prolonged or repeated contact with uncured sealant may cause skin irritation. Repeated or prolonged skin contact may result in allergic sensitization.
<b>Eye contact:</b>	Vapors may irritate eyes. Contact with eyes will cause irritation.
<b>Ingestion:</b>	Not expected under normal conditions of use. May be harmful if swallowed.
<b>Existing conditions aggravated by exposure:</b>	Skin disorders.

**See Section 11 for additional toxicological information.**

#### 4. FIRST AID MEASURES

<b>Inhalation:</b>	Remove to fresh air. If discomfort persists seek medical attention.
<b>Skin contact:</b>	Wipe off paste with paper towel or cloth. Wash with soap and water. Get medical attention if symptoms develop and persist.
<b>Eye contact:</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, consult a specialist.
<b>Ingestion:</b>	Do not induce vomiting. Get medical attention if symptoms develop and persist.

#### 5. FIRE-FIGHTING MEASURES

<b>Flash point:</b>	Greater than 93°C (200°F) Tagliabue closed cup
<b>Autoignition temperature:</b>	Not available
<b>Flammable/Explosive limits-lower %:</b>	Not applicable
<b>Flammable/Explosive limits-upper %:</b>	Not applicable
<b>Extinguishing media:</b>	Carbon dioxide (CO2). Foam. Dry chemical.
<b>Special fire fighting procedures:</b>	Wear self contained breathing apparatus
<b>Unusual fire or explosion hazards:</b>	None
<b>Hazardous combustion products:</b>	Oxides of silicon. Oxides of carbon. Formaldehyde.

#### 6. ACCIDENTAL RELEASE MEASURES

<b>Environmental precautions:</b>	Do not flush into surface water or sanitary sewer system.
<b>Clean-up methods:</b>	Scrape up as much material as possible. Maintain good ventilation for large spills. Store in a partly filled, closed container until disposal.

## 7. HANDLING AND STORAGE

<b>Handling:</b>	Avoid contact with eyes, skin and clothing. Avoid breathing vapor and mist. Wash thoroughly after handling. Do not wear contact lenses.
<b>Storage:</b>	Store in a dry area below 90° F Keep container closed.
<b>Incompatible products:</b>	Never allow product to get in contact with water during storage.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

<b>Engineering controls:</b>	Use local exhaust ventilation to maintain airborne concentrations below established exposure limits.
<b>Respiratory protection:</b>	Use a NIOSH approved air-purifying respirator if the potential to exceed established exposure limits exists. Use a NIOSH approved air-purifying respirator with an organic vapor cartridge.
<b>Skin protection:</b>	Impervious clothing Nitrile gloves. Natural rubber gloves. Butyl rubber gloves.
<b>Eye/face protection:</b>	Safety goggles or safety glasses with side shields.

See Section 2 for exposure limits.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical state:</b>	Paste
<b>Color:</b>	Black
<b>Odor:</b>	Mild
<b>Vapor pressure:</b>	<5 mmHg @20°C (68° F)
<b>pH:</b>	Not applicable
<b>Boiling point/range:</b>	Not applicable
<b>Melting point/range:</b>	Not available
<b>Specific gravity:</b>	1.3 at 20 deg. C
<b>Vapor density:</b>	Heavier than air
<b>Evaporation rate:</b>	Not available
<b>Solubility in water:</b>	Polymerizes in presence of water
<b>Partition coefficient (n-octanol/water):</b>	Not available
<b>VOC content:</b>	3.31%; 40.69 grams/liter

## 10. STABILITY AND REACTIVITY

<b>Stability:</b>	Stable.
<b>Hazardous polymerization:</b>	Will not occur.
<b>Hazardous decomposition products:</b>	Oxides of carbon. Oxides of silicon. Formaldehyde. Methyl ethyl ketoxime formed during cure.
<b>Incompatibility:</b>	Polymerizes on contact with water.
<b>Conditions to avoid:</b>	Moisture.

## 11. TOXICOLOGICAL INFORMATION

### Carcinogen Status

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen
Silicone Resin Proprietary	No	No	No
Reinforcing Filler Proprietary	No	No	No
Silicone Resin Proprietary	No	No	No
Filler Proprietary	No	No	No
Oximino silaneProprietary	No	No	No
Carbon black 1333-86-4	No	Group 2B	Yes

#### **Literature Referenced Target Organ & Other Health Effects**

Hazardous components	Health Effects/Target Organs
Silicone Resin Proprietary	No Target Organs
Reinforcing Filler Proprietary	Nuisance dust
Silicone Resin Proprietary	Irritant
Filler Proprietary	No Target Organs
Oximino silaneProprietary	Allergen, Irritant
Carbon black 1333-86-4	Respiratory, Some evidence of carcinogenicity

## **12. ECOLOGICAL INFORMATION**

### **Ecological information:**

No specific studies have been conducted by Henkel on the ecotoxicity or environmental fate of this material; however, commonly available data on the material indicate that uncontrolled releases to soil, groundwater, or surface waters could entail acute and/or chronic ecological effects, depending on the quantity and concentration of such releases. Releases of volatile components to the atmosphere are not believed to entail significant ecological consequences provided such releases are within the exposure levels set forth in this document. Accordingly, all appropriate measures should be taken to avoid uncontrolled releases to the environment, and any spills or other uncontrolled releases which may occur should be contained and cleaned up immediately in accordance with Section 6.

## **13. DISPOSAL CONSIDERATIONS**

**Information provided is for unused product only.**

**Recommended method of disposal:** Cured rubber can be incinerated or landfilled following EPA and local regulations.

**EPA hazardous waste number:** Not a RCRA hazardous waste.

## **14. TRANSPORT INFORMATION**

### **U.S. Department of Transportation Ground (49 CFR):**

**Proper shipping name:** Unrestricted  
**Hazard class or division:** None  
**Identification number:** None  
**Packing group:** None

### **International Air Transportation (ICAO/IATA):**

**Proper shipping name:** Unrestricted  
**Hazard class or division:** None

**Item No. :** 34018 / IDH No. 274809

**Product name:** Loctite(R) 598 Black RTV High Performance Silicone Gasket  
**Maker**

Identification number: None  
Packing group: None

**WaterTransportation (IMO/IMDG):**

Proper shipping name: Unrestricted  
Hazard class or division: None  
Identification number: None  
Packing group: None  
*Exceptions:* None  
Marine pollutant: None

## 15. REGULATORY INFORMATION

**United States Regulatory Information**

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.  
TSCA 12 (b) Export Notification: None.

CERCLA/SARA Section 302 EHS: None above reporting de minimus.  
CERCLA/SARA Section 311/312: Immediate Health Hazard, Delayed Health Hazard  
CERCLA/SARA 313: None above reporting de minimus.

California Proposition 65: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

**Canada Regulatory Information**

CEPA DSL/NDL Status: One or more components are not listed on, and are not exempt from listing on either the Domestic Substances List or the Non-Domestic Substances List.  
WHMIS hazard class: D.2.A, D.2.B

## 16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: 2,3,8,15

Prepared by: Regulatory Affairs

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.