Material Safety Data Sheet

Henkel Technologies

Revision Date: 01/16/2007 **Issue date:** 01/16/2007

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product name: HYSOL 1X PELLETS 40 LB CT
Product type: Industrial Hot Melt Adhesive
Company address:
Henkel Corporation
1001 Trout Brook Crossing
Rocky Hill, Connecticut 06067

Item No. : 83358 / IDH No. 420383
Region: United States
Contact Information:
Telephone: 860.571.5100
Emergency telephone: 860.571.5100
Internet: www.loctite.com

2. COMPOSITION/INFORMATION ON INGREDIENTS

Non hazardous components
EVA Hotmelt Adhesive Blend

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

HMIS:

Physical state:	Solid	**HEALTH:**	1
Color:	Yellow	**FLAMMABILITY:**	0
Odor:	Slight	**PHYSICAL HAZARD:**	0
		Personal Protection:	See Section 8

WARNING: MOLTEN ADHESIVE MAY CAUSE SEVERE BURNS.

Relevant routes of exposure: Molten adhesive, Skin, Eyes, Solid adhesive has no hazards

Potential Health Effects

Inhalation: Continuous breathing of vapors above molten adhesive may irritate mucous membranes. Dusts from solid adhesive may cause irritation.

Skin contact: Molten adhesive may cause severe burns. Solid adhesive has no hazards

Eye contact: Molten adhesive in eyes will cause severe and permanant damage Can cause mechanical irritation if dusts are generated.

Ingestion: Not expected to be harmful by ingestion.

Existing conditions aggravated by exposure: None known

See Section 11 for additional toxicological information.

4. FIRST AID MEASURES

Inhalation: Move to fresh air in case of accidental inhalation of dust or fumes from overheating or combustion. If breathing is difficult, give oxygen. If not breathing, give artificial respiration.

Skin contact: Thermal burn hazard from molten adhesive Cool melted product on skin with plenty of water. Do not remove solidified product. Cover affected areas with clean sheeting or gauze and seek immedate medical attention No attempt should be made to remove material from skin or to remove contaminated clothing as damaged skin can be easily torn

Eye contact: If eye contact occurs with molten material immediately cool with water. Do not remove adhesive. Seek medical attention.

Ingestion: Ingestion of solid adhesive is not expected to be hazardous. Get medical attention if symptoms develop and persist.

5. FIRE-FIGHTING MEASURES

Flash point: Greater than 232ºC (450ºF)

Autoignition temperature: Not applicable

Flammable/Explosive limits-lower %: Not applicable

Flammable/Explosive limits-upper %: Not applicable

Extinguishing media: Use extinguishing meaures appropriate to local circumstances and the surrounding environment. Water spray (fog), foam, dry chemical or carbon dioxide.

Special fire fighting procedures: None

Unusual fire or explosion hazards: None

Hazardous combustion products: Oxides of carbon. Acrid smoke and fumes.

6. ACCIDENTAL RELEASE MEASURES

Environmental precautions: No special environmental precautions required. Do not allow material to contaminate ground water system.

Clean-up methods: Health injuries are not known or expected under normal use Sweep up spilled material. Avoid creating dust.

7. HANDLING AND STORAGE

Handling: Avoid contact with molten material. Always be careful around molten material. Do not place wet or damp solid into melt tank. Follow suggested application temperature. Do not wear contact lenses.

Storage: Do not store above 38°C (100°F).

Incompatible products: No special restrictions on storage with other products.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering controls: Ventilation hoods and fans required when working with organic solvents or in hot melt applications. Heat only in areas with appropriate exhaust ventilation.

Respiratory protection: Respirator with combination filter for vapour/particulate. In case of insufficient ventilation wear suitable respiratory equipment.

Skin protection: Insulated gloves and long sleeved clothing are strongly recommended when working with molten adhesive.

Eye/face protection: Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Do not wear contact lenses when handling this product.

See Section 2 for exposure limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Solid
Color:	Yellow
Odor:	Slight
Vapor pressure:	Not applicable
pH:	Not applicable
Boiling point/range:	Not available
Melting point/range:	110.2°C (230°F)
Specific gravity:	0.96
Vapor density:	Not available
Evaporation rate:	Not applicable
Solubility in water:	Insoluble.
Partition coefficient (n-octanol/water):	Not available
VOC content:	Zero

10. STABILITY AND REACTIVITY

Stability: Stable.

Hazardous polymerization: Will not occur.

Hazardous decomposition products: None under normal use.

Incompatability: Avoid heating above 400 Degrees F

Conditions to avoid: Prolonged heating at temperatures above 200 °C.

11. TOXICOLOGICAL INFORMATION

Product toxicity data: Loctite is not aware of any toxicity data on the specific mixture of chemical components contained in this product.

Carcinogen Status

Literature Referenced Target Organ & Other Health Effects

12. ECOLOGICAL INFORMATION

Ecological information: No specific studies have been conducted by Henkel on the ecotoxicity or environmental fate of this material; however, commonly available data on the material indicate that uncontrolled releases to soil, groundwater, or surface waters could entail acute and/or chronic ecological effects, depending on the quantity and concentration of such releases. Releases of volatile components to the atmosphere are not believed to entail significant ecological consequences provided such releases are within the exposure levels set forth in this document. Accordingly, all appropriate measures should be taken to avoid uncontrolled releases to the environment, and any spills or other uncontrolled releases which may occur should be contained and cleaned up immediately in accordance with Section 6.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Dispose of in accordance with Federal, State and local regulations.

EPA hazardous waste number: Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

U.S. Department of Transportation Ground (49 CFR):

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

International Air Transportation (ICAO/IATA):

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

WaterTransportation (IMO/IMDG):

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None
Exceptions:	None
Marine pollutant:	None known

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.
TSCA 12 (b) Export Notification: None.

CERCLA/SARA Section 302 EHS: None.
CERCLA/SARA Section 311/312: Immediate Health Hazard
CERCLA/SARA 313: None.

California Proposition 65: No California Proposition 65 listed chemicals are known to be present.

Canada Regulatory Information

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Domestic Substances List.
WHMIS hazard class: D.2.B

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: New Material Safety Data Sheet format.

Prepared by: Lou Fabrizio, Senior Health & Regulatory Affairs Specialist

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.