Material Safety Data Sheet





Revision Number: 004.0 Issue date: 04/28/2009

1. PRODUCT AND COMPANY IDENTIFICATION

3926 Light Cure Medical Device Product name:

Adhesive Visible/UV Cure Fluorescent

Product type: Ultraviolet adhesive

Company address: Henkel Corporation 1001 Trout Brook Crossing Rocky Hill, Connecticut 06067 IDH number: 434108

36492 Item number: Region: **United States**

Contact information: Telephone: 860.571.5100

Emergency telephone: 860.571.5100 Internet: www.henkelna.com

HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

HEALTH: Physical state: *2 Liquid 2 Color: Transparent, Hazy FLAMMABILITY: PHYSICAL HAZARD: Odor: Mild

> **Personal Protection:** See MSDS Section 8

WARNING: COMBUSTIBLE LIQUID AND VAPOR.

HARMFUL IF SWALLOWED. ABSORBED THROUGH SKIN OR INHALED.

DO NOT SPRAY. DO NOT HEAT.

MAY CAUSE ALLERGIC SKIN REACTION.

CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION.

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects

Inhalation: Modified acrylamide is harmful if inhaled. Causes respiratory tract irritation. Vapors and mists

will irritate nose and throat and possibly eyes. Headache. Nausea. DO NOT heat or spray as

this increases the inhalation hazard.

Modified acrylamide may be absorbed through skin in harmful amounts. Toxic. May cause Skin contact:

allergic skin reaction. Causes skin irritation.

Eye contact: Causes eye irritation.

Ingestion: Modified acrylamide is harmful if swallowed. Toxic.

Existing conditions aggravated by

exposure:

IDH number: 434108

Eye, skin, and respiratory disorders.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR

1910.1200).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%
Urethane Polymer	Proprietary	30 - 60
Acrylate monomer	Proprietary	30 - 60
Modified acrylamide	2680-03-7	10 - 30
Photoinitiator	947-19-3	1 - 5
Substituted silane	Proprietary	1 - 5
Silica, amorphous, fumed, crystal-free	112945-52-5	1 - 5
Photoinitiator	Proprietary	1 - 5
2-Hydroxyethyl acrylate	818-61-1	0.1 - 1

4. FIRST AID MEASURES

Inhalation: Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give

artificial respiration. If symptoms develop and persist, get medical attention.

Skin contact: Immediately flush skin with plenty of water (using soap, if available). Remove

contaminated clothing and footwear. Wash clothing before reuse. If symptoms

develop and persist, get medical attention.

Eye contact: Flush with copious amounts of water, preferably, lukewarm water for at least

15 minutes, holding eyelids open all the time. Get immediate medical

attention.

Ingestion: Do not induce vomiting. Keep individual calm. Never give anything by mouth

to an unconscious person. Get immediate medical attention.

5. FIRE FIGHTING MEASURES

Flash point: 80 °C (176°F) Pensky Martens closed cup

Autoignition temperature:

Flammable/Explosive limits - lower:

Not available
Flammable/Explosive limits - upper:

Not available

Extinguishing media: Foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear.

Uncontrolled polymerization may occur at high temperatures resulting in

explosions or rupture of storage containers.

Hazardous combustion products: Oxides of carbon. Oxides of nitrogen. Oxides of silicon. Oxides of phosphorus.

Formaldehyde.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Remove all sources of ignition. Do not allow product to enter sewer or

waterways.

Clean-up methods: Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up.

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Store in a partly filled, closed container until

disposal.

7. HANDLING AND STORAGE

Handling: Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist.

Wash thoroughly after handling. Do not taste or swallow. DO NOT heat or spray. Use only with adequate ventilation. Refer to Section 8. Use only in area

provided with appropriate exhaust ventilation.

Storage: For safe storage, store at or below 26 °C (78.8 °F)

Keep in a cool, well ventilated area away from heat, sparks and open flame.

Keep container tightly closed until ready for use.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Urethane Polymer	None	None	None	None
Acrylate monomer	None	None	None	None
Modified acrylamide	None	None	None	0.1 mg/m3 TWA (Skin) 0.025 ppm TWA (Skin)
Photoinitiator	None	None	None	None
Substituted silane	None	None	None	None
Silica, amorphous, fumed, crystal-free	10 mg/m3 TWA Inhalable dust. 3 mg/m3 TWA Respirable fraction.	20 MPPCF TWA 0.8 mg/m3 TWA	None	None
Photoinitiator	None	None	None	None
2-Hydroxyethyl acrylate	None	None	None	None

Engineering controls: Local exhaust ventilation is recommended when general ventilation is not

sufficient to control airborne contamination below occupational exposure

limits.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure

limit(s). If this material is handled at elevated temperatures or under mist forming conditions, without engineering controls, a NIOSH approved respirator

must be used.

Eye/face protection: Safety goggles or safety glasses with side shields. Wear chemical goggles;

face shield (if splashing is possible).

Skin protection:Use impermeable gloves and protective clothing as necessary to prevent skin

contact. Neoprene gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid

Color: Transparent, Hazy
Odor: Mild

Odor: Mild
Odor threshold: Not available
pH: Not applicable
Vapor pressure: Not available

Boiling point/range: > 93.3 °C (> 199.9 °F)

Melting point/ range:Not availableSpecific gravity:1.0816Vapor density:Not available

Flash point: 80 °C (176°F) Pensky Martens closed cup

Flammable/Explosive limits - lower: Not available Flammable/Explosive limits - upper: Not available

IDH number: 434108

 Autoignition temperature:
 Not available

 Evaporation rate:
 Not available

 Solubility in water:
 Slight

Partition coefficient (n-octanol/water): Not available

 VOC content:
 0.52 %; 5.62 g/l (process)

 0.48 %; 5.19 g/l (potential)

 1.0 %; 10.82 g/l (total)

(ASTM D5403)

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions of storage and use.

Hazardous reactions: May occur.

Hazardous decomposition products: Oxides of carbon. Oxides of nitrogen. Oxides of silicon. Formaldehyde.

Incompatible materials: Strong acids. Strong oxidizing agents. Reducing agents. Bases. Peroxides.

Free radical initiators. Other polymerization initiators.

Conditions to avoid: Keep away from heat, spark and flame. Avoid temperatures above 26°C

(80°F). Store away from incompatible materials.

11. TOXICOLOGICAL INFORMATION

Acute oral product toxicity: Modified acrylamide LD50 (rat) 316 mg/kg

Acute dermal product toxicity: Modified acrylamide LD50 (rabbit) 518 mg/kg

Acute inhalation product toxicity: Modified acrylamide LC50 (rat) 1 h > 776 ppm (vapor)

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Urethane Polymer	No	No	No
Acrylate monomer	No	No	No
Modified acrylamide	No	No	No
Photoinitiator	No	No	No
Substituted silane	No	No	No
Silica, amorphous, fumed, crystal-free	No	No	No
Photoinitiator	No	No	No
2-Hvdroxvethvl acrylate	No	No	No

Hazardous components	Health Effects/Target Organs
Urethane Polymer	No Records
Acrylate monomer	Irritant, Allergen
Modified acrylamide	Irritant, Eyes, Mutagen, Kidney, Less weight gain and food intake.
Photoinitiator	No Records
Substituted silane	Irritant, Allergen
Silica, amorphous, fumed, crystal-free	Nuisance dust
Photoinitiator	No Records
2-Hydroxyethyl acrylate	Allergen, Central nervous system, Heart, Irritant, Kidney, Liver, Lung, Some evidence of carcinogenicity, Spleen

12. ECOLOGICAL INFORMATION

Ecological information: Not available

IDH number: 434108

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Dispose of according to Federal, State and local governmental regulations.

Hazardous waste number:Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

The shipping classification in this section are for bulk packaging only. Shipping classification may be different for non-bulk packaging as exceptions may apply. Refer to shipping documents for package specific transportation classification.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Combustible liquid, n.o.s. (Modified Acrylamide)

Hazard class or division: Combustible Liquid

Identification number: NA 1993
Packing group: III

International Air Transportation (ICAO/IATA)

Proper shipping name:
Hazard class or division:
Identification number:
Packing group:
Not regulated
None
None
None

Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated

Hazard class or division: None Identification number: None Packing group: None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12(b) Export Notification: None above reporting de minimus

CERCLA/SARA Section 302 EHS:
CERCLA/SARA Section 311/312:
CERCLA/SARA 313:

None above reporting de minimus
Immediate Health, Delayed Health, Fire
None above reporting de minimus

California Proposition 65: No California Proposition 65 listed chemicals are known to be present.

Canada Regulatory Information

IDH number: 434108

CEPA DSL/NDSL Status: Contains one or more components listed on the Non-Domestic Substances List. All other

components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities.

Please contact Regulatory Affairs for additional details.

WHMIS hazard class: B.3, D.1.B, D.2.B

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: New Material Safety Data Sheet format. 2-5, 8-11, 14, 15

Prepared by: Jennifer Glieco, Regulatory Affairs Specialist

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

IDH number: 434108