## **Material Safety Data Sheet**



Henkel

Revision Number: 002.1

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: Product type: Silver Anti-Seize Lubricant

**Company address:** Henkel Corporation 1001 Trout Brook Crossing Rocky Hill, Connecticut 06067 IDH number: 531668 Item number: 38181 Region: United States Contact information: Telephone: 860.571.5100 Emergency telephone: 860.571.5100 Internet: www.henkelna.com

#### 2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW HMIS:				
Physical state: Color:	Paste Silver		HEALTH: FLAMMABILITY:	1
Odor:	Hydrocarbo	on-like	PHYSICAL HAZARD:	1 Case MCDC Continue 0
WARNING:	CA	USES EYE, SKIN	Personal Protection: AND RESPIRATORY TRACT	See MSDS Section 8 IRRITATION.
Relevant routes of exposure:		Skin, Inhalation, Eye	25	
Potential Health Effects				
Inhalation: Skin contact Eye contact: Ingestion:	-		on.	
Existing conditions aggravated by exposure:		Eye, skin, and respir	ratory disorders.	
		This material is cons 1910.1200).	idered hazardous by the OSHA Hazard	d Communication Standard (29 CFR

See Section 11 for additional toxicological information.

Hazardous components	CAS NUMBER	%
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	10 - 30
Graphite	7782-42-5	10 - 30
Calcium oxide	1305-78-8	10 - 30
Mineral oil light naphthenic hydrotreat. <3% DMSO	64742-53-6	10 - 30
Aluminum not powder, dust or fume	7429-90-5	5 - 10
Distillates (petroleum), straight-run middle	64741-44-2	1 - 5
Quartz (SiO2)	14808-60-7	0.1 - 1

3. COMPOSITION / INFORMATION ON INGREDIENTS

## 4. FIRST AID MEASURES

Inhalation:	Move to fresh air. If symptoms persist, seek medical advice.
Skin contact:	If symptoms develop and persist, get medical attention. Wash with soap and water.

Eye contact:	Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.	
Ingestion:	Do not induce vomiting. Get immediate medical attention.	
5. FIRE FIGHTING MEASURES		
Flash point:	> 93 °C (> 199.4 °F)	
Autoignition temperature:	Not determined	
Flammable/Explosive limits - lower:	Not available	
Flammable/Explosive limits - upper:	Not available	
Extinguishing media:	Dry chemical. Carbon dioxide. Foam.	
Special firefighting procedures:	None	
Unusual fire or explosion hazards:	None	
Hazardous combustion products:	Oxides of carbon. Oxides of nitrogen.	
6. ACCI	DENTAL RELEASE MEASURES	
Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.		
Environmental precautions:	Prevent further leakage or spillage if safe to do so.	
Clean-up methods:	Store in a partly filled, closed container until disposal. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder,	

#### 7. HANDLING AND STORAGE

Handling:

Storage:

Keep in a cool, well ventilated area.

Keep away from heat, spark and flame. Avoid skin and eye contact.

sawdust). Remove all sources of ignition.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Distillates (petroleum), hydrotreated heavy naphthenic	5 mg/m3 TWA mist 10 mg/m3 STEL mist	5 mg/m3 TWA mist	None	None
Graphite	2 mg/m3 TWA Respirable fraction.	5 mg/m3 TWA Respirable fraction. 15 mg/m3 TWA Total dust. 15 MPPCF TWA	None	None
Calcium oxide	2 mg/m3 TWA	5 mg/m3 TWA	None	None
Mineral oil light naphthenic hydrotreat. <3% DMSO	5 mg/m3 TWA Mist. 10 mg/m3 STEL Mist.	500 ppm (2,000 mg/m3) TWA	None	None
Aluminum not powder, dust or fume	1 mg/m3 TWA Respirable fraction.	15 mg/m3 TWA (as Al) Total dust. 5 mg/m3 TWA (as Al) Respirable dust.	None	None
Distillates (petroleum), straight-run middle	5 mg/m3 TWA mist 10 mg/m3 STEL mist	5 mg/m3 TWA mist	None	None
Quartz (SiO2)	0.025 mg/m3 TWA Respirable fraction.	2.4 MPPCF TWA Respirable. 0.1 mg/m3 TWA Respirable. 0.3 mg/m3 TWA Total dust.	None	None

Engineering controls:

Respiratory protection:

Use local ventilation if general ventilation is insufficient to maintain vapor concentration below established exposure limits.

Eye/face protection:

Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

Safety goggles or safety glasses with side shields.

Skin protection:

Neoprene or oil resistant gloves.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Color: Odor: Odor threshold: pH: . Vapor pressure: Boiling point/range: Melting point/ range: Specific gravity: Vapor density: Flash point: Flammable/Explosive limits - lower: Flammable/Explosive limits - upper: Autoignition temperature: Evaporation rate: Solubility in water: Partition coefficient (n-octanol/water): **VOC content:** 

Paste Silver Hydrocarbon-like Not available Not applicable < 5 mm hg Not available Not available 1.25 Not available > 93 °C (> 199.4 °F) Not available Not available Not determined Not available Insoluble Not determined 12.96 %; 162 g/l

#### **10. STABILITY AND REACTIVITY**

Stability:

Stable

Hazardous reactions:

Will not occur.

Hazardous decomposition products:

Incompatible materials:

Conditions to avoid:

Strong oxidizing agents.

None reasonably foreseeable.

None known

### 11. TOXICOLOGICAL INFORMATION

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Distillates (petroleum), hydrotreated heavy naphthenic	No	No	No
Graphite	No	No	No
Calcium oxide	No	No	No
Mineral oil light naphthenic hydrotreat. <3% DMSO	No	No	No
Aluminum not powder, dust or fume	No	No	No
Distillates (petroleum), straight-run middle	No	No	No
Quartz (SiO2)	Known carcinogen.	Group 1	No

Hazardous components	Health Effects/Target Organs	
Distillates (petroleum), hydrotreated heavy naphthenic	Irritant	
Graphite	Lung	
Calcium oxide	Irritant, Corrosive, Eyes	
Mineral oil light naphthenic hydrotreat. <3% DMSO	Irritant	
Aluminum not powder, dust or fume	Central nervous system, Irritant, Lung	
Distillates (petroleum), straight-run middle	Irritant	
Quartz (SiO2)	Immune system, Lung, Some evidence of carcinogenicity	

#### 12. ECOLOGICAL INFORMATION

Ecological information:

Not available

#### **13. DISPOSAL CONSIDERATIONS**

#### Information provided is for unused product only.

Recommended method of disposal:

Hazardous waste number:

Follow all local, state, federal and provincial regulations for disposal.

# 14. TRANSPORT INFORMATION

Not a RCRA hazardous waste.

#### U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Hazard class or division: Identification number: Packing group: Not regulated None None None

#### International Air Transportation (ICAO/IATA)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

Proper shipping name: Hazard class or division: Identification number: Packing group:	Not regulated None None None
	15. REGULATORY INFORMATION
United States Regulatory Information	
TSCA 8 (b) Inventory Status:	All components are listed or are exempt from listing on the Toxic Substances Control Act
TSCA 12(b) Export Notification:	Inventory. None above reporting de minimus
CERCLA/SARA Section 302 EHS: CERCLA/SARA Section 311/312:	None above reporting de minimus Immediate Health

CERCLA/SARA 313:	This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Aluminum not powder, dust or fume (CAS# 7429-90-5).	
California Proposition 65:	This product contains a chemical known in the State of California to cause cancer.	
Canada Regulatory Information		
CEPA DSL/NDSL Status:	All components are listed on or are exempt from listing on the Canadian Domestic	

#### **16. OTHER INFORMATION**

This material safety data sheet contains changes from the previous version in sections: Not available

Substances List.

D.2.A, D.2.B

Prepared by: C.J. Michaels, Manager, Regulatory Affairs

Water Transportation (IMO/IMDG)

WHMIS hazard class:

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.