

Material Safety Data Sheet



39152 / IDH No. 640484

el) Technologies

Revision Date: 09/12/2008

Issue date: 09/12/2008

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

 Product name:
 Quickstix(TM) 548(TM) Gasket Eliminator Flange Sealant
 Item No.:

 Product type:
 Anaerobic Adhesive
 Region:

 Company address:
 Contact In

 Usersel Company
 Telephone
 Telephone

Henkel Corporation 1001 Trout Brook Crossing Rocky Hill, Connecticut 06067

Region:United StatesContact Information:Telephone:860.571.5100Emergency telephone:860.571.5100Internet:www.loctite.com

2. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Hazardous components</u> Polyurethane methacrylate resin Unknown	<u>%</u> 30-60	ACGIH TLV None	OSHA PEL None	OTHER None
Polyglycol dimethacrylate Proprietary	30-60	None	None	None
Thixotropic agent UNKNOWN	5-10	None	None	None
Acrylic acid 79-10-7	1-5	2 ppm TWA (skin)	10 ppm TWA; 30 mg/m ³	1 ppm TWA (skin); 3 ppm STEL (skin)
Cumene hydroperoxide 80-15-9	1-5	None	None	1 ppm (6 mg/m ³) Skin (WEEL)
Silica, amorphous, fumed, crystalline-free 112945-52-5	1-5	10mg/m ³ TWA inhalable 3mg/m ³ TWA respirable	6mg/m ³ TWA	None
1-Acetyl-2-phenylhydrazine 114-83-0	0.1-1	None	None	None

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW			
		HMIS:	
Physical state:	Solid	HEALTH:	2*
Color:	Orange	FLAMMABILITY:	1
Odor:	Sharp	PHYSICAL HAZARD:	1
		Personal Protection:	See Section 8
WARNING):	CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION	
		MAY CAUSE ALLERGIC SKIN REACTION.	
		MAY BE HARMFUL IF SWALLOWED.	

Relevant routes of exposure:

Skin, Inhalation, Eyes

Potential Health Effects

Inhalation: Skin contact:	May cause irritation to nose and throat. Irritating to skin. May cause allergic skin reaction.
Eye contact:	Vapors may irritate eyes. Contact with eyes will cause irritation.
Ingestion:	May cause gastrointestinal tract irritation if swallowed.

Item No. : 39152 / IDH No. 640484

Product name: Quickstix(TM) 548(TM) Gasket Eliminator Flange Sealant

Existing conditions aggravated by exposure:

Eye, skin, and respiratory disorders. Acrylic acid: Respiratory disorders. Lung disease.

See Section 11 for additional toxicological information.

4. FIRST AID MEASURES Remove to fresh air. If symptoms develop and persist, get medical attention.		
Week with even and water. Demove conteminated elething and choose Week elething before revea		
Wash with soap and water. Remove contaminated clothing and shoes. Wash clothing before reuse. Get medical attention if symptoms occur.		
Flush with copious amounts of water, preferably, lukewarm water for at least 15 minutes, holding eyelids open all the time. Get medical attention.		
Do not induce vomiting. Keep individual calm. Obtain medical attention.		
5. FIRE-FIGHTING MEASURES		
Not classified as a flammable solid per DOT Classification Guidelines Part 173 Appendix H 7/10/2002.		
Not available		
Not available		
Not available		
Foam, dry chemical or carbon dioxide.		
Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.		
None		
Oxides of carbon. Oxides of sulfur. Oxides of nitrogen. Irritating organic vapors.		
6. ACCIDENTAL RELEASE MEASURES		
Prevent product from entering drains or open waters.		
Ensure adequate ventilation. Soak up with inert absorbent. Store in a partly filled, closed container until disposal.		
7. HANDLING AND STORAGE		
Avoid contact with eyes, skin and clothing. Do not breathe mist or vapors.		
For safe storage, store at or below 38°C (100°F).		
Refer to Section 10.		
on product shelf life contact Henkel Customer Service at (800) 243-4874.		
8. EXPOSURE CONTROLS / PERSONAL PROTECTION		
Use local exhaust ventilation to maintain airborne concentrations below established exposure limits.		
Use NIOSH approved respirator if there is potential to exceed exposure limit(s).		
Use impermeable gloves and protective clothing as necessary to prevent skin contact. Neoprene gloves. Butyl rubber gloves. Natural rubber gloves.		

Safety goggles or safety glasses with side shields.

Eye/face protection:

Item No. : 39152 / IDH No. 640484

Product name: Quickstix(TM) 548(TM) Gasket Eliminator Flange Sealant 2 of 5 $\,$

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Solid
Color:	Orange
Odor:	Sharp
Vapor pressure:	Not available
pH:	Not applicable
Boiling point/range:	Not available
Melting point/range:	1.1274
Specific gravity:	Not available
Vapor density:	Not available
Evaporation rate:	Not available
Solubility in water:	Not soluble
Partition coefficient (n-octanol/water):	Not available
VOC content:	0.8911%; 8.5060 grams/liter

10. STABILITY AND REACTIVITY

Stability:	Stable.
Hazardous polymerization:	Will not occur.
Hazardous decomposition products:	Oxides of carbon. Oxides of sulfur. Oxides of nitrogen. Irritating organic vapors.
Incompatability:	Strong oxidizers. Strong reducing agents. Strong alkalis. Other polymerization initiators.
Conditions to avoid:	See "Handling and Storage" (Section 7) and "Incompatabilty" (Section 10).

11. TOXICOLOGICAL INFORMATION

Product toxicity data:

Acute LD50 (oral) :Greater than 5000 (rat). (estimated). Acute dermal LD50 greater than 2000 mg/kg (rabbit) (estimated).

Carcinogen Status

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen
Polyurethane methacrylate resin Unknown	No	No	No
Polyglycol dimethacrylate Proprietary	No	No	No
Thixotropic agent UNKNOWN	No	No	No
Acrylic acid 79-10-7	No	No	No
Cumene hydroperoxide 80-15-9	No	No	No
Silica, amorphous, fumed, crystalline-free 112945-52-5	No	No	No
1-Acetyl-2-phenylhydrazine 114-83-0	No	No	No

Literature Referenced Target Organ & Other Health Effects

Hazardous components	Health Effects/Target Organs
Polyurethane methacrylate resin Unknown	Allergen, Irritant
Polyglycol dimethacrylate Proprietary	Allergen, Irritant
Thixotropic agent UNKNOWN	No data
Acrylic acid 79-10-7	Allergen, Corrosive, Irritant, Kidney, Liver
Cumene hydroperoxide 80-15-9	Allergen, Central nervous system, Corrosive, Irritant, Mutagen
Silica, amorphous, fumed, crystalline-free 112945-52-5	Nuisance dust
1-Acetyl-2-phenylhydrazine 114-83-0	Allergen, Blood, Kidney, Mutagen, Some evidence of carcinogenicity

12. ECOLOGICAL INFORMATION

Ecological information:

Not available

None

None

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Dispose of according to Federal, State and local governmental regulations.

EPA hazardous waste number:

Packing group:

Marine pollutant:

Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

U.S. Department of Transportation Gro	und (49 CFR):
Proper shipping name:	Unrestricted
Hazard class or division:	None
Identification number:	None
Packing group:	None
International Air Transportation (ICAO/	<u>'IATA):</u>
Proper shipping name:	Unrestricted
Hazard class or division:	None
Identification number:	None
Packing group:	None
WaterTransportation (IMO/IMDG):	
Proper shipping name:	Unrestricted
Hazard class or division:	None
Identification number:	None

United States Regulatory Information

TSCA 8 (b) Inventory Status: TSCA 12 (b) Export Notification:	All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory. None above reporting de minimus.	
CERCLA/SARA Section 302 EHS: CERCLA/SARA Section 311/312: CERCLA/SARA 313:	None above reporting de minimus. Immediate Health Hazard, Delayed Health Hazard This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Cumene hydroperoxide (CAS# 80-15-9) . Acrylic acid (CAS# 79-10-7).	
California Proposition 65:	This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.	
Canada Regulatory Information		
CEPA DSL/NDSL Status: WHMIS hazard class:	Contains one or more components listed on the Non-Domestic Substances list. D.2.B	
16. OTHER INFORMATION		

This material safety data sheet contains changes from the previous version in sections: 15

Prepared by:

Kyra Kozak Woods, Manager, Regulatory Affairs

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.