Material Safety Data Sheet

Revision Number: 002.1 **Issue date:** 04/29/2009

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: DB EPOXY ADH E-00NS 200 ML HARD
Product type: Epoxy Hardener
IDH number: 701958
Item number: 29295_209525
Region: United States

Company address:
Henkel Corporation
1001 Trout Brook Crossing
Rocky Hill, Connecticut 06067

Contact information:
Telephone: 860.571.5100
Emergency telephone: 860.571.5100
Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

HMIS:

Physical state: Liquid
Color: Light, Cream
Odor: Mercaptan, Sulfur

HEALTH: *3
FLAMMABILITY: 1
PHYSICAL HAZARD: 0
Personal Protection: See MSDS Section 8

DANGER**:** CAUSES EYE AND SKIN BURNS.
MAY CAUSE ALLERGIC SKIN AND RESPIRATORY REACTION.
MAY CAUSE RESPIRATORY TRACT IRRITATION.
MAY BE HARMFUL IF SWALLOWED.
COMBUSTIBLE LIQUID AND VAPOR.

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

Potential Health Effects

Inhalation: May cause allergic respiratory reaction. Severe respiratory tract irritation. May cause irritation to nose and throat. Tearing.
Skin contact: May cause skin burns. May cause allergic skin reaction. Rash. Redness.
Eye contact: Burns. Severe eye irritation. Redness. Tissue damage.
Ingestion: May be harmful if swallowed. May cause burns of mouth and throat if swallowed.

Existing conditions aggravated by exposure: Eye, skin, and respiratory disorders. Skin allergies.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%
Polymercaptan hardener	Proprietary	60 - 100
Benzyldimethylamine	103-83-3	5 - 10
Treated fumed silica	67762-90-7	1 - 5
Aliphatic amine	Proprietary	1 - 5

4. FIRST AID MEASURES

Inhalation: Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

Skin contact:	Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and footwear. Wash clothing before reuse. Thoroughly clean shoes before reuse. If symptoms develop and persist, get medical attention.
Eye contact:	Immediately flush eyes with water for at least 15 minutes, while holding eyelids open. Seek medical attention at once. Get medical attention.
Ingestion:	DO NOT induce vomiting unless directed to do so by medical personnel. Keep individual calm. Get medical attention.

5. FIRE FIGHTING MEASURES

Flash point:	75.5 °C (167.9 °F) Pensky Martens closed cup
Autoignition temperature:	Not available
Flammable/Explosive limits - lower:	Not available
Flammable/Explosive limits - upper:	Not available
Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.
Special firefighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.
Unusual fire or explosion hazards:	In case of fire, keep containers cool with water spray.
Hazardous combustion products:	Oxides of carbon. Oxides of nitrogen. Ammonia. Nitric acid. Irritating organic fragments.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not allow product to enter sewer or waterways.
Clean-up methods:	Remove all sources of ignition. Immediately contact emergency personnel. Ventilate area. Scrape up as much material as possible. Clean residue with soap and water. Store in a closed container until ready for disposal.

7. HANDLING AND STORAGE

Handling:	Keep away from heat, spark and flame. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Keep container closed.
Storage:	Store in original container until ready to use. Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Polymercaptan hardener	None	None	None	None
Benzyldimethylamine	None	None	None	None
Treated fumed silica	10 mg/m3 TWA Inhalable dust. 3 mg/m3 TWA Respirable fraction.	15 mg/m3 TWA Total dust. 5 mg/m3 TWA Respirable fraction.	None	None
Aliphatic amine	3 ppm TWA 6 ppm STEL	3 ppm (6 mg/m3) TWA	None	None

Engineering controls: Use local exhaust ventilation if the potential for airborne exposure exists.

Respiratory protection: Use a NIOSH approved air-purifying respirator with an organic vapor cartridge.

Eye/face protection: Safety goggles or safety glasses with side shields.

Skin protection: Chemical resistant, impermeable gloves. Butyl rubber gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid
Color: Light, Cream
Odor: Mercaptan, Sulfur
Odor threshold: Not available
pH: Not available
Vapor pressure: Not available
Boiling point/range: Not available
Melting point/ range: Not available
Vapor density: Not available
Flash point: 75.5 °C (167.9 °F) Pensky Martens closed cup
Flammable/Explosive limits - lower: Not available
Flammable/Explosive limits - upper: Not available
Autoignition temperature: Not available
Evaporation rate: Not available
Solubility in water: Not available
Partition coefficient (n-octanol/water): Not available
VOC content: < 1 %; < 10 g/l Estimated

10. STABILITY AND REACTIVITY

Stability: Stable

Hazardous reactions: Polymerization is a highly exothermic reaction and may generate sufficient heat to cause thermal decomposition and/or rupture containers.

Hazardous decomposition products: None

Incompatible materials: Strong acids and strong bases. Peroxides. Calcium hypochlorite. Sodium hypochlorite.

Conditions to avoid: Excessive heat. Store away from incompatible materials.

11. TOXICOLOGICAL INFORMATION

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Polymercaptan hardener	No	No	No
Benzyldimethylamine	No	No	No
Treated fumed silica	No	No	No
Aliphatic amine	No	No	No

Hazardous components	Health Effects/Target Organs
Polymercaptan hardener	No Data
Benzyldimethylamine	Irritant, Corrosive, Allergen, Respiratory
Treated fumed silica	Irritant
Aliphatic amine	Irritant, Kidney, Liver, Corrosive, Respiratory, Developmental

12. ECOLOGICAL INFORMATION

Ecological information: Not available

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: This product may contain traces of: Benzene. Therefore, it may be classified as hazardous waste under EPA RCRA (40 CFR 261.24), with waste number(s): D018. However this product is only classifiable as hazardous waste if it exhibits the characteristics of toxicity as shown by the toxicity characteristic leaching procedure (TCLP). Under RCRA, it is the responsibility of the end user of this product to determine whether it meets this criteria at the time of disposal.

14. TRANSPORT INFORMATION

The shipping classifications in this sections are for non-bulk packaging only (unless otherwise specified). Shipping classification may be different for bulk packaging.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Amines, liquid, corrosive, n.o.s. (aliphatic Amine)
Hazard class or division: 8
Identification number: UN 2735
Packing group: III

International Air Transportation (ICAO/IATA)

Proper shipping name: Amines, liquid, corrosive, n.o.s. (aliphatic Amine)
Hazard class or division: 8
Identification number: UN 2735
Packing group: III

Water Transportation (IMO/IMDG)

Proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. (aliphatic Amine)
Hazard class or division: 8
Identification number: UN 2735
Packing group: III

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.
TSCA 12(b) Export Notification: None above reporting de minimus

CERCLA/SARA Section 302 EHS: None above reporting de minimus
CERCLA/SARA Section 311/312: Immediate Health, Delayed Health
CERCLA/SARA 313: None above reporting de minimus

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Canada Regulatory Information

CEPA DSL/NDSL Status:	Contains one or more components listed on the Non-Domestic Substances List. All other components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities. Please contact Regulatory Affairs for additional details.
WHMIS hazard class:	B.3, D.2.B, E

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: New Material Safety Data Sheet format.

Prepared by: Gary Pierson, Sr. Regulatory Affairs Specialist

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.