

Revision Number: 002.1

Issue date: 01/26/2010

1. PRODUCT AND COMPANY IDENTIFICATION DB EPOXY ADH E-40FL 50 ML Product name: IDH number: 701967 Product type: Epoxy resin Item number: 29304 209528 Region: United States Company address: Contact information: Henkel Corporation Telephone: 860.571.5100 Emergency telephone: 860.571.5100 One Henkel Way Rocky Hill, Connecticut 06067 Internet: www.henkelna.com 2. HAZARDS IDENTIFICATION **EMERGENCY OVERVIEW** HMIS: Physical state: Liquid HEALTH: 2 FLAMMABILITY: Color: Light 1 PHYSICAL HAZARD: Odor: Faint, Epoxy 0 Personal Protection: See MSDS Section 8 MAY CAUSE ALLERGIC SKIN REACTION. WARNING: MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION. Relevant routes of exposure: Skin, Inhalation, Eyes **Potential Health Effects** Inhalation: May cause respiratory tract irritation. Skin contact: May cause allergic skin reaction. May cause skin irritation. Burning sensation. Itching. Redness. Swelling. Eye contact: May cause irritation. Direct contact may cause temporary redness and discomfort. Ingestion: Not a relevant route of exposure. Existing conditions aggravated by Skin allergies. Skin disorders. Respiratory disorders. exposure: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%	
Epichlorohydrin-4,4'-isopropylidene diphenol resin	25068-38-6	60 - 100	
Kaolin	1332-58-7	10 - 30	

4. FIRST AID MEASURES

Inhalation:

Skin contact:

Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. If symptoms develop and persist, get medical attention.

Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and footwear. If symptoms develop and persist, get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.

Eye contact:	Immediately flush eyes with plenty of water for at least 15 minutes. Get
	medical attention.
Ingestion:	DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention.
5. FI	RE FIGHTING MEASURES
Flash point:	> 93 °C (> 199.4 °F) Setaflash Closed Cup
Autoignition temperature:	Not available
Flammable/Explosive limits - lower:	Not available
Flammable/Explosive limits - upper:	Not available
Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.
Special firefighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.
Unusual fire or explosion hazards:	None expected.
Hazardous combustion products:	Acids. Aldehydes. Irritating organic vapours. Oxides of carbon.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not allow product to enter sewer or waterways.
Clean-up methods:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up spilled material and place in a closed container for disposal.
7. HANDLING AND STORAGE	

Handling:	Use only with adequate ventilation. Keep container closed. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling.
Storage:	Keep in a cool, well ventilated area away from heat, sparks and open flame.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

Keep container tightly closed until ready for use.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Epichlorohydrin-4,4'-isopropylidene diphenol resin	None	None	None	None
Kaolin	2 mg/m3 TWA Respirable fraction.	5 mg/m3 TWA Respirable fraction. 15 mg/m3 TWA Total dust.	None	None

Engineering controls:

Use local ventilation if general ventilation is insufficient to maintain vapor concentration below established exposure limits.

Respiratory protection:

Eye/face protection:

Skin protection:

Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

Safety goggles or safety glasses with side shields.

Use impermeable gloves and protective clothing as necessary to prevent skin contact. Butyl rubber gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Color: Odor: Odor threshold: pH: Vapor pressure: Boiling point/range: Melting point/ range: Vapor density: Flash point: Flammable/Explosive limits - lower: Flammable/Explosive limits - upper: Autoignition temperature: Evaporation rate: Solubility in water: Partition coefficient (n-octanol/water): VOC content:

Liquid Light Faint, Epoxy Not available Not available Not available > 250 °C (> 482°F) Not available Not available > 93 °C (> 199.4 °F) Setaflash Closed Cup Not available Not available Not available Not available Negligible Not available < 1 %; < 10 g/l Estimated

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of storage and use.
Hazardous reactions:	Will not occur.
Hazardous decomposition products:	Oxides of carbon. Hydrocarbons. Phenolics.
Incompatible materials:	Strong oxidizing agents. Amines. Acids. Bases.
Conditions to avoid:	Avoid temperatures above 149°C (300°F).

11. TOXICOLOGICAL INFORMATION

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Epichlorohydrin-4,4'-isopropylidene diphenol resin	No	No	No
Kaolin	No	No	No

Hazardous components	Health Effects/Target Organs
Epichlorohydrin-4,4'-isopropylidene diphenol resin	Allergen, Irritant
Kaolin	Nuisance dust

12. ECOLOGICAL INFORMATION

Ecological information:

Not available

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:

Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number:

Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

The shipping classifications in this sections are for non-bulk packaging only (unless otherwise specified). Shipping classification may be different for bulk packaging.

U.S. Department of Transportation Ground (4		
Proper shipping name:	Not regulated	
Hazard class or division:	None	
Identification number:	None	
Packing group:	None	
International Air Transportation (ICAO/IATA)		
Proper shipping name:	Environmentally hazardous substance, liquid, n.o.s. (Bisphenol-A Epichlorhydrine resin)	
Hazard class or division:	9	
Identification number:	UN 3082	
Packing group:	III	
Water Transportation (IMO/IMDG)		
Proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol-A Epichlorhydrine resin)	
Hazard class or division:	9	
Identification number:	UN 3082	
Packing group:	III	
Marine pollutant:	Bisphenol-A Epichlorhydrine resin	
15. REGULATORY INFORMATION		

United States Regulatory Information

TSCA 8 (b) Inventory Status: TSCA 12(b) Export Notification:	All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory. None above reporting de minimus
CERCLA/SARA Section 302 EHS: CERCLA/SARA Section 311/312: CERCLA/SARA 313:	None above reporting de minimus Immediate Health None above reporting de minimus
California Proposition 65:	This product contains a chemical known in the State of California to cause cancer.
Canada Regulatory Information	
CEPA DSL/NDSL Status:	All components are listed on or are exempt from listing on the Canadian Domestic Substances List
WHMIS hazard class:	D.2.B

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: New Material Safety Data Sheet format., This Material Safety Data Sheet contains changes from the previous version in Section(s): 2, 5, 10, 14, 15

Prepared by: Rena Petrides, Regulatory Affairs Specialist

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.