

Material Safety Data Sheet



Revision Number: 003.2

Issue date: 01/27/2010

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: DB EPOXY ADH E-20NS 200 ML HARD
Product type: Epoxy Hardener
Company address:
Henkel Corporation
One Henkel Way
Rocky Hill, Connecticut 06067

IDH number: 702004
Item number: 29335_209541
Region: United States
Contact information:
Telephone: 860.571.5100
Emergency telephone: 860.571.5100
Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Physical state: Viscous, Liquid
Color: Tan
Odor: Strong, Ammoniacal

HEALTH: *3
FLAMMABILITY: 1
PHYSICAL HAZARD: 0
Personal Protection: See MSDS Section 8

DANGER: CAUSES EYE AND SKIN BURNS.
MAY CAUSE ALLERGIC SKIN AND RESPIRATORY REACTION.
MAY CAUSE RESPIRATORY TRACT IRRITATION.
MAY BE HARMFUL IF SWALLOWED.

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

Potential Health Effects

Inhalation: May cause allergic respiratory reaction. May cause respiratory tract irritation. May cause irritation to nose and throat.
Skin contact: May cause skin burns. May cause allergic skin reaction. Rash. Redness.
Eye contact: Burns. Severe eye irritation. Redness. Tissue damage.
Ingestion: May be harmful if swallowed. May cause burns of mouth and throat if swallowed.

Existing conditions aggravated by exposure: Eye, skin, and respiratory disorders. Skin allergies.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%
Amine epoxy adduct	Unknown	10 - 30
Filler	Unknown	10 - 30
Talc	14807-96-6	10 - 30
Quartz (SiO ₂)	14808-60-7	10 - 30
N-Aminoethylpiperazine	140-31-8	5 - 10
Nonylphenol	25154-52-3	5 - 10
Diethylenetriamine	111-40-0	5 - 10
4,4'-Isopropylidenediphenol	80-05-7	1 - 5
Treated fumed silica	67762-90-7	1 - 5

IDH number: 702004

Product name: DB EPOXY ADH E-20NS 200 ML HARD

4. FIRST AID MEASURES

Inhalation:	Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
Skin contact:	Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and footwear. Wash clothing before reuse. Thoroughly clean shoes before reuse. If symptoms develop and persist, get medical attention.
Eye contact:	Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.
Ingestion:	DO NOT induce vomiting unless directed to do so by medical personnel. Keep individual calm. Get medical attention.

5. FIRE FIGHTING MEASURES

Flash point:	> 93 °C (> 199.4 °F) Setaflash Closed Cup
Autoignition temperature:	Not available
Flammable/Explosive limits - lower:	Not available
Flammable/Explosive limits - upper:	Not available
Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.
Special firefighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.
Unusual fire or explosion hazards:	In case of fire, keep containers cool with water spray.
Hazardous combustion products:	Oxides of carbon. Oxides of nitrogen. Irritating organic fragments. Ammonia. Hydrogen cyanide. Nitric acid.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not allow product to enter sewer or waterways.
Clean-up methods:	Remove all sources of ignition. Immediately contact emergency personnel. Scrape up as much material as possible. Clean residue with soap and water. Store in a closed container until ready for disposal.

7. HANDLING AND STORAGE

Handling:	Keep away from heat, spark and flame. Avoid breathing vapors or mists of this product. Avoid contact with eyes, skin and clothing. Keep container closed. Wash thoroughly after handling.
Storage:	Store in original container until ready to use. Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Amine epoxy adduct	None	None	None	None
Filler	None	15 mg/m3 TWA Total dust. 5 mg/m3 TWA Respirable fraction.	None	None
Talc	2 mg/m3 TWA Respirable fraction.	20 MPPCF TWA 2.4 MPPCF TWA Respirable. 0.1 mg/m3 TWA Respirable. 0.3 mg/m3 TWA Total dust.	None	50 ppm
Quartz (SiO ₂)	0.025 mg/m3 TWA Respirable fraction.	2.4 MPPCF TWA Respirable. 0.1 mg/m3 TWA Respirable. 0.3 mg/m3 TWA Total dust.	None	None
N-Aminoethylpiperazine	None	None	None	None
Nonylphenol	None	None	None	None
Diethylenetriamine	1 ppm TWA (SKIN)	None	None	None
4,4'-Isopropylidenediphenol	None	None	None	None
Treated fumed silica	10 mg/m3 TWA Inhalable dust. 3 mg/m3 TWA Respirable fraction.	15 mg/m3 TWA Total dust. 5 mg/m3 TWA Respirable fraction.	None	None

Engineering controls:

Use local exhaust ventilation if the potential for airborne exposure exists.

Respiratory protection:

Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

Eye/face protection:

Safety goggles or safety glasses with side shields.

Skin protection:

Chemical resistant, impermeable gloves. Butyl rubber gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Viscous, Liquid
Color:	Tan
Odor:	Strong, Ammoniacal
Odor threshold:	Not available
pH:	Not available
Vapor pressure:	Not available
Boiling point/range:	Not available
Melting point/ range:	Not available
Specific gravity:	1.47
Vapor density:	Not available
Flash point:	> 93 °C (> 199.4 °F) Setaflash Closed Cup
Flammable/Explosive limits - lower:	Not available
Flammable/Explosive limits - upper:	Not available
Autoignition temperature:	Not available
Evaporation rate:	Not available
Solubility in water:	Slight
Partition coefficient (n-octanol/water):	Not available
VOC content:	< 1.0 %; < 10 g/l (estimated value for resin and hardener mixed together)

10. STABILITY AND REACTIVITY

Stability:	Stable
Hazardous reactions:	Polymerization is a highly exothermic reaction and may generate sufficient heat to cause thermal decomposition and/or rupture containers.
Hazardous decomposition products:	None
Incompatible materials:	Strong acids and strong bases. Strong oxidizing agents. Amines. Water.
Conditions to avoid:	Avoid temperatures above 38°C (100°F). Excessive heat. Store away from incompatible materials. Avoid mixing resin (Part A) and curing agent (Part B) in batches greater than 2 pounds (.9 kg) unless you plan to use immediately. Failure to observe these precautions may result in excessive heat build-up causing an exotherm.

11. TOXICOLOGICAL INFORMATION

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Amine epoxy adduct	No	No	No
Filler	No	No	No
Talc	No	No	No
Quartz (SiO ₂)	Known carcinogen.	Group 1	No
N-Aminoethylpiperazine	No	No	No
Nonylphenol	No	No	No
Diethylenetriamine	No	No	No
4,4'-Isopropylidenediphenol	No	No	No
Treated fumed silica	No	No	No

Hazardous components	Health Effects/Target Organs
Amine epoxy adduct	No Data
Filler	No Data
Talc	Irritant, Lung, Some evidence of carcinogenicity
Quartz (SiO ₂)	Immune system, Lung, Some evidence of carcinogenicity
N-Aminoethylpiperazine	Irritant, Corrosive, Allergen
Nonylphenol	Allergen, Corrosive, Irritant, Kidney
Diethylenetriamine	Allergen, Irritant, Eyes
4,4'-Isopropylidenediphenol	Allergen, Blood, Irritant, Kidney, Reproductive, Spleen
Treated fumed silica	Irritant

12. ECOLOGICAL INFORMATION

Ecological information:	Not available
--------------------------------	---------------

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Corrosive liquids, n.o.s. (Diethylenetriamine, Nonylphenol)
Hazard class or division: 8
Identification number: UN 1760
Packing group: II
Exceptions: (Not more than 1 L), Consumer Commodity, ORM-D

International Air Transportation (ICAO/IATA)

Proper shipping name: Corrosive liquid, n.o.s. (Diethylenetriamine, Nonylphenol)
Hazard class or division: 8
Identification number: UN 1760
Packing group: II

Water Transportation (IMO/MDG)

Proper shipping name: CORROSIVE LIQUID, N.O.S. (Diethylenetriamine, Nonylphenol)
Hazard class or division: 8
Identification number: UN 1760
Packing group: II
Marine pollutant: Nonylphenol

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act inventory.
TSCA 12(b) Export Notification: None above reporting de minimus
CERCLA/SARA Section 302 EHS: None above reporting de minimus
CERCLA/SARA Section 311/312: Immediate Health, Delayed Health
CERCLA/SARA 313: This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). 4,4'-Isopropylidenediphenol (CAS# 80-05-7).
California Proposition 65: This product contains a chemical known in the State of California to cause cancer.

Canada Regulatory Information

CEPA DSL/NDL Status: One or more components are not listed on, and are not exempt from listing on either the Domestic Substances List or the Non-Domestic Substances List.
WHMIS hazard class: D.2.A, D.2.B, E

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: New Material Safety Data Sheet format., This Material Safety Data Sheet contains changes from the previous version in Section(s): 3

Prepared by: Rena Petrides, Regulatory Affairs Specialist

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.