Material Safety Data Sheet



Revision Number: 001.1 Issue date: 02/24/2009

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: DB EPOXY ADH E-120HP 50 ML RES IDH number: 702021

Product type: Epoxy resin | Item number: 29353_209547 | Region: United States

Company address:Contact information:Henkel CorporationTelephone: 860.571.5100

1001 Trout Brook Crossing Emergency telephone: 860.571.5100

Rocky Hill, Connecticut 06067 Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

HMIS:

 Physical state:
 Liquid
 HEALTH:
 2

 Color:
 Pale yellow
 FLAMMABILITY:
 1

 Odor:
 Faint, Epoxy
 PHYSICAL HAZARD:
 1

Personal Protection: See MSDS Section 8

WARNING: MAY CAUSE ALLERGIC SKIN REACTION.

MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects

Inhalation: May cause respiratory tract irritation.

Skin contact: May cause skin irritation with discomfort or rash. May cause allergic skin reaction.

Eye contact: May cause irritation.

Ingestion: Not a relevant route of exposure. Do not taste or swallow.

Existing conditions aggravated by

exposure:

Skin disorders. Skin allergies.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR

1910.1200).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%
Phenol polymer with formaldehyde, glycidyl ether	28064-14-4	30 - 60
Epichlorohydrin-4,4'-isopropylidene diphenol resin	25068-38-6	30 - 60
2-Propenoic acid, 2-methyl-, methyl ester, polyme	25053-09-2	10 - 30
Amorphous fumed silica	68611-44-9	1 - 5

4. FIRST AID MEASURES

Inhalation: Move to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, give oxygen. Get medical attention.

Skin contact: After contact with skin, wash immediately with plenty of water. Remove

contaminated clothing and footwear. Wash clothing before reuse. If symptoms

develop and persist, get medical attention.

Eye contact: Immediately flush eyes with plenty of water for at least 15 minutes. If eye

irritation persists, consult a specialist.

Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious

person. Get medical attention.

5. FIRE FIGHTING MEASURES

Flash point: > 93.33 °C (> 199.99 °F) Setaflash Closed Cup

Autoignition temperature:

Flammable/Explosive limits - lower:

Not available
Flammable/Explosive limits - upper:

Not available

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear.

Unusual fire or explosion hazards: In case of fire, keep containers cool with water spray. Closed containers may

rupture (due to build up of pressure) when exposed to extreme heat.

Hazardous combustion products: Oxides of carbon. Aldehydes. Acids. Irritating organic fragments.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Do not allow product to enter sewer or waterways.

Clean-up methods: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder,

universal binder, sawdust). Store in a closed container until ready for disposal.

Flush with water.

7. HANDLING AND STORAGE

Handling: Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist.

Wash thoroughly after handling. Keep container closed.

Storage: Keep in a cool, well ventilated area away from heat, sparks and open flame.

Keep container tightly closed until ready for use.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Phenol polymer with formaldehyde, glycidyl ether	None	None	None	None
Epichlorohydrin-4,4'-isopropylidene diphenol resin	None	None	None	None
2-Propenoic acid, 2-methyl-, methyl ester, polyme	None	None	None	None
Amorphous fumed silica	None	None	None	None

Engineering controls: Use local ventilation if general ventilation is insufficient to maintain vapor

concentration below established exposure limits.

Respiratory protection: No personal respiratory protective equipment normally required.

Eye/face protection: Safety goggles or safety glasses with side shields.

Skin protection: Chemical resistant, impermeable gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:LiquidColor:Pale yellowOdor:Faint, EpoxyOdor threshold:Not availablepH:Not applicableVapor pressure:Not determinedBoiling point/range:> 149 °C (> 300.2 °F)

Melting point/ range:Not availableSpecific gravity:Not availableVapor density:Not available

Flash point: > 93.33 °C (> 199.99 °F) Setaflash Closed Cup

Flammable/Explosive limits - lower:
Flammable/Explosive limits - upper:
Autoignition temperature:
Evaporation rate:

Not available
Not available
Not available

Solubility in water: Not miscible or difficult to mix

Partition coefficient (n-octanol/water): Not available

VOC content: < 1 %; < 10 g/l Estimated

10. STABILITY AND REACTIVITY

Stability: Stable

Hazardous reactions: Reaction with some curing agents may produce an exothermic reaction which

in large masses could cause runaway polymerization.

Hazardous decomposition products: None reasonably foreseeable.

Incompatible materials: Oxidizing agents. Strong acids and strong bases. Amines.

Conditions to avoid: Excessive heat. Store away from incompatible materials. Avoid mixing resin

(Part A) and curing agent (Part B) unless you plan to use immediately. Failure to observe these precautions may result in excessive heat build-up causing an

exotherm.

11. TOXICOLOGICAL INFORMATION

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Phenol polymer with formaldehyde, glycidyl ether	No	No	No
Epichlorohydrin-4,4'-isopropylidene diphenol resin	No	No	No
2-Propenoic acid, 2-methyl-, methyl ester, polyme	No	No	No
Amorphous fumed silica	No	No	No

Hazardous components	Health Effects/Target Organs
Phenol polymer with formaldehyde, glycidyl ether	Irritant, Allergen
Epichlorohydrin-4,4'-isopropylidene diphenol resin	Allergen, Irritant
2-Propenoic acid, 2-methyl-, methyl ester, polyme	No Target Organs
Amorphous fumed silica	No Target Organs

12. ECOLOGICAL INFORMATION

Ecological information: Not known.

IDH number: 702021 Product name: DB EPOXY ADH E-120HP 50 ML RES

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number:Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated Hazard class or division: None

Identification number:NonePacking group:None

Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated Hazard class or division: None

Identification number:

Packing group:

None

15. REGULATORY INFORMATION

<u>United States Regulatory Information</u>

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12(b) Export Notification: None above reporting de minimus

CERCLA/SARA Section 302 EHS: None above reporting de minimus

CERCLA/SARA Section 311/312: Immediate Health

CERCLA/SARA 313: None above reporting de minimus

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This

product contains a chemical known to the State of California to cause birth defects or other

reproductive harm.

Canada Regulatory Information

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

WHMIS hazard class: D.2.B

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: New Material Safety Data Sheet format.

Prepared by: Gary Pierson, Sr. Regulatory Affairs Specialist

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

IDH number: 702021 Product name: DB EPOXY ADH E-120HP 50 ML RES