Material Safety Data Sheet





Revision Number: 005.1 Issue date: 02/09/2010

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: HYSOL M-31CL MED EPXY HRD 50ML IDH number: Product type: **Epoxy Hardener**

30673_209670 Item number: Region: **United States**

Company address: **Contact information:** Henkel Corporation Telephone: 860.571.5100

Emergency telephone: 860.571.5100 One Henkel Way Rocky Hill, Connecticut 06067 Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW HMIS:

Physical state: HEALTH: Liquid 3 FLAMMABILITY: light 1 Mild PHYSICAL HAZARD: 0

Personal Protection: See MSDS Section 8

CAUSES EYE, SKIN AND RESPIRATORY TRACT BURNS. DANGER:

MAY CAUSE ALLERGIC SKIN REACTION.

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

Potential Health Effects

Inhalation: Inhalation of aerosol may cause irritation to the upper respiratory tract. Can cause severe eye,

skin and respiratory tract burns. May cause nose, throat, and lung irritation. Inhalation of vapors and/or aerosols in high concentration may cause irritation of respiratory system.

Skin contact: Causes skin burns. May cause allergic skin reaction.

Causes eye burns. Exposure to vapor may cause tearing of the eyes, irritation and burning Eye contact:

sensation.

Ingestion: If ingested, severe burns of the mouth and throat may occur, as well as perforation of the

esophagus and the stomach.

Existing conditions aggravated by

exposure:

Color:

Odor:

Eye, skin and respiratory disorders. Skin allergies.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR

1910.1200).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%
Polyglycol diamine	Proprietary	30 - 60
Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane, reaction products with 3,3'-[oxybis(2,1-ethanediyloxy)]bi	68585-28-4	30 - 60

4. FIRST AID MEASURES

Inhalation: Move to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, give oxygen. Get medical attention.

IDH number: 702038 Product name: HYSOL M-31CL MED EPXY HRD 50ML Skin contact: Remove contaminated clothing and footwear. Immediately flush skin with

plenty of water (using soap, if available). Get medical attention. Wash clothing

before reuse. Thoroughly clean shoes before reuse.

Eye contact: Immediately flush eyes with plenty of water for at least 15 minutes. Get

medical attention.

Ingestion: Rinse out mouth, drink 1-2 glasses of water, do not induce vomiting. Never

give anything by mouth to an unconscious person. Get immediate medical

attention

5. FIRE FIGHTING MEASURES

Flash point: > 120 °C (> 248°F)

Autoignition temperature:

Flammable/Explosive limits - lower:

Not available
Flammable/Explosive limits - upper:

Not available

Extinguishing media: Foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear.

Unusual fire or explosion hazards: In case of fire, keep containers cool with water spray. Personnel in vicinity

and downwind should be evacuated. Burning produces obnoxious and toxic

fumes.

Hazardous combustion products: Oxides of carbon. Oxides of nitrogen. Ammonia. Irritating organic fragments.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Do not allow product to enter sewer or waterways.

Clean-up methods: Remove all sources of ignition. Ensure adequate ventilation. Soak up with

inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up spilled material and place in a closed container for

disposal. Clean residue with soap and water.

7. HANDLING AND STORAGE

Handling: Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist.

Wash thoroughly after handling. Do not taste or swallow. Use only with

adequate ventilation. Keep container closed.

Storage: Keep in a cool, well ventilated area away from heat, sparks and open flame.

Keep container tightly closed until ready for use. Store in original container

until ready to use.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Polyglycol diamine	None	None	None	None
Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane, reaction products with 3,3'-[oxybis(2,1-ethanediyloxy)]bi	None	None	None	None

Engineering controls: Use local ventilation if general ventilation is insufficient to maintain vapor

concentration below established exposure limits.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure

Eye/face protection: Safety goggles or safety glasses with side shields.

Skin protection: Use chemical resistant, impermeable clothing including gloves and either an

apron or body suit to prevent skin contact. Neoprene, Butyl-rubber, or nitrile-

rubber gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid Color: light Mild Odor:

Odor threshold: Not available Not applicable pH: Not available Vapor pressure:

> 149 °C (> 300.2 °F) Boiling point/range: Melting point/ range: Not available

IDH number: 702038

Specific gravity: 1.0 Vapor density: Not available > 120 °C (> 248°F) Flash point: Flammable/Explosive limits - lower: Not available Flammable/Explosive limits - upper: Not available Autoignition temperature: Not available Evaporation rate: Not applicable Solubility in water: Partially miscible Partition coefficient (n-octanol/water): Not available

1 %; 10 g/l Estimated VOC content:

STABILITY AND REACTIVITY

Stability: Stable under normal conditions of storage and use.

Hazardous reactions: None under normal processing.

Hazardous decomposition products: Nitrogen oxide can react with water vapor to form corrosive nitric acid. Oxides

of carbon. Ammonia gas may be liberated at high temperatures. Oxides of

nitrogen. Toxic fumes. Nitric acid. Nitrosamines.

Acids. Strong oxidizing agents. Calcium hypochlorite. Sodium hypochlorite. Incompatible materials:

This product slowly corrodes copper, aluminum, zinc and galvanized surfaces.

Reacts violently with peroxides.

Conditions to avoid: Store away from incompatible materials.

11. TOXICOLOGICAL INFORMATION

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Polyglycol diamine	No	No	No
Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane, reaction products with 3,3'-[oxybis(2,1- ethanediyloxy)]bi	No	No	No

Hazardous components	Health Effects/Target Organs
Polyglycol diamine	Corrosive
Phenol, 4,4'-(1-methylethylidene)bis-, polymer with	
(chloromethyl)oxirane, reaction products with 3,3'-	No Records
[oxybis(2,1-ethanediyloxy)]bi	

12. ECOLOGICAL INFORMATION

Ecological information: Not available

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

The shipping classifications in this sections are for non-bulk packaging only (unless otherwise specified). Shipping classification may be different for bulk packaging.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Amines, liquid, corrosive, n.o.s. (Polyglycol diamine)

Hazard class or division: 8
Identification number: UN 2735
Packing group: II

Exceptions: (Not more than 1 L), Consumer Commodity, ORM-D

International Air Transportation (ICAO/IATA)

Proper shipping name: Amines, liquid, corrosive, n.o.s. (Polyglycol diamine)

Hazard class or division: 8
Identification number: UN 2735
Packing group: II

Water Transportation (IMO/IMDG)

Proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. (Polyglycol diamine)

Hazard class or division: 8
Identification number: UN 2735
Packing group: II

15. REGULATORY INFORMATION

United States Regulatory Information

IDH number: 702038

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory

TSCA 12(b) Export Notification: None above reporting de minimus

CERCLA/SARA Section 302 EHS: None above reporting de minimus

CERCLA/SARA Section 311/312: Immediate Health

Product name: HYSOL M-31CL MED EPXY HRD 50ML

CERCLA/SARA 313: None above reporting de minimus

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This

product contains a chemical known to the State of California to cause birth defects or other

reproductive harm.

Canada Regulatory Information

IDH number: 702038

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

WHMIS hazard class: D.2.B, E

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: New Material Safety Data Sheet format., This Material Safety Data Sheet contains changes from the previous version in Section(s): 2, 3, 15

Prepared by: Rena Petrides, Regulatory Affairs Specialist

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.