



Revision Number: 002.2

Issue date: 02/09/2010

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: HYSOL 9462 50ML CQ HARD
Product type: Epoxy Hardener

IDH number: 702158
Item number: 83142_AB9298
Region: United States

Company address:
 Henkel Corporation
 One Henkel Way
 Rocky Hill, Connecticut 06067

Contact information:
 Telephone: 860.571.5100
 Emergency telephone: 860.571.5100
 Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Physical state:	Paste	HEALTH:	*2
Color:	Amber	FLAMMABILITY:	1
Odor:	Slight, Ammoniacal	PHYSICAL HAZARD:	1
WARNING:		Personal Protection:	See MSDS Section 8
MAY CAUSE ALLERGIC SKIN REACTION. CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION. HARMFUL IF SWALLOWED.			

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

Potential Health Effects

Inhalation: May cause respiratory tract irritation. May cause irritation to nose and throat.
Skin contact: Allergic skin reaction. Moderate skin irritation. Rash. Redness.
Eye contact: Moderate eye irritation. Redness. Tissue damage.
Ingestion: Harmful if swallowed.

Existing conditions aggravated by exposure: Eye disorders. Skin disorders. Skin allergies.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%
Quartz (SiO ₂)	14808-60-7	10 - 30
Benzyl alcohol	100-51-6	10 - 30
Formaldehyde, polymer with 5-amino-1,3,3-trimethylcyclohexanemethanamine and phenol	25265-17-2	10 - 30
3- Aminomethyl-3,5,5-trimethylcyclohexylamine	2855-13-2	10 - 30
Nonylphenol	25154-52-3	5 - 10
N,N'-Bis(3-aminopropyl)piperazine	7209-38-3	5 - 10
Silica, amorphous, fumed, crystal-free	112945-52-5	1 - 5
Phenol	108-95-2	1 - 5
N-Aminoethylpiperazine	140-31-8	1 - 5
Microcrystalline Silica	1317-95-9	0.1 - 1

4. FIRST AID MEASURES

Inhalation:	Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention.
Skin contact:	Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and footwear. Wash clothing before reuse. Thoroughly clean shoes before reuse. If symptoms develop and persist, get medical attention.
Eye contact:	Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.
Ingestion:	DO NOT induce vomiting unless directed to do so by medical personnel. Keep individual calm. Get immediate medical attention.

5. FIRE FIGHTING MEASURES

Flash point:	> 149 °C (> 300.2 °F) Cleveland closed cup
Autoignition temperature:	Not available
Flammable/Explosive limits - lower:	Not available
Flammable/Explosive limits - upper:	Not available
Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.
Special firefighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.
Unusual fire or explosion hazards:	In case of fire, keep containers cool with water spray.
Hazardous combustion products:	Oxides of carbon. Oxides of nitrogen. Irritating organic fragments.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not allow product to enter sewer or waterways.
Clean-up methods:	Remove all sources of ignition. Immediately contact emergency personnel. Scrape up as much material as possible. Clean residue with soap and water. Store in a partly filled, closed container until disposal.

7. HANDLING AND STORAGE

Handling:	Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Keep container closed.
Storage:	Store in original container until ready to use. Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Quartz (SiO ₂)	0.025 mg/m ³ TWA Respirable fraction.	2.4 MPPCF TWA Respirable. 0.1 mg/m ³ TWA Respirable. 0.3 mg/m ³ TWA Total dust.	None	None
Benzyl alcohol	None	None	10 ppm (44 mg/m ³) TWA	None
Formaldehyde, polymer with 5-amino-1,3,3-trimethylcyclohexanemethanamine and phenol	None	None	None	None
3- Aminomethyl-3,5,5-trimethylcyclohexylamine	None	None	None	None
Nonylphenol	None	None	None	None
N,N'-Bis(3-aminopropyl)piperazine	None	None	None	None
Silica, amorphous, fumed, crystal-free	10 mg/m ³ TWA Inhalable dust. 3 mg/m ³ TWA Respirable fraction.	20 MPPCF TWA 0.8 mg/m ³ TWA	None	None
Phenol	5 ppm TWA (SKIN)	5 ppm (19 mg/m ³) TWA (SKIN)	None	None
N-Aminoethylpiperazine	None	None	None	None
Microcrystalline Silica	0.025 mg/m ³ TWA Respirable fraction.	None	None	None

Engineering controls:

Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

Respiratory protection:

Use a NIOSH approved air-purifying respirator if the potential to exceed established exposure limits exists.

Eye/face protection:

Safety goggles or safety glasses with side shields.

Skin protection:

Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact. Chemical resistant, impermeable gloves. Neoprene, Butyl-rubber, or nitrile-rubber gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Paste
Color:	Amber
Odor:	Slight, Ammoniacal
Odor threshold:	Not available
pH:	Not applicable
Vapor pressure:	Not available
Boiling point/range:	> 149 °C (> 300.2 °F)
Melting point/ range:	Not available
Specific gravity:	1.31
Vapor density:	Not available
Flash point:	> 149 °C (> 300.2 °F) Cleveland closed cup
Flammable/Explosive limits - lower:	Not available
Flammable/Explosive limits - upper:	Not available
Autoignition temperature:	Not available
Evaporation rate:	Not available
Solubility in water:	Insoluble
Partition coefficient (n-octanol/water):	Not available
VOC content:	< 0.05 % (value for resin and hardener together) (estimated)

10. STABILITY AND REACTIVITY

Stability:	Stable
Hazardous reactions:	Will not occur.
Hazardous decomposition products:	None
Incompatible materials:	Strong acids. Strong oxidizing agents.
Conditions to avoid:	Excessive heat. Store away from incompatible materials.

11. TOXICOLOGICAL INFORMATION

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Quartz (SiO ₂)	Known carcinogen.	Group 1	No
Benzyl alcohol	No	No	No
Formaldehyde, polymer with 5-amino-1,3,3-trimethylcyclohexanemethanamine and phenol	No	No	No
3- Aminomethyl-3,5,5-trimethylcyclohexylamine	No	No	No
Nonylphenol	No	No	No
N,N'-Bis(3-aminopropyl)piperazine	No	No	No
Silica, amorphous, fumed, crystal-free	No	No	No
Phenol	No	No	No
N-Aminoethylpiperazine	No	No	No
Microcrystalline Silica	Known carcinogen.	Group 1	No

Hazardous components	Health Effects/Target Organs
Quartz (SiO ₂)	Immune system, Lung, Some evidence of carcinogenicity
Benzyl alcohol	Allergen, Central nervous system, Corrosive, Irritant
Formaldehyde, polymer with 5-amino-1,3,3-trimethylcyclohexanemethanamine and phenol	No Records
3- Aminomethyl-3,5,5-trimethylcyclohexylamine	Irritant, Allergen, Corrosive, Lung
Nonylphenol	Allergen, Corrosive, Irritant, Kidney
N,N'-Bis(3-aminopropyl)piperazine	No Records
Silica, amorphous, fumed, crystal-free	Nuisance dust
Phenol	Blood, Cardiac, Corrosive, Developmental, Eyes, Irritant, Kidney, Liver, Mutagen, Nervous System, Skin, Vascular
N-Aminoethylpiperazine	Irritant, Corrosive, Allergen
Microcrystalline Silica	Lung, Some evidence of carcinogenicity

12. ECOLOGICAL INFORMATION

Ecological information:	Not available
--------------------------------	---------------

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

The shipping classifications in this sections are for non-bulk packaging only (unless otherwise specified). Shipping classification may be different for bulk packaging.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

International Air Transportation (ICAO/IATA)

Proper shipping name: Environmentally hazardous substance, solid, n.o.s. (Nonylphenol)
Hazard class or division: 9
Identification number: UN 3077
Packing group: III

Water Transportation (IMO/IMDG)

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Nonylphenol)
Hazard class or division: 9
Identification number: UN 3077
Packing group: III
Marine pollutant: Nonylphenol

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.
TSCA 12(b) Export Notification: None above reporting de minimus
CERCLA/SARA Section 302 EHS: Phenol (CAS# 108-95-2).
CERCLA/SARA Section 311/312: Immediate Health, Delayed Health
CERCLA/SARA 313: This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Phenol (CAS# 108-95-2).
California Proposition 65: This product contains a chemical known in the State of California to cause cancer.

Canada Regulatory Information

CEPA DSL/NDL Status: All components are listed on or are exempt from listing on the Canadian Domestic Substances List.
WHMIS hazard class: D.2.A, D.2.B

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: New Material Safety Data Sheet format.

Prepared by: Gary Pierson, Manager, Regulatory Affairs

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.