

Revision Date: 05/15/2007

Issue date: 05/15/2007

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product name: Fixmaster Wear Resist Putty
Product type: Epoxy Hardener
Company address:
 Henkel Corporation
 1001 Trout Brook Crossing
 Rocky Hill, Connecticut 06067

Item No. : 98743_00363000 / IDH No. 702268
Region: United States
Contact Information:
 Telephone: 860.571.5100
 Emergency telephone: 860.571.5100
 Internet: www.loctite.com

2. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Hazardous components</u>	<u>%</u>	<u>ACGIH TLV</u>	<u>OSHA PEL</u>	<u>OTHER</u>
Aluminum oxide 1344-28-1	60-100	10 mg/m ³ TWA particulate matter containing no asbestos and <1% crystalline silica	15 mg/m ³ TWA total dust 5 mg/m ³ TWA respirable fraction	None
Amine reacted fatty acid Proprietary	10-30	None	None	None
Nonylphenol 25154-52-3	1-5	None	None	None
Diethylene triamine 111-40-0	1-5	1 ppm TWA (skin)	None	None
Silica, amorphous, fumed, crystalline-free 112945-52-5	1-5	10 mg/m ³ TWA inhalable 3 mg/m ³ TWA respirable	6 mg/m ³ TWA	None
Epoxy polyamine adduct Unknown	1-5	None	None	None
4,4'-Isopropylidenediphenol 80-05-7	1-5	None	None	None
Triethylenetetramine 112-24-3	1-5	None	None	1 ppm, skin TWA, (WEEL)
N-(2-Aminoethyl)piperazine 140-31-8	1-5	None	None	None

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Physical state: Paste
Color: Dark grey
Odor: Ammoniacal

HMIS:

HEALTH: 3*
FLAMMABILITY: 1
PHYSICAL HAZARD: 0
Personal Protection: See Section 8

DANGER: CAUSES EYE AND SKIN BURNS.
 MAY CAUSE ALLERGIC SKIN AND RESPIRATORY REACTION.
 MAY CAUSE RESPIRATORY TRACT IRRITATION.
 MAY BE HARMFUL IF SWALLOWED OR ABSORBED THROUGH SKIN.

Relevant routes of exposure: Eye contact, Ingestion, Inhalation, Skin contact

Potential Health Effects

Item No. : 98743_00363000 / IDH No. 702268

Product name: Fixmaster Wear Resist Putty

Inhalation:	Allergic respiratory reaction. May cause respiratory tract irritation. May cause irritation to nose and throat.
Skin contact:	May cause skin burns. Allergic skin reaction. Rash. Redness. May be harmful if absorbed through skin.
Eye contact:	Burns. Severe eye irritation. Redness. Tissue damage. Corneal edema may give appearance of "blue haze" or "fog" around lights.
Ingestion:	May be harmful if swallowed. May cause burns of mouth and throat if swallowed.

Existing conditions aggravated by exposure: Skin disorders. Skin allergies. Respiratory disorders. Eye disorders.

See Section 11 for additional toxicological information.

4. FIRST AID MEASURES

Inhalation:	Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
Skin contact:	Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and shoes. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention if symptoms occur.
Eye contact:	Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.
Ingestion:	DO NOT induce vomiting unless directed to do so by medical personnel. Keep individual calm. Get medical attention immediately.
Notes to physician:	None.

5. FIRE-FIGHTING MEASURES

Flash point:	Greater than 93°C (200°F) Setaflash
Autoignition temperature:	Not available
Flammable/Explosive limits-lower %:	Not available
Flammable/Explosive limits-upper %:	Not available
Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.
Special fire fighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.
Unusual fire or explosion hazards:	In the event of fire, cool tanks with water spray.
Hazardous combustion products:	Oxides of carbon. Oxides of nitrogen. Ammonia. Cyanides. Nitrosamines. Nitric acid. Phenolics. Irritating organic fragments.

6. ACCIDENTAL RELEASE MEASURES

Environmental precautions:	Prevent product from entering drains or open waters.
Clean-up methods:	Remove all ignition sources. Immediately contact emergency personnel. Scrape up as much material as possible. Clean residue with soap and water. Store in a closed container until ready for disposal.

7. HANDLING AND STORAGE

Handling:	Keep away from heat, spark and flame. Do not breathe mist or vapors. Keep container closed. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.
Storage:	Store in original container until ready to use. Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.
Incompatible products:	Refer to Section 10.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering controls:	Use local exhaust ventilation to maintain airborne concentrations below established exposure limits.
Respiratory protection:	Use a NIOSH approved air-purifying respirator if the potential to exceed established exposure limits exists.
Skin protection:	Chemical resistant, impermeable gloves. Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact. Neoprene gloves. Nitrile gloves. Butyl rubber gloves.
Eye/face protection:	Chemical splash goggles or safety glasses with side shields.

See Section 2 for exposure limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Paste
Color:	Dark grey
Odor:	Ammoniacal
Vapor pressure:	<1 mmHg @ 20°C (68°F)
pH:	Not applicable
Boiling point/range:	137-293°C (278-560°F)
Melting point/range:	Not available
Specific gravity:	1.07
Vapor density:	>1
Evaporation rate:	Slower than butyl acetate
Solubility in water:	Slightly soluble
Partition coefficient (n-octanol/water):	Not available
VOC content:	0%; 0 grams/liter

10. STABILITY AND REACTIVITY

Stability:	Stable
Hazardous polymerization:	Will not occur.
Hazardous decomposition products:	None
Incompatibility:	Strong acids. Strong bases. Strong oxidizers. Amines. Water. Strong mineral acids. Calcium hypochlorite. Sodium hypochlorite. Nitrous acid and other nitrosating agents. Copper. Aluminum. Zinc. Aldehydes. Ketones. Acrylates. Organic halides. Iron.
Conditions to avoid:	Excessive heat. Storage with incompatible materials.

11. TOXICOLOGICAL INFORMATION

Carcinogen Status

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen
Aluminum oxide 1344-28-1	No	No	No
Amine reacted fatty acid Proprietary	No	No	No
Nonylphenol 25154-52-3	No	No	No
Diethylene triamine 111-40-0	No	No	No
Silica, amorphous, fumed, crystalline-free 112945-52-5	No	No	No
Epoxy polyamine adduct Unknown	No	No	No
4,4'-Isopropylidenediphenol 80-05-7	No	No	No
Triethylenetetramine 112-24-3	No	No	No
N-(2-Aminoethyl)piperazine 140-31-8	No	No	No

Literature Referenced Target Organ & Other Health Effects

Hazardous components	Health Effects/Target Organs
Aluminum oxide 1344-28-1	Corrosive, Irritant, Nuisance dust
Amine reacted fatty acid Proprietary	No Records
Nonylphenol 25154-52-3	Allergen, Corrosive, Irritant, Kidney
Diethylene triamine 111-40-0	Allergen, Eyes, Irritant
Silica, amorphous, fumed, crystalline-free 112945-52-5	Nuisance dust
Epoxy polyamine adduct Unknown	No data
4,4'-Isopropylidenediphenol 80-05-7	Allergen, Blood, Irritant, Kidney, Spleen, Reproductive
Triethylenetetramine 112-24-3	Allergen, Developmental, Irritant, Mutagen, Corrosive
N-(2-Aminoethyl)piperazine 140-31-8	Irritant, Corrosive, Allergen

12. ECOLOGICAL INFORMATION

Ecological information: Not available

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Dispose according to EPA and local governmental regulations.

EPA hazardous waste number: Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

The shipping classifications in this section are for non-bulk packaging only (unless otherwise specified). Shipping classification may be different for bulk packaging.

U.S. Department of Transportation Ground (49 CFR):

Proper shipping name: Corrosive liquid, basic, organic, n.o.s. (Nonylphenol , diethylenetriamine)

Hazard class or division: 8

Identification number: UN 3267

Item No. : 98743_00363000 / IDH No. 702268

Product name: Fixmaster Wear Resist Putty

Packing group: III
Exceptions: (Not more than 4L) Consumer Commodity ORM-D

International Air Transportation (ICAO/IATA):

Proper shipping name: Corrosive liquid, basic, organic, n.o.s. (Nonylphenol , Diethylenetriamine)
Hazard class or division: 8
Identification number: UN3267
Packing group: III

WaterTransportation (IMO/MDG):

Proper shipping name: Corrosive liquid, basic, organic, n.o.s. (Nonylphenol , Diethylenetriamine)
Hazard class or division: 8
Identification number: UN3267
Packing group: III
Marine pollutant: Nonylphenol

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.
TSCA 12 (b) Export Notification: None.

CERCLA/SARA Section 302 EHS: None.
CERCLA/SARA Section 311/312: Immediate Health Hazard, Delayed Health Hazard
CERCLA/SARA 313: This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). 4,4'-Isopropylidenediphenol (CAS# 80-05-7). Aluminum oxide (CAS# 1344-28-1).

California Proposition 65: No California Proposition 65 listed chemicals are known to be present.

Canada Regulatory Information

CEPA DSL/NDL Status: All components are listed on or are exempt from listing on the Domestic Substances List.
WHMIS hazard class: E, D.2.A, D.2.B

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: 2, 11, 15

Prepared by: Gary Pierson, Sr. Product Safety and Regulatory Affairs Specialist

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.