

Revision Date: 03/25/2005

Issue date: 03/06/2006

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product name: 598 RTV 190 ml Double Piston Can
Product type: Silicone Sealant
Company address:
 Henkel Corporation
 1001 Trout Brook Crossing
 Rocky Hill, Connecticut 06067

Item No. : 40463 / IDH No. 743518
Region: United States
Contact Information:
 Telephone: 860.571.5100
 Emergency telephone: 860.571.5100
 Internet: www.loctite.com

2. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Hazardous components</u>	<u>%</u>	<u>ACGIH TLV</u>	<u>OSHA PEL</u>	<u>OTHER</u>
Limestone 1317-65-3	30-60	10 mg/m ³ TWA (particulate matter containing no asbestos and <1% crystalline silica)	15 mg/m ³ TWA total dust 5 mg/m ³ TWA respirable fraction	None
1,1,1,2-Tetrafluoroethane 811-97-2	5-10	None	None	AEL- 1000 ppm 8 & 12 hour TWA. WEEL 1000 ppm 8 & 12 hour TWA (AIHA).
Methyl ethyl ketoxime 96-29-7	1-5	None	None	None
Carbon black 1333-86-4	0.1-1	3.5 mg/m ³ TWA	3.5 mg/m ³ TWA	None
Methanol 67-56-1	0-0.1	200 ppm TWA 250 ppm STEL (skin)	200 ppm TWA 260 mg/m ³ TWA	None

Non hazardous components

Silicone Resins 30-50%

Exposure to moisture during cure will release 0.1 - 0.9% methyl alcohol. Methyl ethyl ketoxime(MEKO) is formed during cure. This product will release up to 5% MEKO.

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Physical state: Paste
Color: Black
Odor: Mild petroleum

HMIS:

HEALTH: 2*
FLAMMABILITY: 1
PHYSICAL HAZARD: 0
Personal Protection: See Section 8

WARNING: CONTENTS UNDER PRESSURE.
 CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

Potential Health Effects

Inhalation:

Vapors and mists will irritate the respiratory tract and nasal passages. When heated to temperatures exceeding 300° F (150° C) in the presence of air, silicones may form formaldehyde vapors. Formaldehyde is a potential cancer hazard and a known skin and respiratory sensitizer. Vapors irritate the eyes, nose and throat. Safe handling conditions may be maintained by keeping formaldehyde vapor concentrations below the OSHA permissible limit. The silane is a skin and eye irritant and may cause skin burns. Overexposure may cause coma and respiratory failure. The low concentration makes such overexposure unlikely and minimizes its affect on health and safety.

Skin contact:

May cause skin irritation with discomfort or rash.

Eye contact:

Vapors may irritate eyes. Contact with eyes will cause irritation.

Ingestion:

Moderately toxic by ingestion. Not expected under normal conditions of use.

Existing conditions aggravated by exposure:

Skin disorders.

See Section 11 for additional toxicological information.

4. FIRST AID MEASURES

Inhalation:	Remove to fresh air. If discomfort persists seek medical attention.
Skin contact:	Wipe off paste with paper towel or cloth. Wash with soap and water.
Eye contact:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Ingestion:	Do not induce vomiting. Keep individual calm. Obtain medical attention.

5. FIRE-FIGHTING MEASURES

Flash point:	Greater than 93°C (200°F) Tagliabue closed cup
Autoignition temperature:	Not available
Flammable/Explosive limits-lower %:	Not available
Flammable/Explosive limits-upper %:	Not available
Extinguishing media:	Carbon dioxide (CO ₂). Foam. Dry chemical.
Special fire fighting procedures:	Use water spray to keep fire exposed containers cool.
Unusual fire or explosion hazards:	Contents under pressure. Closed containers may rupture (due to build up of pressure) when exposed to extreme heat.
Hazardous combustion products:	Formaldehyde. Silica fume.

6. ACCIDENTAL RELEASE MEASURES

Environmental precautions:	Do not flush into surface water or sanitary sewer system.
Clean-up methods:	Scrape up as much material as possible. Maintain good ventilation for large spills. Place scrap material in a well ventilated area and allow to cure to rubber.

7. HANDLING AND STORAGE

Handling:	Avoid contact with eyes, skin and clothing. Avoid breathing vapor and mist. Wash thoroughly after handling. Do not wear contact lenses.
Storage:	Keep container closed. Store at or below 32°C (90°F).
Incompatible products:	Never allow product to get in contact with water during storage.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering controls:	Use local exhaust ventilation to maintain airborne concentrations below established exposure limits.
Respiratory protection:	Use a NIOSH approved air-purifying respirator if the potential to exceed established exposure limits exists.
Skin protection:	Chemical resistant, impermeable gloves. Impervious clothing
Eye/face protection:	Safety goggles or safety glasses with side shields.

See Section 2 for exposure limits.

Item No. : 40463 / IDH No. 743518

Product name: 598 RTV 190 ml Double Piston Can

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Paste
Color:	Black
Odor:	Mild petroleum
Vapor pressure:	<5 mmHg @20°C (68° F)
pH:	Not applicable
Boiling point/range:	Not available
Melting point/range:	Not available
Specific gravity:	1.31 at 20 deg. C
Vapor density:	Not available
Evaporation rate:	Not available
Solubility in water:	Polymerizes in presence of water
Partition coefficient (n-octanol/water):	Not available
VOC content:	3.9%; 50.7 grams/liter

10. STABILITY AND REACTIVITY

Stability:	Stable.
Hazardous polymerization:	Will not occur.
Hazardous decomposition products:	Methyl ethyl ketoxime formed during cure.
Incompatibility:	Polymerizes on contact with water.
Conditions to avoid:	Moisture.

11. TOXICOLOGICAL INFORMATION

Carcinogen Status

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen
Limestone 1317-65-3	No	No	No
1,1,1,2-Tetrafluoroethane 811-97-2	No	No	No
Methyl ethyl ketoxime 96-29-7	No	No	No
Carbon black 1333-86-4	No	Group 2B	Yes
Methanol 67-56-1	No	No	No

Literature Referenced Target Organ & Other Health Effects

Hazardous components	Health Effects/Target Organs
Limestone 1317-65-3	Nuisance dust
1,1,1,2-Tetrafluoroethane 811-97-2	Cardiac, Central nervous system, Irritant, Respiratory, Skin
Methyl ethyl ketoxime 96-29-7	Allergen, Blood, Central nervous system, Eyes, Irritant, Some evidence of carcinogenicity
Carbon black 1333-86-4	Respiratory, Some evidence of carcinogenicity
Methanol 67-56-1	Eyes, Heart, Irritant, Kidney, Liver, Metabolic, Nervous System, Reproductive

12. ECOLOGICAL INFORMATION

Ecological information:

No specific studies have been conducted by Henkel on the ecotoxicity or environmental fate of this material; however, commonly available data on the material indicate that uncontrolled releases to soil, groundwater, or surface waters could entail acute and/or chronic ecological effects, depending on the quantity and concentration of such releases. Releases of volatile components to the atmosphere are not believed to entail significant ecological consequences provided such releases are within the exposure levels set forth in this document. Accordingly, all appropriate measures should be taken to avoid uncontrolled releases to the environment, and any spills or other uncontrolled releases which may occur should be contained and cleaned up immediately in accordance with Section 6.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Cured rubber can be incinerated or landfilled following EPA and local regulations.

EPA hazardous waste number: Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION**U.S. Department of Transportation Ground (49 CFR):**

Proper shipping name: Aerosols, non-flammable
Hazard class or division: None 2.2
Identification number: None UN 1950
Packing group: None
Exceptions: Consumer Commodity ORM-D Aerosols, not more than 1 L -

International Air Transportation (ICAO/IATA):

Proper shipping name: Aerosols, non-flammable
Hazard class or division: None 2.2
Identification number: None UN 1950
Packing group: None

WaterTransportation (IMO/IMDG):

Proper shipping name: Aerosols, Non-flammable
Hazard class or division: None 2.2
Identification number: None UN 1950
Packing group: None
Exceptions: None
Marine pollutant: None known

15. REGULATORY INFORMATION**United States Regulatory Information**

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.
TSCA 12 (b) Export Notification: Methyl ethyl ketoxime (CAS# 96-29-7).

CERCLA/SARA Section 302 EHS: None.
CERCLA/SARA Section 311/312: None.
CERCLA/SARA 313: None.

California Proposition 65: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm. Toluene (CAS# 108-88-3). <1 ppm.

Canada Regulatory Information

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Domestic Substances List.
WHMIS hazard class: A, D.2.A, D.2.B

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: New Material Safety Data Sheet format.

Prepared by:

Lou Fabrizio, Senior Health & Regulatory Affairs Specialist

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.