

Revision Date: 06/20/2007

Issue date: 06/20/2007

## 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

**Product name:** Instant Gasket 190ml AE  
**Product type:** Silicone Sealant  
**Company address:**  
 Henkel Corporation  
 1001 Trout Brook Crossing  
 Rocky Hill, Connecticut 06067

**Item No. :** 40479 / IDH No. 743913  
**Region:** United States  
**Contact Information:**  
 Telephone: 860.571.5100  
 Emergency telephone: 860.571.5100  
 Internet: www.loctite.com

## 2. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Hazardous components</u>	<u>%</u>	<u>ACGIH TLV</u>	<u>OSHA PEL</u>	<u>OTHER</u>
Calcium carbonate 471-34-1	30-60	10 mg/m <sup>3</sup> TWA (particulate matter containing no asbestos and <1% crystalline silica)	15 mg/m <sup>3</sup> TWA (total dust) 5 mg/m <sup>3</sup> TWA (respirable fraction)	None
Silicone Resin Proprietary	30-60	None	None	None
Silicone Resin Proprietary	10-30	None	None	None
Oximino silaneProprietary	1-5	None	None	None
Methyl ethyl ketoxime 96-29-7	1-5	None	None	10 ppm, dermal sensitizer TWA, (WEEL)
Organic Acid Proprietary	1-5	None	None	None
Carbon black 1333-86-4	1-5	3.5 mg/m <sup>3</sup> TWA	3.5 mg/m <sup>3</sup> TWA	None

Exposure to moisture during cure will release 0.1 - 0.9% methyl alcohol. Methyl ethyl ketoxime(MEKO) is formed during cure. This product will release up to 5% MEKO.

## 3. HAZARDS IDENTIFICATION

### EMERGENCY OVERVIEW

**Physical state:** Paste  
**Color:** Black  
**Odor:** Mild petroleum

#### HMIS:

**HEALTH:** 2\*  
**FLAMMABILITY:** 1  
**PHYSICAL HAZARD:** 0  
**Personal Protection:** See Section 8

**WARNING:** CONTENTS UNDER PRESSURE.  
 PROLONGED OR REPEATED CONTACT WITH UNCURED SEALANT MAY CAUSE EYE,  
 SKIN AND RESPIRATORY TRACT IRRITATION.  
 PROLONGED OR REPEATED CONTACT WITH UNCURED SEALANT MAY CAUSE  
 BURNS TO SKIN AND EYES  
 MAY CAUSE ALLERGIC SKIN REACTION.

**Relevant routes of exposure:** Skin, Inhalation, Eyes

### Potential Health Effects

**Item No. :** 40479 / IDH No. 743913

**Product name:** Instant Gasket 190ml AE

<b>Inhalation:</b>	Vapors and mists will irritate the respiratory tract and nasal passages. When heated to temperatures exceeding 300° F (150° C) in the presence of air, silicones may form formaldehyde vapors. Formaldehyde is a potential cancer hazard and a known skin and respiratory sensitizer. Vapors irritate the eyes, nose and throat. Safe handling conditions may be maintained by keeping formaldehyde vapor concentrations below the OSHA permissible limit.
<b>Skin contact:</b>	Prolonged or repeated contact may cause irritation. May cause allergic skin reaction. The silane is a skin and eye irritant and prolonged contact may cause eye and skin burns. The low concentration makes such overexposure unlikely and minimizes its affect on health and safety.
<b>Eye contact:</b>	Contact with uncured product may irritate the eyes. The silane is a skin and eye irritant and prolonged contact may cause eye and skin burns. The low concentration makes such overexposure unlikely and minimizes its affect on health and safety.
<b>Ingestion:</b>	Not expected under normal conditions of use. May be harmful if swallowed.

**Existing conditions aggravated by exposure:** Skin disorders.

**See Section 11 for additional toxicological information.**

#### 4. FIRST AID MEASURES

<b>Inhalation:</b>	Remove to fresh air. If discomfort persists seek medical attention.
<b>Skin contact:</b>	Wipe off paste with paper towel or cloth. Wash with soap and water.
<b>Eye contact:</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
<b>Ingestion:</b>	Do not induce vomiting. Keep individual calm. Obtain medical attention.

#### 5. FIRE-FIGHTING MEASURES

<b>Flash point:</b>	Greater than 93°C (200°F) Tagliabue closed cup
<b>Autoignition temperature:</b>	Not available
<b>Flammable/Explosive limits-lower %:</b>	Not available
<b>Flammable/Explosive limits-upper %:</b>	Not available
<b>Extinguishing media:</b>	Carbon dioxide (CO2). Foam. Dry chemical.
<b>Special fire fighting procedures:</b>	Use water spray to keep fire exposed containers cool.
<b>Unusual fire or explosion hazards:</b>	Contents under pressure. Closed containers may rupture (due to build up of pressure) when exposed to extreme heat.
<b>Hazardous combustion products:</b>	Oxides of silicon. Oxides of carbon. Formaldehyde.

#### 6. ACCIDENTAL RELEASE MEASURES

<b>Environmental precautions:</b>	Do not flush into surface water or sanitary sewer system.
<b>Clean-up methods:</b>	Scrape up as much material as possible. Maintain good ventilation for large spills. Place scrap material in a well ventilated area and allow to cure to rubber.

## 7. HANDLING AND STORAGE

<b>Handling:</b>	Avoid contact with eyes, skin and clothing. Avoid breathing vapor and mist. Wash thoroughly after handling. Do not handle contact lenses until all sealant has been removed from hands. Residual sealant may transfer to lenses and cause eye irritation.
<b>Storage:</b>	Keep container closed. Store at or below 32°C (90°F).
<b>Incompatible products:</b>	Never allow product to get in contact with water during storage.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

<b>Engineering controls:</b>	Use local exhaust ventilation to maintain airborne concentrations below established exposure limits.
<b>Respiratory protection:</b>	Use a NIOSH approved air-purifying respirator if the potential to exceed established exposure limits exists.
<b>Skin protection:</b>	Chemical resistant, impermeable gloves. Impervious clothing
<b>Eye/face protection:</b>	Safety goggles or safety glasses with side shields.

**See Section 2 for exposure limits.**

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical state:</b>	Paste
<b>Color:</b>	Black
<b>Odor:</b>	Mild petroleum
<b>Vapor pressure:</b>	<5 mmHg @20°C (68° F)
<b>pH:</b>	Not applicable
<b>Boiling point/range:</b>	Not available
<b>Melting point/range:</b>	Not available
<b>Specific gravity:</b>	1.31 at 20 deg. C
<b>Vapor density:</b>	Not available
<b>Evaporation rate:</b>	Not available
<b>Solubility in water:</b>	Polymerizes in presence of water
<b>Partition coefficient (n-octanol/water):</b>	Not available
<b>VOC content:</b>	3.9%; 50.7 grams/liter

## 10. STABILITY AND REACTIVITY

<b>Stability:</b>	Stable.
<b>Hazardous polymerization:</b>	Will not occur.
<b>Hazardous decomposition products:</b>	Oxides of carbon. Oxides of silicon. Methyl ethyl ketoxime formed during cure. Formaldehyde.
<b>Incompatibility:</b>	Polymerizes on contact with water.
<b>Conditions to avoid:</b>	Moisture.

## 11. TOXICOLOGICAL INFORMATION

### Carcinogen Status

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen
Calcium carbonate 471-34-1	No	No	No
Silicone Resin Proprietary	No	No	No
Silicone Resin Proprietary	No	No	No
Oximino silaneProprietary	No	No	No
Methyl ethyl ketoxime 96-29-7	No	No	No
Organic Acid Proprietary	No	No	No
Carbon black 1333-86-4	No	Group 2B	Yes

#### Literature Referenced Target Organ & Other Health Effects

Hazardous components	Health Effects/Target Organs
Calcium carbonate 471-34-1	Nuisance dust
Silicone Resin Proprietary	No Target Organs
Silicone Resin Proprietary	Irritant
Oximino silaneProprietary	Allergen, Irritant
Methyl ethyl ketoxime 96-29-7	Allergen, Blood, Central nervous system, Eyes, Irritant, Some evidence of carcinogenicity
Organic Acid Proprietary	Irritant
Carbon black 1333-86-4	Respiratory, Some evidence of carcinogenicity

## 12. ECOLOGICAL INFORMATION

### Ecological information:

No specific studies have been conducted by Henkel on the ecotoxicity or environmental fate of this material; however, commonly available data on the material indicate that uncontrolled releases to soil, groundwater, or surface waters could entail acute and/or chronic ecological effects, depending on the quantity and concentration of such releases. Releases of volatile components to the atmosphere are not believed to entail significant ecological consequences provided such releases are within the exposure levels set forth in this document. Accordingly, all appropriate measures should be taken to avoid uncontrolled releases to the environment, and any spills or other uncontrolled releases which may occur should be contained and cleaned up immediately in accordance with Section 6.

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Cured rubber can be incinerated or landfilled following EPA and local regulations.

**EPA hazardous waste number:** Not a RCRA hazardous waste.

## 14. TRANSPORT INFORMATION

### U.S. Department of Transportation Ground (49 CFR):

**Proper shipping name:** Aerosols, non-flammable  
**Hazard class or division:** 2.2  
**Identification number:** UN 1950  
**Packing group:** None  
**Exceptions:** Aerosols, not more than 1 L - Consumer Commodity

### International Air Transportation (ICAO/IATA):

**Item No. :** 40479 / IDH No. 743913

**Product name:** Instant Gasket 190ml AE

Proper shipping name:	Aerosols, non-flammable
Hazard class or division:	2.2
Identification number:	UN 1950
Packing group:	None

**WaterTransportation (IMO/IMDG):**

Proper shipping name:	Aerosols, Non-flammable
Hazard class or division:	2.2
Identification number:	UN 1950
Packing group:	None
Exceptions:	None
Marine pollutant:	None known

**15. REGULATORY INFORMATION****United States Regulatory Information**

TSCA 8 (b) Inventory Status:	All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.
TSCA 12 (b) Export Notification:	None.

CERCLA/SARA Section 302 EHS:	None above reporting de minimus.
CERCLA/SARA Section 311/312:	Immediate Health Hazard, Delayed Health Hazard
CERCLA/SARA 313:	None above reporting de minimus.

California Proposition 65:	This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.
----------------------------	---

**Canada Regulatory Information**

CEPA DSL/NDL Status:	All components are listed on or are exempt from listing on the Domestic Substances List.
WHMIS hazard class:	A, D.2.A, D.2.B

**16. OTHER INFORMATION**

This material safety data sheet contains changes from the previous version in sections: 3,15

Prepared by:	Lou Fabrizio, Senior Health & Regulatory Affairs Specialist
--------------	---

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.