

Material Safety Data Sheet



Revision Date: 07/01/2008 **Issue date:** 07/01/2008

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product name: LOCTITE H8100 SPEED PT A 490ML | Item No.: 1056476_AA0801 / IDH No. 1056476

Product type: Acrylics Region: United States

Company address: Contact Information:
Henkel Corporation Telephone: 860.571.5100
1001 Trout Brook Crossing Emergency telephone: 860.571.5100

Rocky Hill, Connecticut 06067 Internet: www.loctite.com

2. COMPOSITION/INFORMATION ON INGREDIENTS

| Hazardous components Methyl methacrylate 80-62-6 | <u>%</u> 30-60 | ACGIH TLV 50 ppm TWA 100 ppm STEL (sensitizer) | OSHA PEL 100 ppm TWA 410 mg/m³ TWA | OTHER 50 ppm |
|--|-------------------|---|-------------------------------------|-----------------|
| Carboxy-terminated polybutadiene, glycidyl methacrylate diester 68649-04-7 | 10-30 | None | None | None |
| Methacrylic acid 79-41-4 | 5-10 | 20 ppm TWA | None | None |
| Synthetic rubber 9003-18-3 | 5-10 | None | None | None |
| N,N-Dimethyl-p-toluidine 99-97-8 | 1-5 | None | None | None |
| Talc 14807-96-6 | 0.1-1 | 2 mg/m ³ TWA particulate matter containing no asbestos and <1% crystalline silica | = 20 mppcf TWA | 50 ppm |

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

HMIS:

Physical state:LiquidHEALTH:2*Color:Yellow OpaqueFLAMMABILITY:3Odor:SharpPHYSICAL HAZARD:1Personal Protection:See Section 8

WARNING: FLAMMABLE LIQUID AND VAPOR.

MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.

MAY CAUSE ALLERGIC SKIN REACTION. MAY BE HARMFUL IF SWALLOWED.

Relevant routes of exposure: Inhalation, Skin contact, Eye contact, Ingestion

Potential Health Effects

Inhalation: Vapors may cause headaches, nausea, dizziness and respiratory tract irritation.

Skin contact: May cause skin irritation. May cause allergic skin reaction.

Eye contact: May cause irritation.

Ingestion: May be harmful if swallowed.

Existing conditions aggravated by

exposure:

Eye, skin, and respiratory disorders.

See Section 11 for additional toxicological information.

4. FIRST AID MEASURES

Inhalation: Remove to fresh air. If symptoms develop and persist, get medical attention.

Skin contact: Wash with soap and water. Remove contaminated clothing and shoes. Wash clothing before reuse.

Get medical attention if symptoms occur.

Eye contact: Flush with copious amounts of water, preferably, lukewarm water for at least 15 minutes, holding

eyelids open all the time. Get medical attention.

Ingestion: Do not induce vomiting. Keep individual calm. Obtain medical attention.

5. FIRE-FIGHTING MEASURES

Flash point: 14°C (58°F) Setaflash Closed cup

Autoignition temperature: Not available

Flammable/Explosive limits-lower %: Not available

Flammable/Explosive limits-upper %: Not available

Extinguishing media: Foam, dry chemical or carbon dioxide.

Special fire fighting procedures: None

Unusual fire or explosion hazards: Vapors may accumulate in low or confined areas, travel considerable distance to source of ignition,

and flash back.

Hazardous combustion products: Oxides of carbon. Oxides of nitrogen. Toxic fumes. Acrid smoke and fumes. Irritating organic vapors.

6. ACCIDENTAL RELEASE MEASURES

Environmental precautions: Prevent product from entering drains or open waters.

Clean-up methods: Remove all ignition sources. Ensure adequate ventilation. Soak up with inert absorbent. Store in a

closed container until ready for disposal.

7. HANDLING AND STORAGE

Handling: Avoid contact with eyes, skin and clothing. Avoid breathing vapor and mist. Wash thoroughly after

handling. During use and until all vapors are gone: Keep area ventilated - do not smoke; extinguish all flames, pilot lights, and heaters; turn off stoves, electrical tools and appliances, and any other sources

of ignition. Make sure containers are properly grounded before use or transfer of material.

Storage: Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly

closed until ready for use. For safe storage, store at or below 32°C (90°F).

Incompatible products: Refer to Section 10.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering controls: Use local exhaust ventilation to maintain airborne concentrations below established exposure limits.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

Skin protection: Chemical resistant, impermeable gloves. Nitrile gloves.

Eye/face protection: Safety goggles or safety glasses with side shields.

See Section 2 for exposure limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid

Color: Yellow Opaque Odor: Sharp Vapor pressure: Not available Not applicable pH: Boiling point/range: Not available Melting point/range: Not available 0.94

Specific gravity: Vapor density: Greater than 1 **Evaporation rate:** Faster than ether Solubility in water: Completely miscible Partition coefficient (n-octanol/water): Not available

VOC content: Not available

10. STABILITY AND REACTIVITY

Stability: Stable.

Hazardous polymerization: May occur.

Hazardous decomposition products: Oxides of carbon. Oxides of nitrogen. Toxic fumes. Irritating organic vapors. Smoke.

Incompatability: Oxidizing agents. Reducing agents. Acids. Bases.

Conditions to avoid: See "Handling and Storage" (Section 7) and "Incompatability" (Section 10). Do not mix in batches

greater than 100 grams (0.220 pounds) unless you plan to use immediately.

11. TOXICOLOGICAL INFORMATION

Carcinogen Status

| Hazardous components | NTP Carcinogen | IARC Carcinogen | OSHA Carcinogen |
|--|----------------|-----------------|-----------------|
| Methyl methacrylate 80-62-6 | No | No | No |
| Carboxy-terminated polybutadiene, glycidyl methacrylate diester 68649-04-7 | No | No | No |
| Methacrylic acid 79-41-4 | No | No | No |
| Synthetic rubber 9003-18-3 | No | No | No |
| N,N-Dimethyl-p-toluidine 99-97-8 | No | No | No |
| Talc 14807-96-6 | No | No | No |

Literature Referenced Target Organ & Other Health Effects

| Hazardous components | Health Effects/Target Organs |
|--|---|
| Methyl methacrylate | Allergen, Irritant, Kidney, Liver, Nervous System, Respiratory, Mutagen |
| 80-62-6 | |
| Carboxy-terminated polybutadiene, glycidyl methacrylate diester 68649-04-7 | Allergen, Irritant |
| Methacrylic acid 79-41-4 | Allergen, Corrosive, Irritant |
| Synthetic rubber 9003-18-3 | No Target Organs |
| N,N-Dimethyl-p-toluidine 99-97-8 | Allergen, Mutagen |
| Talc 14807-96-6 | Some evidence of carcinogenicity, Lung, Irritant |

12. ECOLOGICAL INFORMATION

Ecological information: Not available

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Dispose of according to Federal, State and local governmental regulations.

EPA hazardous waste number: D001: Ignitable.

14. TRANSPORT INFORMATION

U.S. Department of Transportation Ground (49 CFR):

Proper shipping name: Adhesives
Hazard class or division: 3
Identification number: UN 1133
Packing group: II

Packing group: II
Exceptions: Consumer Commodity ORM-D (Not more than 5 L)

Marine pollutant: None

International Air Transportation (ICAO/IATA):

Proper shipping name: Adhesives
Hazard class or division: 3
Identification number: UN 1133
Packing group: II

Exceptions: May Qualify as Consumer Commodity ID8000 (Not more than 500 ml)

WaterTransportation (IMO/IMDG):

Proper shipping name:
Hazard class or division:
Identification number:
Packing group:

Marine pollutant:

Adhesives
UN1133
UN1133
II
None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

TSCA 12 (b) Export Notification: None.

CERCLA/SARA Section 302 EHS: None above reporting de minimus.

CERCLA/SARA Section 311/312: Immediate Health Hazard, Delayed Health Hazard, Fire

CERCLA/SARA 313: This product contains the following toxic chemicals subject to the reporting requirements of section 313

of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Methyl

Methacrylate (CAS# 80-62-6) .

California Proposition 65: This product contains a chemical known to the State of California to cause cancer.

Canada Regulatory Information

CEPA DSL/NDSL Status: Contains one or more components listed on the Non-Domestic Substances list.

WHMIS hazard class: B.2, D.2.B

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: 2, 11, 15

Prepared by: Kyra Kozak Woods, Manager, Regulatory Affairs

For Safety and Regulatory Information contact:

Product Safety and Regulatory Affairs,

Rocky Hill, CŤ. 860-571-5204

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.