



Revision Number: 002.1

Issue date: 03/04/2009

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: LOCTITE H8100 SPEED PT B 490ML
Product type: Activator
Company address:
Henkel Corporation
1001 Trout Brook Crossing
Rocky Hill, Connecticut 06067

IDH number: 1056477
Item number: 1056477_AB0800
Region: United States
Contact information:
Telephone: 860.571.5100
Emergency telephone: 860.571.5100
Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION**EMERGENCY OVERVIEW**

| | | | |
|------------------------|-------|-----------------------------|--------------------|
| Physical state: | Paste | HEALTH: | *2 |
| Color: | Blue | FLAMMABILITY: | 1 |
| Odor: | Mild | PHYSICAL HAZARD: | 2 |
| | | Personal Protection: | See MSDS Section 8 |

WARNING: MAY CAUSE ALLERGIC SKIN REACTION.
MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects

Inhalation: May cause respiratory tract irritation.
Skin contact: May cause skin irritation. May cause allergic skin reaction.
Eye contact: May cause irritation.
Ingestion: Not expected to be harmful by ingestion.

Existing conditions aggravated by exposure: Eye, skin, and respiratory disorders.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

| Hazardous components | CAS NUMBER | % |
|------------------------|-------------|---------|
| Benzoyl peroxide | 94-36-0 | 10 - 30 |
| Epoxy resin | Proprietary | 10 - 30 |
| Aromatic Ester | Proprietary | 10 - 30 |
| Butyl benzyl phthalate | 85-68-7 | 10 - 30 |
| Aromatic Ester | Proprietary | 1 - 5 |
| Aromatic Ester | Proprietary | 1 - 5 |

4. FIRST AID MEASURES

Inhalation: Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

| | |
|----------------------|--|
| Skin contact: | Wash with soap and water. Remove contaminated clothing and footwear. Wash clothing before reuse. If symptoms develop and persist, get medical attention. |
| Eye contact: | Flush with copious amounts of water, preferably, lukewarm water for at least 15 minutes, holding eyelids open all the time. Get medical attention. |
| Ingestion: | Do not induce vomiting. Never give anything by mouth to an unconscious person. Keep individual calm. Get medical attention. |

5. FIRE FIGHTING MEASURES

| | |
|--|--|
| Flash point: | > 93 °C (> 199.4 °F) Tagliabue closed cup; Estimated |
| Autoignition temperature: | Not available |
| Flammable/Explosive limits - lower: | Not available |
| Flammable/Explosive limits - upper: | Not available |
| Extinguishing media: | Foam, dry chemical or carbon dioxide. |
| Special firefighting procedures: | Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. |
| Unusual fire or explosion hazards: | Not available |
| Hazardous combustion products: | Oxides of carbon. Irritating organic vapours. |

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

| | |
|-----------------------------------|---|
| Environmental precautions: | Do not allow product to enter sewer or waterways. |
| Clean-up methods: | Remove all sources of ignition. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Store in a partly filled, closed container until disposal. |

7. HANDLING AND STORAGE

| | |
|------------------|---|
| Handling: | Use only with adequate ventilation. Avoid contact with eyes, skin and clothing. Keep away from heat, spark and flame. |
| Storage: | For safe storage, store at or below 38 °C (100.4 °F) |

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

| Hazardous components | ACGIH TLV | OSHA PEL | AIHA WEEL | OTHER |
|------------------------|-------------------------|-------------------------|-----------|-------|
| Benzoyl peroxide | 5 mg/m ³ TWA | 5 mg/m ³ TWA | None | None |
| Epoxy resin | None | None | None | None |
| Aromatic Ester | None | None | None | None |
| Butyl benzyl phthalate | None | None | None | None |
| Aromatic Ester | None | None | None | None |
| Aromatic Ester | None | None | None | None |

| | |
|--------------------------------|---|
| Engineering controls: | Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits. |
| Respiratory protection: | Use NIOSH approved respirator if there is potential to exceed exposure limit(s). |
| Eye/face protection: | Safety goggles or safety glasses with side shields. |
| Skin protection: | Use impermeable gloves and protective clothing as necessary to prevent skin contact. |

9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|---|--|
| Physical state: | Paste |
| Color: | Blue |
| Odor: | Mild |
| Odor threshold: | Not available |
| pH: | Not applicable |
| Vapor pressure: | Not available |
| Boiling point/range: | 149 °C (300.2 °F) Decomposition. |
| Melting point/ range: | Not available |
| Specific gravity: | 1.15 |
| Vapor density: | Not available |
| Flash point: | > 93 °C (> 199.4 °F) Tagliabue closed cup; Estimated |
| Flammable/Explosive limits - lower: | Not available |
| Flammable/Explosive limits - upper: | Not available |
| Autoignition temperature: | Not available |
| Evaporation rate: | Not available |
| Solubility in water: | Slight |
| Partition coefficient (n-octanol/water): | Not available |
| VOC content: | 1.37 %; 12.8 g/l (Adhesive and Activator mixed) |

10. STABILITY AND REACTIVITY

| | |
|--|---|
| Stability: | Stable |
| Hazardous reactions: | Will not occur. |
| Hazardous decomposition products: | Oxides of carbon. Irritating organic vapours. |
| Incompatible materials: | Strong oxidizing agents. Strong acids. |
| Conditions to avoid: | See "Handling and Storage" (Section 7) and "Incompatibility" (Section 10). Do not mix in batches greater than 100 grams (0.22 pounds) unless you plan to use immediately. |

11. TOXICOLOGICAL INFORMATION

| | |
|---------------------------------------|---|
| Acute oral product toxicity: | LD50 (rat) > 10,000 mg/kg |
| Acute dermal product toxicity: | LD50 (rabbit) > 5,000 mg/kg (Estimated) |

| Hazardous components | NTP Carcinogen | IARC Carcinogen | OSHA Carcinogen (Specifically Regulated) |
|------------------------|----------------|-----------------|---|
| Benzoyl peroxide | No | No | No |
| Epoxy resin | No | No | No |
| Aromatic Ester | No | No | No |
| Butyl benzyl phthalate | No | No | No |
| Aromatic Ester | No | No | No |
| Aromatic Ester | No | No | No |

| Hazardous components | Health Effects/Target Organs |
|------------------------|--|
| Benzoyl peroxide | Allergen, Irritant, Mutagen |
| Epoxy resin | Allergen, Irritant |
| Aromatic Ester | No Target Organs |
| Butyl benzyl phthalate | Blood, Central nervous system, Irritant, Kidney, Liver, Pancreas, Reproductive |
| Aromatic Ester | No Target Organs |
| Aromatic Ester | No Records |

12. ECOLOGICAL INFORMATION

Ecological information: Not available

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: D003: Reactive.

14. TRANSPORT INFORMATION

When transporting as a set (component A and B) then the following dangerous good classification is used: UN 3269 Polyester resin kit, 3, III.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Organic peroxide type E, solid (Dibenzoyl peroxide [as a paste]) (Butyl-benzyl-phthalate)
Hazard class or division: 5.2
Identification number: UN 3108
Packing group: II
Marine pollutant: Butyl-benzyl-phthalate
Exceptions: (Not more than 500 g), Consumer Commodity

International Air Transportation (ICAO/IATA)

Proper shipping name: Organic peroxide type E, solid (Dibenzoyl peroxide)
Hazard class or division: 5.2
Identification number: UN 3108
Packing group: None

Water Transportation (IMO/IMDG)

Proper shipping name: ORGANIC PEROXIDE TYPE E, SOLID (DIBENZOYL PEROXIDE) (Butyl-benzyl-phthalate)
Hazard class or division: 5.2
Identification number: UN 3108
Packing group: None
Marine pollutant: Butyl-benzyl-phthalate

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.
TSCA 12(b) Export Notification: None above reporting de minimus
CERCLA/SARA Section 302 EHS: None above reporting de minimus
CERCLA/SARA Section 311/312: Immediate Health, Delayed Health, Reactive
CERCLA/SARA 313: This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Benzoyl peroxide (CAS# 94-36-0).
CERCLA Reportable quantity: Butyl benzyl phthalate (CAS# 85-68-7) 100 lbs. (45.4 kg)

California Proposition 65:

This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Canada Regulatory Information

CEPA DSL/NDL Status:

All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

WHMIS hazard class:

C, D.2.A, D.2.B

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: New Material Safety Data Sheet format.

Prepared by: Kyra Kozak Woods, Manager, Regulatory Affairs

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.