Material Safety Data Sheet



Revision Number: 002.1 Issue date: 04/08/2010

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: HYSOL E-40HT EPOXY 50ML PT A IDH number: 1086059

Product type: Adhesive Item number: 1086059_193385
Region: United States

Company address:Contact information:Henkel CorporationTelephone: 860.571.5100

One Henkel Way Emergency telephone: 860.571.5100 Rocky Hill, Connecticut 06067 Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW HMIS:

 Physical state:
 Liquid
 HEALTH:
 *2

 Color:
 Off white
 FLAMMABILITY:
 1

 Odor:
 Slight
 PHYSICAL HAZARD:
 0

or: Slight PHYSICAL HAZARD: 0
Personal Protection: See MSDS Section 8

WARNING: MAY CAUSE ALLERGIC SKIN REACTION.

CAUSES EYE AND SKIN IRRITATION.

MAY CAUSE RESPIRATORY TRACT IRRITATION.

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects

Inhalation:May cause respiratory tract irritation. May cause irritation to nose and throat.Skin contact:May cause allergic skin reaction. Causes skin irritation. Rash. Itching.

Eye contact: Moderate eye irritation.

Ingestion: Not expected to be harmful by ingestion.

Existing conditions aggravated by

exposure:

Eye, skin, and respiratory disorders.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR

1910.1200).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%
Epichlorohydrin-4,4'-isopropylidene diphenol resin	25068-38-6	60 - 100
4,4'-Methylenebis[N,N-bis(2,3-epoxypropyl)aniline]	28768-32-3	10 - 30
Synthetic rubber	Proprietary	10 - 30
Glass, oxide, chemicals	65997-17-3	5 - 10
Treated fumed silica	67762-90-7	1 - 5

4. FIRST AID MEASURES

Inhalation:Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. If symptoms develop and persist, get medical attention.

Skin contact: Immediately flush skin with plenty of water (using soap, if available). Remove

contaminated clothing and footwear. If symptoms develop and persist, get medical attention. Wash clothing before reuse. Thoroughly clean shoes before

reuse.

Eye contact: Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes. Get medical attention.

Ingestion: DO NOT induce vomiting unless directed to do so by medical personnel.

Never give anything by mouth to an unconscious person. If symptoms develop

and persist, get medical attention.

5. FIRE FIGHTING MEASURES

Flash point: > 94.5 °C (> 202.1 °F) Pensky Martens closed cup

Autoignition temperature:

Flammable/Explosive limits - lower:

Not available
Flammable/Explosive limits - upper:

Not available

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear. Cartridge respirators do not provide adequate protection for fire

fighters or exotherm mitigation.

Unusual fire or explosion hazards: May liberate large quantities of dense, foul-smelling smoke which may contain

unidentified toxic gasses.

Hazardous combustion products: Oxides of carbon and nitrogen, aldehydes, acids and undetermined organics.

Oxides of silicon. Formaldehyde.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected

personnel.

Environmental precautions: Do not allow product to enter sewer or waterways.

Clean-up methods: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder,

universal binder, sawdust). Scrape up as much material as possible. Store in a

partly filled, closed container until disposal.

7. HANDLING AND STORAGE

Handling: Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist.

Wash thoroughly after handling. Use only with adequate ventilation. Keep

container closed.

Storage: Keep container tightly closed and in a cool, well-ventilated place away from

incompatible materials.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Epichlorohydrin-4,4'-isopropylidene diphenol resin	None	None	None	None
4,4'-Methylenebis[N,N-bis(2,3-epoxypropyl)aniline]	None	None	None	None
Synthetic rubber	None	None	None	None
Glass, oxide, chemicals	10 mg/m3 TWA Inhalable dust. 3 mg/m3 TWA Respirable fraction.	None	None	None
Treated fumed silica	10 mg/m3 TWA Inhalable dust. 3 mg/m3 TWA Respirable fraction.	15 mg/m3 TWA Total dust. 5 mg/m3 TWA Respirable fraction.	None	None

Engineering controls: Local exhaust ventilation is recommended when general ventilation is not

sufficient to control airborne contamination below occupational exposure

imits.

Respiratory protection: Use a NIOSH approved air-purifying respirator if the potential to exceed

established exposure limits exists.

Eye/face protection: Safety goggles or safety glasses with side shields.

Skin protection:Use impermeable gloves and protective clothing as necessary to prevent skin

contact

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid Color: Off white Odor: Slight Odor threshold: Not available Not available pH: Vapor pressure: Not available Boiling point/range: Not available Melting point/ range: Not available Specific gravity: 1.14 Vapor density:

Vapor density:Not availableFlash point:> 94.5 °C (> 202.1 °F) Pensky Martens closed cup

Flammable/Explosive limits - lower:

Flammable/Explosive limits - upper:

Autoignition temperature:

Evaporation rate:

Solubility in water:

Partition coefficient (n-octanol/water):

Not available

Not available

Not available

VOC content: 0 %; 0 g/l (value as mixed for use)

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions of storage and use.

Hazardous reactions: May occur.

Hazardous decomposition products: Oxides of carbon and nitrogen, aldehydes, acids and undetermined organics.

Oxides of silicon. Formaldehyde.

Incompatible materials: Oxidizing agents. Acids. Bases.

Conditions to avoid: Avoid mixing resin (Part A) and curing agent (Part B) unless you plan to use

immediately. Avoid heating unless curing surfaces to be bonded. Failure to observe these precautions may result in excessive heat build-up causing an

exotherm.

11. TOXICOLOGICAL INFORMATION

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Epichlorohydrin-4,4'-isopropylidene diphenol resin	No	No	No
4,4'-Methylenebis[N,N-bis(2,3-epoxypropyl)aniline]	No	No	No
Synthetic rubber	No	No	No
Glass, oxide, chemicals	No	No	No
Treated fumed silica	No	No	No

Hazardous components	Health Effects/Target Organs	
Epichlorohydrin-4,4'-isopropylidene diphenol resin	Allergen, Irritant	
4,4'-Methylenebis[N,N-bis(2,3-epoxypropyl)aniline]	Allergen, Blood, Central nervous system, Gastrointestinal, Irritant, Kidney, Liver, Mutagen, Nervous System	
Synthetic rubber	No Target Organs	
Glass, oxide, chemicals	Allergen, Respiratory	
Treated fumed silica	Irritant	

12. ECOLOGICAL INFORMATION

Ecological information: Not available

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:Not regulatedHazard class or division:NoneIdentification number:NonePacking group:None

International Air Transportation (ICAO/IATA)

Proper shipping name: Environmentally hazardous substance, liquid, n.o.s. (Bisphenol-A Epichlorhydrine

resin)

Hazard class or division: 9
Identification number: UN 3082
Packing group: III

Water Transportation (IMO/IMDG)

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol-A

Epichlorhydrine resin)

Hazard class or division:

Identification number:UN 3082Packing group:III

Marine pollutant: Bisphenol-A Epichlorhydrine resin

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12(b) Export Notification: None above reporting de minimus

IDH number: 1086059 Product name: HYSOL E-40HT EPOXY 50ML PT A

CERCLA/SARA Section 302 EHS:
CERCLA/SARA Section 311/312:
CERCLA/SARA 313:

None above reporting de minimus
Immediate Health, Delayed Health
None above reporting de minimus

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This

product contains a chemical known to the State of California to cause birth defects or other

reproductive harm.

Canada Regulatory Information

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

WHMIS hazard class: D.2.A, D.2.B

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: New Material Safety Data Sheet format., This Material Safety Data Sheet contains changes from the previous version in Section(s): 2, 3, 4, 5, 10, 11

Prepared by: Rena Petrides, Regulatory Affairs Specialist

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.