



Revision Number: 001.3

Issue date: 07/01/2009

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:	LOCTITE 5605 SIL PT B 400ML	IDH number:	1251055
Product type:	Silicone sealant	Item number:	1250155_198286
		Region:	United States
Company address:	Contact information:		
Henkel Corporation	Telephone: 860.571.5100		
1001 Trout Brook Crossing			
Rocky Hill, Connecticut 06067	Internet: www.henkelna.com		

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Physical state:	Paste	HMIS:	
Color:	Gray	HEALTH:	*2
Odor:	Slight, Alcoholic	FLAMMABILITY:	1
		PHYSICAL HAZARD:	0
		Personal Protection:	See MSDS Section 8

WARNING: PROLONGED OR REPEATED CONTACT WITH UNCURED SEALANT MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION. REPEATED OR PROLONGED CONTACT MAY CAUSE ALLERGIC SKIN REACTION. PROLONGED OR REPEATED CONTACT WITH UNCURED SEALANT MAY CAUSE BURNS TO SKIN AND EYES.

Relevant routes of exposure: Skin, Eye contact, Lungs

Potential Health Effects

Inhalation:	Prolonged or excessive inhalation may cause respiratory tract irritation. Overexposure to methanol formed during cure may cause drowsiness, nausea, and vomiting. When heated to temperatures exceeding 300° F (150° C) in the presence of air, silicones may form formaldehyde vapors. Formaldehyde is a potential cancer hazard and a known skin and respiratory sensitizer. Vapors irritate the eyes, nose and throat. Safe handling conditions may be maintained by keeping formaldehyde vapor concentrations below the OSHA permissible limit.
Skin contact:	Prolonged or repeated contact may cause irritation. Repeated or prolonged exposure may cause skin burns. Repeated contact may cause skin sensitization.
Eye contact:	Vapors may irritate eyes. Contact with eyes will cause irritation. May cause eye injury.
Ingestion:	Not expected under normal conditions of use. Not expected to be harmful by ingestion.

Existing conditions aggravated by exposure: Eye, skin, and respiratory disorders.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%
Limestone	1317-65-3	60 - 100
Silicone Resin	Proprietary	10 - 30
Substituted silane	Proprietary	1 - 5
Substituted silane	Proprietary	1 - 5
Organic Acid	Proprietary	1 - 5
Quartz (SiO ₂)	14808-60-7	0.1 - 1
Carbon black	1333-86-4	0.1 - 1

Exposure to moisture during cure will release 0.1 - 0.9% methanol.

4. FIRST AID MEASURES

Inhalation:	Move to fresh air. If symptoms persist, seek medical advice.
Skin contact:	Wash with soap and water. Wipe off paste with paper towel or cloth.
Eye contact:	Rinse thoroughly with plenty of water, also under the eyelids. If eye irritation persists, consult a specialist.
Ingestion:	Do not induce vomiting. If symptoms develop and persist, get medical attention.

5. FIRE FIGHTING MEASURES

Flash point:	> 93 °C (> 199.4 °F)
Autoignition temperature:	Not available
Flammable/Explosive limits - lower:	Not available
Flammable/Explosive limits - upper:	Not available
Extinguishing media:	Foam, dry chemical or carbon dioxide.
Special firefighting procedures:	None
Unusual fire or explosion hazards:	None
Hazardous combustion products:	Acrid smoke and fumes. Formaldehyde. Oxides of silicon. Oxides of carbon, oxides of nitrogen, irritating organic vapors.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not allow product to enter sewer or waterways.
Clean-up methods:	Maintain good ventilation for large spills. Scrape up as much material as possible. Spilled material will solidify. Store in a partly filled, closed container until disposal.

7. HANDLING AND STORAGE

Handling:	Do not get on skin or clothing. Do not get in eyes. Avoid contact with eyes, skin and clothing. Do not handle contact lenses until all sealant has been removed from hands. Residual sealant may transfer to lenses and cause eye irritation.
------------------	---

Storage:

Keep container closed. Store in a dry area below 90° F.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Limestone	10 mg/m3 TWA Total dust.	5 mg/m3 TWA Respirable fraction. 15 mg/m3 TWA Total dust.	None	None
Silicone Resin	None	None	None	None
Substituted silane	None	None	None	None
Substituted silane	None	None	None	None
Organic Acid	10 mg/m3 TWA	None	None	None
Quartz (SiO ₂)	0.025 mg/m3 TWA Respirable fraction.	2.4 MPPCF TWA Respirable. 0.1 mg/m3 TWA Respirable. 0.3 mg/m3 TWA Total dust.	None	None
Carbon black	3.5 mg/m3 TWA	3.5 mg/m3 TWA	None	None

Engineering controls:

Use only with adequate ventilation.

Respiratory protection:

Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

Eye/face protection:

Safety goggles or safety glasses with side shields.

Skin protection:

Chemical resistant, impermeable gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Paste
Color:	Gray
Odor:	Slight, Alcoholic
Odor threshold:	Not available
pH:	Not available
Vapor pressure:	Not available
Boiling point/range:	Not available
Melting point/ range:	Not available
Specific gravity:	1.1 at 20 °C (68°F)
Vapor density:	Not available
Flash point:	> 93 °C (> 199.4 °F)
Flammable/Explosive limits - lower:	Not available
Flammable/Explosive limits - upper:	Not available
Autoignition temperature:	Not available
Evaporation rate:	Not available
Solubility in water:	Polymerises in presence of water.
Partition coefficient (n-octanol/water):	Not available
VOC content:	0.84 %; 9.20 g/l (by weight) (estimated)

10. STABILITY AND REACTIVITY

Stability:	Stable
Hazardous reactions:	Will not occur.
Hazardous decomposition products:	Formaldehyde. Oxides of silicon. Oxides of carbon. Irritating vapours.
Incompatible materials:	Oxidizing agents. Bases. Water Acids.
Conditions to avoid:	Prolonged heating at temperatures above 150 °C. Exposure to moisture.

11. TOXICOLOGICAL INFORMATION

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Limestone	No	No	No
Silicone Resin	No	No	No
Substituted silane	No	No	No
Substituted silane	No	No	No
Organic Acid	No	No	No
Quartz (SiO ₂)	Known carcinogen.	Group 1	No
Carbon black	No	Group 2B	No

Hazardous components	Health Effects/Target Organs
Limestone	Nuisance dust
Silicone Resin	Irritant
Substituted silane	Irritant, Allergen
Substituted silane	Irritant, Allergen
Organic Acid	Irritant
Quartz (SiO ₂)	Immune system, Lung, Some evidence of carcinogenicity
Carbon black	Respiratory, Some evidence of carcinogenicity

12. ECOLOGICAL INFORMATION

Ecological information:	No specific studies have been conducted by Henkel on the ecotoxicity or environmental fate of this material; however, commonly available data on the material indicate that uncontrolled releases to soil, ground water, or surface waters could entail acute and/or chronic ecological effects, depending on the quantity and concentration of such releases. Releases of volatile components to the atmosphere are not believed to entail significant ecological consequences provided such releases are within the exposure levels set forth in this document. Accordingly, all appropriate measures should be taken to avoid uncontrolled releases to the environment, and any spills or other uncontrolled releases which may occur should be contained and cleaned up immediately in accordance with Section 6.
--------------------------------	---

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal. Cured rubber can be incinerated or landfilled following EPA and local regulations.

Hazardous waste number: Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.
TSCA 12(b) Export Notification: None above reporting de minimus
CERCLA/SARA Section 302 EHS: None above reporting de minimus
CERCLA/SARA Section 311/312: Immediate Health, Delayed Health
CERCLA/SARA 313: None above reporting de minimus
California Proposition 65: No California Proposition 65 listed chemicals are known to be present.

Canada Regulatory Information

CEPA DSL/NDSL Status: Contains one or more components listed on the Non-Domestic Substances List. All other components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities. Please contact Regulatory Affairs for additional details.
WHMIS hazard class: D.2.A, D.2.B

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: New Material Safety Data Sheet format.

Prepared by: Lou Fabrizio, Regulatory Affairs Specialist

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.