# **Material Safety Data Sheet**





Revision Number: 001.2 Issue date: 08/27/2009

#### 1. PRODUCT AND COMPANY IDENTIFICATION

Product name: LOCTITE HYS 1C 1GAL PT A IDH number: 1377345

Product type: Epoxy resin Item number: 1377344\_1284591
Region: United States

 Company address:
 Contact information:

 Henkel Corporation
 Telephone: 860.571.5100

One Henkel Way

Rocky Hill, Connecticut 06067

Emergency telephone: 860.571.5100
Internet: www.henkelna.com

#### 2. HAZARDS IDENTIFICATION

**EMERGENCY OVERVIEW** 

HMIS:

Physical state:LiquidHEALTH:\*2Color:Off whiteFLAMMABILITY:1Odor:NegligiblePHYSICAL HAZARD:0

Personal Protection: See MSDS Section 8

WARNING: MAY CAUSE ALLERGIC SKIN REACTION.

MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.

Relevant routes of exposure: Skin, Inhalation, Eyes

**Potential Health Effects** 

Inhalation: May cause irritation to nose and throat. Mild respiratory tract irritation. Coughing.

**Skin contact:** Allergic skin reaction. Itching. Redness. Moderate skin irritation.

**Eye contact:** Moderate eye irritation. Redness.

**Ingestion:** Not expected under normal conditions of use.

Existing conditions aggravated by

exposure:

Eye, skin and respiratory disorders. Skin allergies.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR

1910.1200).

See Section 11 for additional toxicological information.

#### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%
Talc	14807-96-6	30 - 60
Epichlorohydrin-4,4'-isopropylidene diphenol resin	25068-38-6	30 - 60
Phenol polymer with formaldehyde, glycidyl ether	28064-14-4	10 - 30
Titanium dioxide	13463-67-7	1 - 5

## 4. FIRST AID MEASURES

**Inhalation:** Move to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, give oxygen. Get medical attention.

Skin contact: Immediately flush skin with plenty of water (using soap, if available). Remove

contaminated clothing and footwear. If symptoms develop and persist, get

medical attention.

IDH number: 1377345 Product name: LOCTITE HYS 1C 1GAL PT A

Eye contact: Immediately flush eyes with plenty of water for at least 15 minutes. Get

medical attention.

Ingestion: DO NOT induce vomiting unless directed to do so by medical personnel. Keep

individual calm. If symptoms develop and persist, get medical attention.

## 5. FIRE FIGHTING MEASURES

Flash point: > 200 °C (> 392°F) Cleveland open cup

Autoignition temperature: Not available

Flammable/Explosive limits - lower: Not available

Flammable/Explosive limits - upper: Not available

**Extinguishing media:** Foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear.

Unusual fire or explosion hazards: In case of fire, keep containers cool with water spray. Closed containers may

rupture (due to build up of pressure) when exposed to extreme heat.

Hazardous combustion products: Oxides of carbon. Irritating organic fragments. Aldehydes. Acids.

#### 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:** Do not allow product to enter sewer or waterways.

Clean-up methods: Remove all sources of ignition. Immediately contact emergency personnel.

Scrape up as much material as possible. Clean residue with soap and water.

Store in a partly filled, closed container until disposal.

## 7. HANDLING AND STORAGE

Handling: Keep away from heat, spark and flame. Do not breathe

gas/fumes/vapor/spray. Keep container closed. Avoid contact with eyes, skin

and clothing. Wash thoroughly after handling.

Storage: Store in original container until ready to use. Keep in a cool, well ventilated

area away from heat, sparks and open flame. Keep container tightly closed

until ready for use.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Talc	2 mg/m3 TWA Respirable fraction.	20 MPPCF TWA 2.4 MPPCF TWA Respirable. 0.1 mg/m3 TWA Respirable. 0.3 mg/m3 TWA Total dust.	None	50 ppm
Epichlorohydrin-4,4'-isopropylidene diphenol resin	None	None	None	None
Phenol polymer with formaldehyde, glycidyl ether	None	None	None	None
Titanium dioxide	10 mg/m3 TWA	15 mg/m3 TWA Total dust.	None	None

Engineering controls: Provide adequate local exhaust ventilation to maintain worker exposure below

exposure limits.

Respiratory protection: Use a NIOSH approved air-purifying respirator if the potential to exceed

established exposure limits exists.

**Eye/face protection:** Safety goggles or safety glasses with side shields.

**Skin protection:** Chemical resistant, impermeable gloves.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:

Color:
Odor:
Odor:
Odor hreshold:
PH:
Vapor pressure:
Boiling point/range:
Melting point/ range:
Liquid
Negligible
Negligible
Not available
Negligible
260 °C (500°F)
Melting point/ range:
Not available

Specific gravity: 1.57

Vapor density: Not available

Flash point: > 200 °C (> 392°F) Cleveland open cup

Flammable/Explosive limits - lower:

Flammable/Explosive limits - upper:

Autoignition temperature:

Evaporation rate:

Solubility in water:

Partition coefficient (n-octanol/water):

Not available
Insoluble
Not available

VOC content: 0.01 %; 0.13 g/l (value for resin and hardener together)

## 10. STABILITY AND REACTIVITY

Stability: Stable

Hazardous reactions: Will not occur.

**Hazardous decomposition products:** Oxides of carbon. Irritating organic fragments. Acids. Aldehydes.

**Incompatible materials:** Strong acids. Strong bases. Strong oxidizing agents. Amines. Water.

**Conditions to avoid:** Store away from incompatible materials.

## 11. TOXICOLOGICAL INFORMATION

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Talc	No	No	No
Epichlorohydrin-4,4'-isopropylidene diphenol resin	No	No	No
Phenol polymer with formaldehyde, glycidyl ether	No	No	No
Titanium dioxide	No	Group 2B	No

Hazardous components	Health Effects/Target Organs
Talc	Irritant, Lung, Some evidence of carcinogenicity
Epichlorohydrin-4,4'-isopropylidene diphenol resin	Allergen, Irritant
Phenol polymer with formaldehyde, glycidyl ether	Irritant, Allergen
Titanium dioxide	Irritant, Respiratory, Some evidence of carcinogenicity

## 12. ECOLOGICAL INFORMATION

Ecological information: Not available

#### 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: Not a RCRA hazardous waste.

#### 14. TRANSPORT INFORMATION

#### U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

#### International Air Transportation (ICAO/IATA)

Proper shipping name:
Hazard class or division:
Identification number:
Packing group:
Not regulated
None
None
None

#### Water Transportation (IMO/IMDG)

Proper shipping name:Not regulatedHazard class or division:NoneIdentification number:NonePacking group:None

## 15. REGULATORY INFORMATION

## **United States Regulatory Information**

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12(b) Export Notification: None above reporting de minimus

CERCLA/SARA Section 302 EHS:
CERCLA/SARA Section 311/312:
CERCLA/SARA 313:

None above reporting de minimus
Immediate Health, Delayed Health
None above reporting de minimus

IDH number: 1377345 Product name: LOCTITE HYS 1C 1GAL PT A

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This

product contains a chemical known to the State of California to cause birth defects or other

reproductive harm.

**Canada Regulatory Information** 

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

WHMIS hazard class: D.2.A, D.2.B

#### 16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: First issue.

Prepared by: Gary Pierson, Sr. Regulatory Affairs Specialist

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

IDH number: 1377345 Product name: LOCTITE HYS 1C 1GAL PT A