

OSHA-Required Health And Safety Information!

This Material Safety Data Sheet (MSDS) was requested moments ago from Hercules Automated Fax Information System. Please forward it immediately to the person in charge of MSDS's, or retain it at the machine until claimed.

Section 1

MATERIAL SAFETY DATA SHEET # 6 Hercules Jel Flux

Date Prepared: 2/21/1990 Last Reviewed: 1/25/2010

Meets OSHA 29 CFR 1910.1200



MATERIAL SAFETY INFORMATION SERVICE

Hercules Chemical Company Inc. 111 South Street Passaic NJ 07055

Phone (800) 221-9330 Fax (800) 333-3456

Section 2 - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity;

Common Name(s), CAS Numbers)

OSHA PEL

ACGIH TLV

Other Limits

Upper Bound
Limit if SARA

Limit if SARA Reportable

Zinc Chloride (7646-85-7)

 1.0mg/M^3

1.0mg/M³ (fumes) N/A

26%

Ammonium Chloride (12125-02-9)

N/A

1.0mg/M³ (fumes) N/A

- -

HMIS Hazard Rating: Health: 2 Flammability: 0 Reactivity: 1 Personal Protection: C

Section 3 - Physical/Chemical Characteristics

Boiling Point (°F):

Specific Gravity (H2O = 1):

Vapor Density (Air = 1): Vapor Pressure (mm Hg):

212

1.25

. .

At 100° C 76

Melting Point (° F):

Evaporation Rate:

<1

Solubility in Water:

N/A

(Butyl Acetate = 1)

100% miscible in water

VOC Level (g/l): 0

Appearance And Color:

Greenish yellow color

Odor: None

Section 4 - Fire And Explosion Hazard Data

Flash Point: Flammable Limits: LEL: UEL:

None N/A

Extinguishing Media: As appropriate for surrounding fire.

Special Firefighting Procedures:

None

Unusual Fire And Explosion Hazards:

None

Continued on Next Page

Section 5 - Reactivity Data

Stability: Stable Conditions To Avoid: Avoid contact with concentrated alkalis.

Incompatability Zinc chloride is incompatible with cyanides (may release toxic HCN gas) & sulfide salts (may

(Materials To Avoid): release toxic H2S gas)

Hazardous Decomposition: Will not occur except at high temperatures

Hazardous Polymerization: Will not occur

Section 6 - Health Hazard Data

Routes of Entry: Inhalation N/A Skin YES/Primary Ingestion YES/Primary

Health Hazards:

Individuals with pre-existing diseases of lungs may have increased susceptibility to the toxicity of excessive exposures to zinc chloride.

Carcinogenicity: NTP NO IARC NO OSHA Regulated NO

Signs And Symptoms of Exposure:

INGESTION: Severe damage to internal organs (esophagus & pylorus) will occur if swallowed in large quantities. SKIN CONTACT: Prolonged contact causes burns, skin irritation with discomfort and rash. EYE CONTACT: Will cause eye irritation with discomfort, tearing or blurring of vision.

Medical Conditions Generally Aggravated By Exposure:

Emergency And First Aid Procedures:

INGESTION: Do not induce vomiting. If conscious, dilute by giving large quantities of water or milk. Call a physician immediately. SKIN CONTACT: Wash affected skin area with soapy water. Remove contaminated clothing. If burn or rash appears consult a physician. EYE CONTACT: Immediately flush eyes with plenty of water for 15 minutes. Consult a physician.

Continued on Next Page

Section 7 - Precautions For Safe Handling And Use:

Steps To Be Taken In Case Material Is Released Or Spilled:

Flush with large quantities of water and pick up with absorbing materials.

Waste Disposal Method:

Landfill, to dispose of large quantities, comply with federal, state and local regulations.

Precautions To Be Taken In Handling And Storing:

If handling in large quantities, wear rubber gloves & goggles.

Other Precautions:

None

Section 8 - Control Measures:

Respiratory Protection:

In confined spaces or other circumstances where adequate ventilation cannot be assured use NIOSH-approved respirator, positive pressure airline mask, or self contained breathing apparatus.

Ventilation: Local Exhaust N/A Special N/A

Mechanical Exhaust fan

Gloves: Rubber gloves

Eye Protection: Safety goggles

Other Protective

Clothing: Gloves while handling the material.

Work/Hygienic Practices: Wash thoroughly after handling.





For Hercules Material Safety Data Sheets by fax anytime, day or night, just call 1-800-942-INFO (1-800-942-4636) from any Touch-Tone phone. Have your fax number ready. Checking the product label for the correct MSDS # will save time.

Other: N/A