

OSHA-Required Health And Safety Information!

This Material Safety Data Sheet (MSDS) was requested moments ago from Hercules Automated Fax Information System. Please forward it immediately to the person in charge of MSDS's, or retain it at the machine until claimed.

Section 1

MATERIAL SAFETY DATA SHEET # 116

Hercules Plumber's Firestop Caulk

Date Prepared: 7/12/2004 Last Reviewed:

Meets OSHA 29 CFR 1910.1200

HERCULES®

MATERIAL SAFETY INFORMATION SERVICE

Hercules Chemical Company Inc. 111 South Street

Passaic NJ 07055 Phone (800) 221-9330 Fax (800) 333-3456

Section 2 - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s), CAS Numbers)

OSHA PEL

ACGIH TLV

Other Limits

Upper Bound Limit if SARA Reportable

Proprietary mixture

HMIS Hazard Rating: Health: 1 Flammability: 0 Reactivity: 0 Personal Protection: A

Section 3 - Physical/Chemical Characteristics

Boiling Point (°F):

Specific Gravity Vapor Density Vapor

212

1.10

N/A

Pressure N/A

Melting Point (° F

Evaporation Rate:

(Rutyl Acetate = 1)

Solubility in Water:

N/A

>1

slightly

Percent volatile 22%

Appearance And Color:

Pale, red paste

Odor: Minimal odor

Section 4 - Fire And Explosion Hazard Data

Flash Point

Flammable Limit

LEL:

UEL:

N/A

N/A N/A

Extinguishing Media: Dry chemical. Carbon dioxide, Foam, water spray

Special Firefighting Procedures:

As for surrounding fires

Unusual Fire And Explosion Hazards:

Not a fire hazard Continued on Next Page

Hercules Chemical Material Safety Data Sheet # 116

Hercules Plumber's Firestop Caulk

Page 2

Section 5 - Reactivity Data

Stability: Stable Conditions To Avoid: Storage above 55 deg C

Incompatability None

(Materials To Avoid):

Hazardous Decomposition: N/A

Hazardous Polymerization: Will Not Occur

Section 6 - Health Hazard Data

Routes of Entr Inhalation N/A Skin Yes/Secondary Ingestion N/A

Health Hazard

Chronic Hazards: None known. Acute Hazards: May cause skin irritation on prolonged contact

Carcinogenicit NTP NO IARC NO OSHA Regulated NO

Signs And Symptoms of Exposure:

Eye: Contact may cause irritation. Skin: Contact may cause irritation. Inhalation: Irritation of the nose, throat and lungs may result from over-exposure to vapors or mist. Ingestion: Relatively non-toxic

Medical Conditions Generally Aggravated By Exposure:

None Known

Emergency And First Aid Procedures:

SKIN: Wash thoroughly with water. EYES: Flush with water for 15 minutes. Seek medical attention if irritation persists. Inhalation: Remove to fresh air. If not breathing, give artificial respiration. Get medical attention.

INGESTION: Not applicable.

Continued on Next Page

Section 7 - Precautions For Safe Handling And Use:

Steps To Be Taken In Case Material Is Released Or Spilled:

Use an absorbent material and sweep up for disposal.

Waste Disposal Method:

Dispose according to applicable federal, state and local regulations.

Precautions To Be Taken In Handling And Storing:

Store under ambient conditions. No special handling required.

Other Precautions:

None required

Section 8 - Control Measures:

Respiratory Protection:

N/A

Ventilation: Local Exhaust Adequate

Mechanical N/A Other N/A

Other 14/7

Special N/A

:

Gloves Rubber

Eye Protection: Safety glasses/goggles

Other Protective

Clothina:

N/A

Work/Hygienic Practice Use good personal hygiene practices. Wash thoroughly after handling.





For Hercules Material Safety Data Sheets by fax anytime, day or night, just call 1-800-942-INFO (1-800-942-4636) from any Touch-Tone phone. Have your fax number ready. Checking the product label for the correct MSDS # will save time.