



PVC Short Repair Couplings

Space Saving, Compact Version of Standard Repair Coupling
Requires 1/3 less Space

(SH119) Socket x Socket



(SH118) Spigot x Socket

- | Compact Telescoping Design
- | Socket x Socket Configuration for Pipe Repair or Use as a Short-Stroke Expansion Joint
- | Spigot x Socket Configuration for Replacing Damaged Fittings
- | Both Configurations can be Easily Modified for Opposite Use
- | Available in PVC White, Sizes 1/2" - 2"
- | EPDM Double O-ring Seal
- | Pressure Rated to 235 PSI @ 73°F (23°C)
- | NSF Certified for Potable Water Use

PVC - Spigot x Soc

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
PVC White with EPDM O-ring					
SH118-05	1/2	36	0	025	5.28
SH118-07	3/4	30	0	025	6.00
SH118-10	1	35	0	025	6.93
SH118-12	1-1/4	25	0	025	13.05
SH118-15	1-1/2	32	0	025	14.21
SH118-20	2	15	0	025	21.98

PVC - Soc x Soc

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
PVC White with EPDM O-ring					
SH119-05	1/2	40	0	025	5.28
SH119-07	3/4	30	0	025	6.00
SH119-10	1	30	0	025	6.93
SH119-12	1-1/4	20	0	025	13.05
SH119-15	1-1/2	21	0	025	14.21
SH119-20	2	12	0	025	21.98

Dimensions

Size	L1	L2	L3	L4	L5	S	M
1/2	5-7/8	4-5/16	4-15/16	7/8	3/4	2	1-7/16
3/4	6-9/16	4-3/4	5-7/16	1	13/16	2-1/4	1-3/4
1	6-13/16	4-3/4	5-9/16	1-1/8	15/16	2-3/16	2-1/16
1-1/4	7-15/16	5-11/16	6-5/8	1-1/4	1	2-1/2	2-7/16
1-1/2	8-1/4	5-13/16	6-3/4	1-3/8	1-1/8	2-13/16	2-11/16
2	10-1/16	7-3/8	8-5/16	1-1/2	1-3/16	3-1/8	3-1/4

INSTALLATION NOTE: For expansion joint applications, install with unit 1/2 extended. System must be supported and blocked against thrusts and movement under pressure. May be installed with flow in either direction.

NOT FOR USE WITH COMPRESSED AIR OR GAS

Page 21

Thursday, January 13, 2011 7:36:56 AM

Spears® Manufacturing Company

Progressive Products from Spears® Innovation and Technology