

## Passive Ceiling Mount Telecommunications Enclosures

### APPLICATION

Leviton's Ceiling Mount Telecommunications Enclosures mount in standard drop ceilings. The enclosures accommodate removable 19" rack-mount patch panels and wire management for use in zone cabling applications. Edge protected cable access ports with fire-rated foam sealing kits make these enclosures ideal for use in plenum spaces.

### FEATURES

- Fully-hinged, drop down doors support installed equipment and open to provide safe, easy access.
- Enclosures install flush with the drop ceiling for clean look.
- Plenum-rated.
- Two edge-protected cable access ports with fire-rated foam sealing kit.
- 2' x 2' enclosure houses one removable rack-mount assembly with total 5RU space.

### STANDARDS COMPLIANCE

UL Listed - Communications Circuit Accessory.

### PHYSICAL SPECIFICATIONS

Dimensions: See second page.  
Weight: Unit weight - 38 lbs  
Door weight capacity - 25 lbs  
Maximum unit weight capacity - 75 lbs  
Materials: Enclosures are manufactured of .060" sheet aluminum with riveted construction. Foam Sealing Kit is polychloroprene latex compound.

### WARRANTY INFORMATION

For a copy of Leviton product warranties, log on to [www.levitonvoicedata.com/warranty](http://www.levitonvoicedata.com/warranty).

### DESIGN CONSIDERATIONS

- Use for zone cabling applications such as consolidation points.
- Use 3/8" threaded rods and hardware (sold separately) to support the enclosure within the drop ceiling.
- Use #12-24 equipment mounting screws to attach patch panels (included with all Leviton patch panels).

See ELECTRONIC FILES for CAD files (.DXF, .DWG, MS-DOS.EPS) on disk



### TYPICAL SPECIFICATION

Ceiling Mount Telecommunications Enclosures shall be plenum-rated and suitable for installation in air handling spaces, and shall fit standard drop ceiling tile sizes. Fire-rated foam sealing kit shall be included. Units shall accommodate removable 19" rack-mount assemblies with space for passive devices, patch panels and wire management for consolidation points or other zone cabling applications.

For ELECTRONIC Typical Specs see (.TXT) file on disk.



For Technical Support Call 1-425-485-4288; in USA call 1-800-824-3005.  
Spec sheets and updates are also available at [www.levitonvoicedata.com](http://www.levitonvoicedata.com).

2222 - 222nd St. SE • Bothell, WA 98021 USA  
Tel: 1-800-722-2082 / 1-425-485-4288 • Fax: 1-425-483-5270 • Int'l Fax: 1-425-485-9170 • GSA Schedule Available.




# Passive Ceiling Mount Telecommunications Enclosures

Part Number  
**Z1000-PC2**

.....

## DIMENSIONAL LINE ART

See ELECTRONIC FILES for CAD images  
(.DXF, .DWG, MS-DOS.EPS)



## PART NUMBERS

Description	Part No.
Passive Ceiling Mount Telecommunication Enclosure	Z1000-PC2



For Technical Support Call 1-425-485-4288; in USA call 1-800-824-3005.  
Spec sheets and updates are also available at [www.levitonvoicedata.com](http://www.levitonvoicedata.com).



2222 – 222nd St. SE • Bothell, WA 98021 USA • Tel: 1-800-722-2082 / 1-425-485-4288 • Fax: 1-425-483-5270 • Int'l Fax: 1-425-485-9170 • GSA Schedule Available.