PRODUCT SPECIFICATION



	LOG NUMBER: See table below DESCRIPTION: STOW twist lock "Y" adapter cord set			t
CONSTRUCTION PARAMETERS:				
Cable gauge: Cable stranding: Jacket material: Cord rating: Cable legend type: Cable temperature rating:			See table below Class K (30 ga strands) Low durometer (<75A) PVC, yellow Extra Hard Usage per the National Electric Code Indent print -40 to +60 °C	
Cord set length: Attachment plug and cord connectors: Plug material: "Y" material: Cord connector material: Connector markings:		3 ft. total, 2 ft plug to "Y" See table below for NEMA configurations PVC, black PVC, black PVC, clear with power indicator light CCI and NEMA configuration on face surfaces		
Catalog number	Cable gau	ae	Plug configuration	Cord connector configuration
01923 01924	12/4 (plug to "Y		L14-20P	(2) L5-20R (2) 5-20R
01933 01934	10/4 (plug to "Y	′"), 10/3	L14-30P	(2) L5-20R (2) 5-20R

The information presented here is, to the best of our knowledge, true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable Inc.. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable Inc..

CUSTOMER APPROVAL: Approved by:

Title: