




PRODUCT SPECIFICATION

CATALOG NUMBER: 01970-3R-02
PRODUCT DESCRIPTION: Construction-site portable power distribution box
NRTL APPROVAL: ETL Listed to UL 1640 and CAN/CSA C22.2 No. 14



PRODUCT DESCRIPTION

Power inlet: 50A 125/250V California Standard twist lock flanged inlet with integral cover
Power outlets: (1) 50A 125/250V California Standard twist lock receptacle
(1) NEMA L6-30R 30A 250V twist lock receptacle
(6) NEMA 5-20R 20A 125V straight blade receptacles
Over-current protection: 50A receptacle - none
30A receptacle - 30A circuit breaker for each ungrounded conductor
20A receptacles - 20A circuit breaker for each receptacle
Ground fault protection: Individual Class A GFCI for each 20A receptacle
Over-voltage protection: Provided by GFCI on each 20A receptacle



Enclosure type: NEMA Type 3R, rainproof
Enclosure material: Carbon steel, protected by e-coat and yellow exterior paint finish
Enclosure base: Carbon steel, with black powder coat finish
Receptacle covers: Thermoplastic, on all receptacles
Receptacle cover colors: Black, except for the 30A receptacle cover, which is gray
Weight (approx): 32 lbs.

The information presented here is, to the best of our knowledge, true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.

This specification is the proprietary intellectual property of Coleman Cable Inc.. Any information contained herein shall not be disclosed to any party without the written consent of Coleman Cable Inc..