



PRODUCT SPECIFICATION

CATALOG NUMBER: 02822

DESCRIPTION: Cord connected portable GFCI, with duplex GFCI receptacle in thermoplastic protective housing

The GFCI receptacle has an automatic power-on reset

APPROVALS: UL 943, Class A Ground Fault Circuit Interrupter; complies with OSHA requirements, including open-neutral protection, for personnel protection in temporary wiring installations

CONSTRUCTION PARAMETERS:

Cord type: 12/3 SJTW
Cord length: 6 ft.
Cord color: Yellow
Attachment plug configuration: NEMA 5-15P
Attachment plug color: Yellow
Receptacle configuration: NEMA 5-15R

Housing material: ABS
Housing color: Yellow
Housing dimensions (approx): 8.5 x 3.8 x 3.5 including handle
Receptacle protection: Spring-loaded cover provides protection when not in use; sloping top repels rain



ELECTRICAL & ENVIRONMENTAL PROPERTIES:

Temperature rating: -30 to +60 °C
Operating environment: Outdoor, if protected from water entry
Nominal operating voltage: 120 VAC
Maximum operating current: 15 A
Maximum operating wattage: 1800 W

The information presented here is, to the best of our knowledge, true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable Inc. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable Inc.