



PRODUCT SPECIFICATION

COLEMAN CATALOG NUMBER: 07605

DESCRIPTION: Metal halide light intended for temporary job-site lighting

OPERATING ENVIRONMENT: Indoor/ outdoor, suitable for use in dry or damp locations

APPROVALS: UL/CUL Listed; meets OSHA and NEC requirements, EISA2007 compliant

CONSTRUCTION PARAMETERS:

Dimensions: 10" x 10" x 23" high, including mounting hook w/ spring latch

Weight: 20 lbs (approx)

Lamp guard: Plated steel wire, includes snap-on protective bottom guard

Ballast type: ANSI M135/M155 CWA, pulse start

Lamp holder: EX39 exclusionary mogul base

Electrical supply: Supplied pre-wired with a 6' 18/3 SJTW power supply cord with a NEMA 5-15P 125V 15A attachment plug

Voltage options: Quad-tap ballast for operation at 120V, 208V, 240V, or 277V

Wiring options: (2) knock-outs in wiring compartment accommodate hard-wiring if required by local code

Lamp requirements:

Lamp type: Pulse start MP400, w/ extended eyelet mogul base, "O" rated, CCI #07625

Lamp wattage: 400 watts



The information presented here is, to the best of our knowledge, true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable Inc. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable Inc.