



## PRODUCT SPECIFICATION

**COLEMAN PART NUMBER:** See table below

**DESCRIPTION:** 14/2 w/gnd SPT-3 power supply cord with straight attachment plug cap.

**APPROVALS:** UL Listed

### CONSTRUCTION PARAMETERS:

Conductor:	14 AWG, 41/30 bunched bare copper
Conductor O.D. (nom):	0.071"
Insulated ground conductor O.D. (nom):	0.106"
Insulation material:	PVC, beige
Overall cable dimensions (nom):	0.234 x 0.512"
Attachment plug configuration:	NEMA 5-15P
Plug material:	PVC, beige
Open end configuration:	1.5" separation, 0.38" strip

### ELECTRICAL PROPERTIES:

Temperature rating:	-20 to +60 °C
Maximum operating voltage:	125 VAC
Maximum operating current:	15 A
Maximum operating wattage:	1875 W

### PART NUMBERS

Catalog number	Cable length
09743	3 ft
09746	6 ft

The information presented here is, to the best of our knowledge, true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable Inc. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable Inc.

**CUSTOMER APPROVAL:** Approved by: \_\_\_\_\_ Date: \_\_\_\_\_  
Title: \_\_\_\_\_