

## PRODUCT DATA SHEET

Controlled Document - Engineering Drive

1530 Shields Drive Waukegan, IL 60085 Toll-Free (800) 323-9355 Fax: (847) 689-1192

**PART NUMBER:** 

**DESCRIPTION:** 14/4 STRANDED STOW FLEXIBLE POWER CABLE

This cable consists of four bare copper insulated conductors cabled with fillers with an overall jacket. CONSTRUCTION:

APPROVALS: Underwriter's Laboratory, Canadian Standards Association, NEC Article 400

600 Volt Outdoor and Oil Portable Power Cable Applications **APPLICATION:** 

(	$\mathbb{C}$ o	nsi	tru	ctic	าท	Par	am	ete	rs:

Conductor 14 AWG Bare Copper

Stranding 41/30 Insulation Material **PVC** 

Insulation Thickness 0.046" Nom. Insulated Conductor Diameter 0.166" Nom. 4

Number of Conductors

Lay Length 3.25" Nom.

Lay Direction All Layers Left Hand Lay

Filler Polypropylene Separator Paper Tissue **Jacket Material PVC** 

Jacket Thickness 0.082" Nom. Overall Cable Diameter 0.565" Nom. Approximate Cable Weight 168.5 Lbs/1M' Nom.

Flame Rating **UL/CSA Horizontal Flame Test** 

## **Electrical Properties:**

Temperature Rating -20°C to 60°C 600 V RMS Max. Operating Voltage DC Resistance per Conductor @ 20°C 2.53 Ohms/1M' Nom.

**Insulation Colors** Jacket Color

Black White Red Green

Gray or Yellow (Other colors available for minimum order)

CSA LL39753 STOW 600V 60C FT1 WATER-RESISTANT

Legend (Indent Print)

This product complies with European Directive 2002/95/EC (RoHS)

On special orders, the customer will accept all factory lengths and +/- 10 percent of total order requested.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of products(s) is conditioned upon acceptance of a purchase order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman cable disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable.

Customer Name	 	
Customer Approval _		