PRODUCT DATA SHEET

Controlled Document - Engineering Drive

1530 Shields Drive Waukegan, IL 60085 Toll-Free (800) 323-9355 Fax: (847) 689-1192

PART NUMBER: 20049

DESCRIPTION: 10/4 STRANDED TYPE STOW FLEXIBLE POWER CABLE

This cable consists of four bare copper insulated conductors cabled with fillers and an overall jacket. UL Standard 62, CSA 22.2 No. 49, NEC Article 400. CONSTRUCTION:

APPROVALS:

APPLICATION: 600V Portable Oil and Water Resistant Outdoor Flexible Power Cable Construction Parameters:	
Electrical Properties: Temperature Rating Operating Voltage DC Resistance per Conductor @ 20°C	-20 ^o C to 60 ^o C 600 V RMS Max. 0.99 Ohms/1M' Nom.
Insulation Colors Jacket Color	Black White Red Green Yellow or Gray (Other colors available for minimum order)
Legend (Indent Print)	CCI ROYAL * * 4/C 10 AWG (5.26mm 2) STOW E54864 (UL) 600V 60C CSA LL39753 STOW FT1 WATER-RESISTANT
This product complies with European Directive 2002/98. The customer will accept all factory lengths and +/- 10 percent of tot	
control all product data presented is for informational purposes only or confer any rights on any customer. The sale of products(s) is cor	without limitation Coleman Cable's standard warranty. Coleman cable
This specification is proprietary intellectual property of Coleman Cat party without written consent of Coleman Cable.	ole. Any information contained herein shall not be disclosed to any
Customer NameCustomer Approval	
Specification Issue Date: October 29, 2008	

1-800-323-9355 (Phone) 1-847-689-1192 (Fax)