

PRODUCT DATA SHEET

Controlled Document - Engineering Drive

1530 Shields Drive Waukegan, IL 60085 Toll-Free (800) 323-9355 Fax: (847) 689-1192

PART NUMBER: 20147

DESCRIPTION: 14/4 STRANDED SJTOW FLEXIBLE POWER CABLE

CONSTRUCTION: This cable consists of four bare copper insulated conductors cabled with fillers with an overall jacket.

APPROVALS: Underwriter's Laboratory, Canadian Standards Association, NEC Article 400

APPLICATION: 300 Volt Outdoor and Oil Portable Power Cable Applications

Cons	struct	lion	Parar	neters:

Conductor 14 AWG Bare Copper

Stranding 41/30
Insulation Material PVC
Insulation Thickness 0.031" Nom.
Insulated Conductor Diameter 0.136" Nom.

Number of Conductors 4

Lay Length 3.25" Nom.

Lay Direction All Layers Left Hand Lay
Filler Polypropylene

Filler Polypropylene
Separator Paper Tissue
Jacket Material PVC
Jacket Thickness 0.033" Nom.
Overall Cable Diameter 0.395" Nom.
Approximate Cable Weight 103 Lbs/1M' Nom.

Flame Rating UL/CSA Horizontal Flame Test

Electrical Properties:

Temperature Rating -20° C to 60° C Operating Voltage 300 V RMS Max. DC Resistance per Conductor @ 20° C 2.58 Ohms/1M' Nom.

Insulation Colors Black White Red Green

Jacket Color Gray or Yellow (Other colors available for minimum order)

Legend (Indent Print) CCI ROYAL = 14 AWG (2.08mm²) 4/C SJTOW (UL) 300V 60C --

CSA LL39753 SJTOW 300V 60C FT1 WATER-RESISTANT

This product complies with European Directive 2002/95/EC (RoHS)

On special orders, the customer will accept all factory lengths and +/- 10 percent of total order requested.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of products(s) is conditioned upon acceptance of a purchase order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman cable disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable.

Customer Name	 	
Customer Approval _	 	 -

Specification Issue Date: February 4, 2011