



PRODUCT DATA SHEET

Controlled Document - Engineering Drive


1530 Shields Drive
Waukegan, IL 60085
Toll-Free (800) 323-9355
Fax: (847) 689-1192

PART NUMBER: 54707
DESCRIPTION: 18/7 SOLID UNDERGROUND SPRINKLER SYSTEM WIRE
CONSTRUCTION: This cable consists of seven bare copper insulated conductors with an overall jacket.
APPROVALS: Underwriters Laboratory - Underground Golf Course Sprinkler System Cable
APPLICATION: Underground Sprinkler Systems

Construction Parameters:

Conductor	18 AWG Bare Copper
Stranding	Solid
Insulation Material	Polypropylene
Insulation Thickness	0.016" Nom.
Insulated Conductor Diameter	0.072" Nom.
Number of Conductors	7
Lay Length	Parallel
Jacket Material	PE
Jacket Thickness	0.026" Nom.
Overall Cable Diameter	0.268" Nom.
Approximate Cable Weight	53.7 Lbs/1M' Nom.
Flame Rating	VW-1 or FT1 Verticle Flame Test

Cable Cross-Section



Electrical & Enviromental Properties:

Temperature Rating	-20°C to 60°C
Operating Voltage	30 Volts RMS Max.
Capacitance Between Conductors @ 1 KHz	16 pF/ft Nom.
Capacitance Between Conductors to Shield @ 1 KHz	-----
DC Resistance per Conductor @ 20°C	6.32 Ohms/1M' Nom.

Insulation Colors	Red White Green Blue Yellow Brown Orange
Jacket Color	Black (Other colors available for minimum order)

Legend (Surface Ink Print)	BARON WIRE E54868 18 AWG BAROGATION 30V SPRINKLER SYSTEMS WIRE (UL) DIRECT BURIAL yyddd
----------------------------	--

This product complies with European Directive 2002/95/EC (RoHS)

On special orders, the customer will accept all factory lengths and +/- 10 percent of total order requested.

Cable has a rip cord for easy jacket removal. The jacket is sequentially footmarked.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of products(s) is conditioned upon acceptance of a purchase order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman Cable disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable.

Customer Name _____

Customer Approval _____

Specification Issue Date: July 27, 2007