

PRODUCT DATA SHEET

Controlled Document - Engineering Drive

1530 Shields Drive Waukegan, IL 60085 Toll-Free (800) 323-9355 Fax: (847) 689-1192

PART NUMBER: 54712

DESCRIPTION: 18/12 SOLID UNDERGROUND SPRINKLER SYSTEM WIRE

CONSTRUCTION: This cable consists of twelve bare copper insulated conductors with an overall jacket. **APPROVALS:** Underwriters Laboratory - Underground Golf Course Sprinkler System Cable

APPLICATION: Underground Sprinkler Systems

Construction Parameters:

Cable Cross-Section

Conductor 18 AWG Bare Copper Stranding Solid

Insulation Material Polypropylene
Insulation Thickness 0.016" Nom.
Insulated Conductor Diameter 0.072" Nom.

Number of Conductors

Number of Conductors 12
Lay Length Parallel
Jacket Material PE
Jacket Thickness 0.026" Nom.

Overall Cable Diameter 0.352" Nom.
Approximate Cable Weight 87.7 Lbs/1M' Nom.

Flame Rating VW-1 or FT1 Verticle Flame Test



Electrical & Environmental Properties:

Temperature Rating -20°C to 60°C
Operating Voltage 30 Volts RMS Max.
Capacitance Between Conductors @ 1 KHz 16 pF/ft Nom.

Capacitance Between Conductors to Shield @ 1 KHz

DC Resistance per Conductor @ 20°C 6.32 Ohms/1M' Nom.

Insulation Colors Red White Green Blue Yellow Brown Orange Black Pink Gray Tan Purple

Jacket Color Black (Other colors available for minimum order)

Legend (Surface Ink Print) BARON WIRE E54868 18 AWG BAROGATION 30V SPRINKLER SYSTEMS

WIRE (UL) DIRECT BURIAL yyddd

This product complies with European Directive 2002/95/EC (RoHS)

On special orders, the customer will accept all factory lengths and +/- 10 percent of total order requested.

Cable has a rip cord for easy jacket removal. The jacket is sequentially footmarked.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of products(s) is conditioned upon acceptance of a purchase order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman Cable disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable.

Customer Name			
Customer Approval			

Specification Issue Date: July 27, 2007