

# PRODUCT DATA SHEET

Controlled Document - Engineering Drive

1530 Shields Drive Waukegan, IL 60085 Toll-Free (800) 323-9355 Fax: (847) 689-1192

**PART NUMBER:** 92003-xx-08

**DESCRIPTION:** RG-6/U GAS INJECTED COAXIAL CABLE WITH 60%

ALUMINUM BRAID AND SWEEP TO 3.0 GHZ

RATING: ETL DUAL LISTED AS CM/CL2 AND CATV

## Construction Parameters:

		<u>waii (in)^</u>	<u>OD (in)^</u>
Conductors:	18 AWG (1/.040) Copper Clad Steel		0.040
Dielectric:	Foam Polyethylene color natural	0.070	0.180
Shielding:	Polyester/Aluminum Fusible Tape plus 60% Aluminum Braid		0.216
Jacket:	PVC	0.032	0.269

# **Electrical Properties:**

#### **VALUE\*** Impedance (ohms): 75 Capacitance (pF/ft): 17 Velocity of Propagation (%): 81 Attenuation (db/100 ft): 10 MHz 0.8 50 MHz 1.3 100 MHz 1.65 200 MHz 3.1 400 MHz 4.12 700 MHz 6.28 1000 MHz 6.48 1200 MHz 6.60 1500 MHz 9.30 2000 MHz 9.76 2200 MHz 9.79 2500 MHz 10.13

# Cable Cross-section:



## Miscellaneous Information:

Jacket Color: Black or White

Jacket Print: COLEMAN CABLE 92003 RG6 18 AWG CCS DUAL SHIELD 60% AL BRAID (Sequentially footprinted) (ETL) 3020454 CM OR CL2 OR CATV 75C SUN RES SWEPT TO 3.0 GHZ

14.61

Applicable NEC Article: 725 and 820

Flame Rating: UL-1581 Vertical Tray Flame Test

3000 MHz

Max. Temperature Rating: 75° C Approximate Weight (lb/1000 ft): 30

This product complies with European Directive 2002/95/EC (RoHS) On special orders the customer will accept all factory lengths and  $\pm$  10% of total order requested.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control, all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of product (s) is conditioned upon acceptance of a purchase order subject to Coleman Cable's standard warranty. Coleman cable disclaims all liability in connection with the use of information contained herein or otherwise

Company Name:		
Customer Approval:	Date:	

Issued: 09/20/2006 \*=Nominal value By: HCS