



# PRODUCT DATA SHEET

Controlled Document - Engineering Drive


1530 Shields Drive  
Waukegan, IL 60085  
Toll-Free (800) 323-9355  
Fax: (847) 689-1192

**PART NUMBER:** 94544  
**DESCRIPTION:** 14/4 STRANDED CM/CL3/FPL/PLTC DIRECT BURIAL SOUND AUDIO CABLE  
**CONSTRUCTION:** This cable consists of four bare copper insulated conductors and an overall jacket.  
**APPROVALS:** UL Standard 13, 444 & 1424 NEC Articles 725, 760 & 800.  
**APPLICATION:** General Purpose Direct Burial Power Limited Circuit, Fire Alarm, Tray and Communications Cable Used in Audio Applications

## Construction Parameters:

Conductor	14 AWG Bare Copper
Stranding	105/34
Insulation Material	PVC
Insulation Thickness	0.009" Nom.
Insulated Conductor Diameter	0.091" Nom.
Number of Conductors	4
Lay Length	3.00" Nom.
Core Wrap	None
Jacket Material	PVC
Jacket Type	Tubed
Jacket Thickness	0.020" Nom.
Overall Cable Diameter	0.260" Nom.
Approximate Cable Weight	67.2 Lbs/1M' Nom.
Flame Rating	UL 1581 Vertical Tray Flame Test

## Cable Cross-Section



## Electrical Properties:

Temperature Rating	-20°C to 60°C
Operating Voltage	300 V RMS Max.
Capacitance Between Conductors @ 1 KHz	42 pF/ft Nom.
Capacitance Between Conductors to Shield @ 1 KHz	-----
DC Resistance per Conductor @ 20°C	2.56 Ohms/1M' Nom.

Insulation Colors	Black Red White Green
Jacket Color	Varies (Consult Factory)

Legend (Surface Ink Print) COLEMAN CABLE 94544 14 AWG 4/C C(ETL)US (ETL CODE) TYPE CM/CL3/FPL/PLTC  
DIRECT BURIAL AUDIO CABLE SUN RES -- TYPE CMH FT1

This product complies with European Directive 2002/95/EC (RoHS)

On special orders, the customer will accept all factory lengths and +/- 10 percent of total order requested.

Cable has a rip cord for easy jacket removal. The jacket is sequentially footmarked.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of products(s) is conditioned upon acceptance of a purchase order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman Cable disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable.

Customer Name \_\_\_\_\_ Date Signed \_\_\_\_\_  
Customer Approval \_\_\_\_\_

Specification Issue Date: March 12, 2008