PRODUCT DATA SHEET

Controlled Document - Engineering Drive

1530 Shields Drive Waukegan, IL 60085 Toll-Free (800) 323-9355 Fax: (847) 689-1192

PART NUMBER: 97194

DESCRIPTION: 24/2PR +16/2 CL2R/CMR CMX OUTDOOR CABLE

CONSTRUCTION: This cable consists of 24/2 pair and 16 AWG two insulated conductors with an overall

PVC jacket

APPROVALS: ETL Listed to UL Standard 13 & 444		
Construction Parameters:		
Conductors	24ga: 16ga:	24 AWG Solid BC 16 AWG 19/.0117" BC
Insulation (Polyethylene)	24ga: 16ga:	0.008" Nom. 0.008" Nom.
Insulated Cond. Dia.	24ga: 16ga:	0.036" Nom. 0.074" Nom.
Number of Conds.	24ga: 16ga:	4 (2 twisted pairs) 2
Lay Length	· ·	24ga pairs are twisted to CAT5E lay lengths, 16ga run parallel under jacket
Overall Jacket Material		PVC
Overall Jacket Thickness		0.017" Nom.
Overall Cable Diameter		0.185" Nom.
Approximate Cable Weight		33.9 Lbs/1M' Nom.
Flame Rating		UL 1666 Riser Flame Test
Electrical Properties:		
Temperature Rating		-20°C to 60°C
Operating Voltage		300 V RMS Max.
Component Colors		24/2pr: White/Blue & Blue White/Orange & Orange
Jacket Color		16/2: Black Red White (Other colors available, please consult factory)
1/0 (115:0		0015MAN 0ADI 5 07404 04/0DD 46/0 0/57LVIO 57L # TVP5 0MD/01 0D 0MV
Legend (Surface Ink Print)		COLEMAN CABLE 97194 24/2PR + 16/2 C(ETL)US ETL# TYPE CMR/CL2R CMX OUTDOOR CMG FT4
This product complies with European Directive 2002/95/EC (RoHS) On special orders, the customer will accept all factory lengths and +/- 10 percent of total order requested. Material is not returnable and purchase order is non-cancelable after production has been started or special materials have been ordered. The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control, all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman Cable disclaims all liability in connection with the use of information contained herein or otherwise.		
This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable.		
Customer Name		Date Signed
Customer Approval		_
Specification Issue Date: January 10, 2008		