



PRODUCT DATA SHEET

Controlled Document - Engineering Drive


1530 Shields Drive
Waukegan, IL 60085
Toll-Free (800) 323-9355
Fax: (847) 689-1192

PART NUMBER: 98300
DESCRIPTION: 18/2 SOLID SHIELDED FPLR
CONSTRUCTION: This cable consists of two bare copper insulated conductors with an overall shield with a drain. The overall assembly has an overall jacket.
APPROVALS: UL Standard 1424 and 444, NEC Articles 760 and 800.
APPLICATION: Power Limited Fire Alarm Cable and Communications Cable for Riser Applications

Construction Parameters:

Cable Cross-Section

Conductor	18 AWG Bare Copper
Stranding	Solid
Insulation Material	PVC
Insulation Thickness	0.008" Nom.
Insulated Conductor Diameter	0.056" Nom.
Number of Conductors	2
Lay Length	4.00" Nom.
Shield	Alum/Mylar
Drain	24 AWG Solid Tinned Copper
Jacket Material	PVC
Jacket Thickness	0.014" Nom.
Overall Cable Diameter	0.151" Nom.
Approximate Cable Weight	19.2 Lbs/1M' Nom.
Flame Rating	UL 1666 Riser Flame Test



Electrical Properties:

Temperature Rating	-20°C to 60°C
Operating Voltage	300 V RMS Max.
Capacitance Between Conductors @ 1 KHz	63 pF/ft Nom.
Capacitance Between Conductors to Shield @ 1 KHz	115 pF/ft Nom.
DC Resistance per Conductor @ 20°C	6.32 Ohms/1M' Nom.

Insulation Colors	Black Red
Jacket Color	Red (Other colors available for minimum order)

Legend (Surface Ink Print)	COLEMAN CABLE 98300 18 AWG 2/C C(ETL)US (ETL CODE) TYPE CMR/CL3R/FPLR SUN RES - TYPE CMG FT4
----------------------------	-------------------------------------------------------------------------------------------------

This product complies with European Directive 2002/95/EC (RoHS)
On special orders, the customer will accept all factory lengths and +/- 10 percent of total order requested.
The jacket is sequentially footmarked. Rip cord added under jacket for ease of jacket removal.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control, all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman Cable disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable.

Customer Name _____ Date Signed _____

Customer Approval _____

Specification Issue Date: January 19, 2007