



PRODUCT DATA SHEET


Controlled Document - Engineering Drive

1530 Shields Drive
Waukegan, IL 60085
Toll-Free (800) 323-9355
Fax: (847) 689-1192

PART NUMBER: 99286
DESCRIPTION: CAT5E 24/4PAIR PLUS A 16 AWG 4/C IN A 2 "LEG" PARALLEL CONSTRUCTION
CONSTRUCTION: This cable consists of four 16 AWG cabled conductors and one CAT5E 24/4Pair, laid parallel under an overall PVC jacket.
APPROVALS: ETL Listed as CMR/CL3R, CMG/FT4
APPLICATION: DIGITAL COMMUNICATION & POWER LIMITED CABLE APPLICATIONS

Construction Parameters:

Conductor (16 AWG 4/C) 16 AWG Bare Copper
Stranding 26/30
Insulation PVC
Insulation Thickness 0.009" Nom.
Conductor Thickness 0.077" Nom.
Lay Length 4.00" Nom.
Conductor (CAT5E, 24 AWG 4/PAIR) 24 AWG Bare Copper
Stranding Solid
Dielectric Solid PE
Dielectric Thickness 0.008" Nom.
Conductor Diameter 0.036" Nom.
Pair Lay Length Different length for cross-talk prevention
Overall Jacket Material PVC
Overall Jacket Thickness 0.022" Nom.
Overall Cable Diameter 0.202" / 0.228" x 0.440" Nom.
Approximate Cable Weight 67.3 Lbs/1M' Nom.
Flame Rating UL 1666 Riser Flame Test



Electrical Properties:

16 AWG 4/C
Temperature Rating -20°C to 60°C
Operating Voltage 300 V RMS Max.
DC Resistance per Conductor @ 20°C 4.00 Ohms/1M' Nom.
Capacitance Between Conductors @ 1 KHz 35 pF/ft Nom.

CAT5e 24/4PR

Freq. (MHz)	Attn. (dB/100m) Max	NEXT loss (dB) Min	PSNEXT loss (dB) Min	ACR (dB@100m) Min	PSACR (dB@100m) Min	ELFEXT (dB@100m) Min	PSELFEXT (dB@100m) Min	Ret. Loss (dB) Max
1	2.0	65.3	62.5	63.3	60.3	63.8	60.8	20.0
10	6.5	50.3	47.3	43.8	40.8	43.8	40.8	25.0
16	8.2	47.3	44.3	39.1	36.1	39.7	36.7	25.0
20	9.3	45.8	42.8	36.5	33.5	37.7	34.7	25.0
31.25	11.7	42.9	39.9	31.2	28.2	33.9	30.9	23.6
62.5	17.0	38.4	35.4	21.4	18.4	27.8	24.8	21.5
100	22.0	35.3	32.3	13.3	10.3	23.8	20.8	20.1

Specification	Value
Mutual Capacitance: (nF / 100m) Nominal	4.4
DC Resistance: (Ohms / 100m @ 20°C) Max	8.9
Delay Skew: (ns / 100m) Max	45
Velocity of Propagation: Non-Plenum (%): Plenum (%):	70 72
Input Impedance: (Ohms @ 1-100 MHz)	100 +/- 15

Overall Cable Temperature Rating -20°C to 60°C

Insulation Colors (16 AWG) Black Red White Green
Insulation Colors (CAT5E) Pair 1: White/Blue with Blue Pair 2: White/Orange with Orange Pair 3: White/Green with Green Pair 4: White/Brown with Brown

Overall Jacket Color Purple

Legend (Surface Ink Print) COLEMAN CABLE 99286 CLEAR SIGNAL SPEAKER PLUS DATA C(ETL)US (ETL CODE) CMR/CL3R 60C
CAT5E 24/4PR 350 MHZ UTP & 16/4 SPEAKER CABLE CMG FT4 *****FEET

This product complies with European Directive 2002/95/EC (RoHS)

The customer will accept all factory lengths and +/- 10 percent of total order requested.

Cable has a rip cord for easy jacket removal. The jacket is sequentially footmarked.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control, all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman Cable disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable.

Customer Name _____ Date Signed _____

Customer Approval _____

Specification Issue Date: December 3, 2008