



PRODUCT DATA SHEET

Controlled Document – Engineering Drive

1530 Shields Drive
Waukegan, IL 60085
Toll-Free (800) 323-9355
Fax: (847) 689-1192

PART NUMBER: 671802

DESCRIPTION: 18 AWG / 2 CONDUCTOR WITH SHIELD & DRAIN AUDIO CABLE

RATING: UL DUAL LISTED AS CM/CL2
UL RECOGNIZED COMPONENT AWM STYLE 2092

Construction Parameters:

		<u>Wall (in)*</u>	<u>OD (in)*</u>
Conductor:	18 AWG (16/30) Stranded Tinned Copper		0.047
Dielectric:	Polyethylene	0.018	0.083
Shielding:	Two (2) insulated conductors are twisted and wrapped overall in an Aluminum/Mylar Foil with Aluminum side out. Then a 20 AWG (10/30) Tinned Copper Drain Wire is added to outside of core.		0.169
Jacket:	PVC	0.030	0.229

Electrical Properties:

	<u>VALUE*</u>
Conductor Resistance (ohms/kft):	7.5
Pair Capacitance pf/ft @ 1 kHz)	24

Miscellaneous Information:

Wire Colors:	Black Natural
Jacket Color:	Chrome Gray
Jacket Print (Black):	COLEMAN CABLE E100316 18 AWG TYPE CM/CL2 (UL) OR AWM STYLE 2092
Applicable NEC Article:	725, 800 & 310
Flame rating:	UL-1581 Vertical Tray Flame Test
Max. Operating Volts:	300 RMS
Max. Operating Temperature:	60° C
Approximate Weight (lb/1000 ft):	29

This product complies with European Directive 2002/95/EC (RoHS)

On special orders the customer will accept all factory lengths and $\pm 10\%$ of total order requested.

The information presented here is, to the best of our knowledge, true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We reserve the right to review and modify all constructions to conform with the latest Regulatory requirement. We disclaim all liability in connection with the use of information contained herein or otherwise. This specification is propriety intellectual property of COLEMAN CABLE. Any information contained herein shall not be disclosed to any party without written consent of COLEMAN CABLE.

Company Name: _____

Customer Approval: _____

Date: _____

Issued: 07/11/08

* = Nominal value
By: PEP