## EEI Goleman Cable Inc.

## **PRODUCT DATA SHEET**

Controlled Document - Engineering Drive

1530 Shields Drive Waukegan, IL 60085 Toll-Free (800) 323-9355 Fax: (847) 689-1192

PART NUMBER: 823226

DESCRIPTION: 16/2 STRANDED TYPE SJOOW FLEXIBLE POWER CABLE

CONSTRUCTION: This cable consists of two bare copper insulated conductors cabled with fillers and an overall jacket.

APPROVALS: UL Standard 62, CSA 22.2 No. 49, NEC Article 400., MSHA

APPLICATION: 300V Portable Oil and Water Resistant Submersible Outdoor Flexible Power Cable

Construction Parameters:			
Conductor	16 AWG Bare Copper		
Stranding	26/30		
Insulation Material	EPDM		
Insulation Thickness	0.031" Nom.		
Insulated Conductor Diameter	0.121" Nom.		
Number of Conductors	2		
Lay Length	1.75" Nom.		
Filler Type	Paper or Jute	$I \setminus I \setminus \{ \cup \} \setminus \{ \cup $	
Separator/Wrap	Paper		
Jacket Material	CPE (chlorinated polyethylene)	\ \(\O\) /	
Jacket Thickness	0.034" Nom.		
Overall Cable Diameter	0.310" Nom.		
Approximate Cable Weight	60.0 Lbs/1M' Nom.		
Flame Rating	UL/CSA Horizontal Flame Test		
Electrical Properties:			
Temperature Rating	-40°C to 90°C		
Operating Voltage	300 V RMS Max.		
DC Resistance per Conductor @ 20°C	4.00 Ohms/1M' Nom.		
Insulation Colors	Black White		
Jacket Color	Black		
Legend (White Surface Ink Print)		CCI ROYAL ★★★★2/C 16 AWG (1.31mm²) SJOOW E54864-L (UL) 300V -40C to 90C CSA LL39753(L) FT2 WATER RESISTANT 07-KA070018-1 MSHA (Julian Date	
Ink Jet Legend (White)	P-07-KA070018-1 MSHA		
informational purposes only and does not create a binding obliq acceptance of a purchase order subject to Coleman Cable's sta Cable disclaims all liability in connection with the use of information	and +/- 10 percent of total order requested.  e, true and accurate. Since conditions of use are beyond Coleman Cable's conditions of use are beyond Coleman Cable's condition or liability on Coleman Cable or confer any rights on any customer. The andard terms and conditions contained therein, including without limitation Co	e sale of product(s) is conditioned upon	
	D 0:		
Customer Name	Date Signed		
Customer Approval			

Specification Issue Date: March 23, 2009