





300 S. DAYTON ST. DAVISON, MI 48423 PH: 810-653-9626 FAX:810-654-2616

*This Part requires two clamps, part number 128-300. See additional drawing for information on these clamps.

NOTES:
- SOME HIDDEN LINES NOT SHOWN
-BREAK ALL SHARP CORNERS
-REPORT ALL CHANGES TO

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF FERNCO, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF FERNCO, INC.

	Part Weight	2.47 lbs.	Т
	Min/Max Temp.	-30/140 Degrees F	.X=
	Pressure Tested	4.3 PSI	
	Material	Flexible PVC	
	Installation Torque	60" Lbs.	UNLESS
	Conforms to ASTM	D5926, C1173	LIN UTO
	Box Quantity	10	INCH
	Clamps used	300 Series	
			3DD V V

TOLERANCES: X= Fractional ± $.XX = \pm .02$ $.XXX = \pm .030$ $ANG = \pm 0.5$ ESS OTHERWISE SPECIFIED

DO NOT SCALE DRAWING

3RD ANGLE PROJECTION CHECKER:

DESCRIPTION:

Coupling 6" Ductile Iron, A/C Fibre x 6" Ductile Iron, A/C Fibre

1055-66

SCALE not to scale D. Brady 2/1/2007 SHEET 1 OF 1